

**SCHOTTKY BARRIER RECTIFIER**

**VOLTAGE RANGE 100 Volts CURRENT 8.0 Amperes**

**FEATURES**


- \* Low switching noise
- \* Low forward voltage drop
- \* Low thermal resistance
- \* High current capability
- \* High surge capability
- \* High reliability

**MECHANICAL DATA**

- \* Case: DO277 molded plastic
- \* Lead: MIL-STD-202E method 208C guaranteed
- \* Mounting position: Any
- \* Halogen free

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Ratings at 25 °C ambient temperature unless otherwise specified.  
Single phase, half wave, 60 Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.



**MAXIMUM RATINGS (@ TA=25 °C unless otherwise noted)**

RATINGS	SYMBOL	SR8100P	UNITS
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	100	Volts
Maximum RMS Voltage	$V_{RMS}$	70	Volts
Maximum DC Blocking Voltage	$V_{DC}$	100	Volts
Maximum Average Forward Rectified Current at $T_C=115^{\circ}C$	$I_O$	8.0	Amps
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	$I_{FSM}$	150	Amps
Typical Thermal Resistance (Note 1)	$R_{\theta JC}$	2.5	$^{\circ}C/W$
	$R_{\theta JA}$	60	
Typical Junction Capacitance (Note 3)	$C_J$	450	pF
Operating Temperature Range	$T_J$	175	$^{\circ}C$
Storage Temperature Range	$T_{STG}$	-55 to + 175	$^{\circ}C$

**ELECTRICAL CHARACTERISTICS (@ TA=25 °C unless otherwise noted)**

CHARACTERISTICS	SYMBOL	SR8100P	UNITS
Maximum Instantaneous Forward Voltage at 8.0A DC	$V_F$	.80	Volts
Maximum Average Reverse Current at Rated DC Blocking Voltage	$I_R$	10	$\mu A$
		2.5	$\mu A$

NOTES : 1. Thermal Resistance : Heat-sink mounted.  
2. Measured at 1 MHz and applied reverse voltage of 4.0 volts.  
3. "Fully ROHS compliant", "100% Sn plating (Pb-free)".

2015-10  
REV: O

RATING AND CHARACTERISTICS CURVES ( SR8100P )




FIG.1 TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2 TYPICAL REVERSE CHARACTERISTICS




FIG.3 TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4 TYPICAL JUNCTION CAPACITANCE





FIG.5 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT

Recommendation of Mounting Pad Layout



Dimensions in millimeters

# REEL TAPING SPECIFICATIONS FOR SURFACE MOUNT DEVICES-FLAT MELF ( DO-277 )





Fig.: Configuration of FLAT MELF TAPING  
(DO-277)

ITEM	SYMBOL	DO-277 mm(inch)	
Carrier width	A	5.45 ± 0.1 (0.179 ± 0.004)	
Carrier length	B	6.80 ± 0.1 (0.268 ± 0.004)	
Carrier depth	C	1.33 ± 0.1 (0.052 ± 0.004)	
Sprocket hole	d	1.5 ± 0.1 (0.059 ± 0.004)	
Reel outside diameter	D	178 ± 2.0 (7.0 ± 0.079)	
Reel inner diameter	D1	50 Min.	
Feed hole diameter	D2	13 ± 0.5 (0.512 ± 0.020)	
Stroket hole position	E	1.75 ± 0.1 (0.069 ± 0.004)	
Punch hole position	F	5.50 ± 0.05 (0.217 ± 0.002)	
Punch hole pitch	P	8.0 ± 0.1 (0.315 ± 0.004)	
Sprocket hole pitch	P0	4.0 ± 0.1 (0.157 ± 0.004)	
Embossment center	P1	2.00 ± 0.05 (0.079 ± 0.002)	
Totall tape thickness	T	0.28 ± 0.02 (0.011 ± 0.001)	
Tape width	W	12.00 ± 0.3 (0.472 ± 0.012)	12.00 - 0.1 (0.472 - 0.004)
Reel width	W1	16.8 ± 2.0 (0.661 ± 0.079)	


Note: 1.Devices are packed in accordance with EIA standard RS-481-A and specification given above.

1. BOX




Packing Code	L (mm)	W (mm)	H (mm)
-T/W	338	338	40

2. REEL



Packing Code	D (mm)
-T/W	330

3. CARTON




Packing Code	L (mm)	W (mm)	H (mm)
-T/W	360	355	360

## PACKAGING OF DIODE AND BRIDGE RECTIFIERS

### REEL PACK

PACKAGE	PACKING CODE	EA PER REEL	EA PER INNER BOX	COMPONENT SPACE (mm)	TAPE SPACE (mm)	REEL DIA (mm)	CARTON SIZE (mm)	EA PER CARTON	GROSS WEIGHT(Kg)
DO-277	-T/W	5,000	10,000	---	---	330	360*355*360	80,000	15.29

## Marking Description



## DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.