



SURFACE MOUNT BARRIER RECTIFIER

SRB820 THRU SRB8100

VOLTAGE RANGE

20 to 100 Volts

CURRENT


8.0 Ampere

FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-O
- Metal silicon junction majority carrier conduction
- Low power loss, high efficiency
- High current capability, low forward voltage drop
- High surge capacity
- For use in low voltage high frequency inverters, Free wheeling ,and polarity protection applications
- Guardring for over voltage protection
- High temperature soldering in accordance with CECC 802/Reflow guaranteed

MECHANICAL DATA

- Case: JEDEC TO-263AB molded Plastic body
- Terminals: Lead solderable per MIL-STD-750, Method 2026
- Polarity: As marked
- Mounting Position: Any
- Weight: 0.06 ounce, 1.7 gram



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified.
- Single phase, half wave,60Hz, resistive or inductive load
- For capacitive load, derate current by 20%

		SYMBOLS	SRB820	SRB830	SRB835	SRB840	SRB845	SRB850	SRB860	SRB880	SRB8100	UNIT
Maximum Repetitive Peak Reverse Voltage		V _{RRM}	20	30	35	40	45	50	60	80	100	Volts
Maximum RMS Voltage		V _{RMS}	14	21	25	28	32	35	42	56	70	Volts
Maximum DC Blocking Voltage		V _{DC}	20	30	35	40	45	50	60	80	100	Volts
Maximum Average Forward Rectified Current at T _C =100℃		I _(AV)	8.0									Amps
Peak Forward Surge Current 8.3mS single half sine-wave superimposed on rated load (JEDEC method)		I _{FSM}	150									Amps
Maximum Forward Voltage at 8.0A per element		V _F	0.55			0.75			0.85			Volts
Maximum DC Reverse Current at rated DC Blocking Voltage per element	T _C = 25℃	I _R	0.5									mA
	T _C = 100℃		50									
Typical Junction Capacitance (Note 2)		C _J	400									pF
Typical thermal Resistance (Note1)		R _{ΘJL}	3.0									℃/W
Operating and Storage Temperature Range		T _J , T _{STG}	(-55 to +150)									℃

Notes:

1. Thermal Resistance Junction to CASE
2. Measured at $V_R=4V$ and $f=1\text{MHz}$



SURFACE MOUNT BARRIER RECTIFIER

SRB820 THRU SRB8100

VOLTAGE RANGE	20 to 100Volts
CURRENT	8.0 Ampere

RATING AND CHARACTERISTIC CURVES SRB820 THRU SRB8100

FIG.1-TYPICAL FORWARD CURRENT
DERATING CURVE




FIG.3-TYPICAL INSTANTANEOUS
FORWARD CHARACTERISTIC




FIG.2-TYPICAL REVERSE
CHARACTERISTICS




FIG.4-MAXIMUM NON-REPETITIVE
SURGE CURRENT




FIG.5-TYPICAL JUNCTION
CAPACITANCE

