

100A 650V Trench Fieldstop IGBT with anti-parallel diode SRE100N065FSUD8
General Description

The SRE100N065FSUD8 is a Field Stop Trench IGBT with anti-parallel diode, which offers ultra-low switching losses, high energy efficiency for switching applications such as PFC, Power Supply, Inverter, etc.

The SRE100N065FSUD8 package is TO-247.

Features

- High Breakdown Voltage to 650V
- Advanced Trench Fieldstop technology
 - Ultra low E_{off}
 - High Ruggedness, Temperature Stability
 - Easy Parallel Switching Capability due to Positive Temperature Coefficient in $V_{CE(SAT)}$
- Low $V_{CE(SAT)}$
- Enhanced Avalanche Capability

Application

- Inverter
- Uninterruptible power supplies
- PFC application
- Converter with high switching frequency


Symbol


Figure 1 Symbol of SRE100N065FSUD8



Package Type


Figure 2 Package Type of SRE100N065FSUD8

Ordering Information


Package	Part Number	Marking ID	Packing Type
	Green	Green	
TO-247	SRE100N065FSUD8T-G	SRE100N065FSUD8TG	Tube

100A 650V Trench Fieldstop IGBT with anti-parallel diode SRE100N065FSUD8
Absolute Maximum Ratings

Parameter		Symbol	Rating	Unit
Collector-emitter Voltage		V_{CES}	650	V
Gate-emitter Voltage		V_{GES}	± 20	V
Transient Gate-emitter Voltage ($t_p \leq 10\mu s$)			± 30	V
Continuous Collector Current	$T_C=25\text{ }^\circ\text{C}$	I_C	125	A
	$T_C=100\text{ }^\circ\text{C}$		100	
Pulsed Collector Current, Limited by T_{Jmax}		I_{CM}	400	A
Diode Continuous Collector Current	$T_C=25\text{ }^\circ\text{C}$	I_F	100	A
	$T_C=100\text{ }^\circ\text{C}$		80	
Diode Pulsed Current, Limited by T_{Jmax}		I_{FM}	320	A
Power Dissipation	$T_C=25\text{ }^\circ\text{C}$	P_{tot}	328	W
	$T_C=100\text{ }^\circ\text{C}$		131	
Operating Junction Temperature Range		T_J	-40 ~ 150	$^\circ\text{C}$
Storage Temperature Range		T_{STG}	-55 ~ 150	$^\circ\text{C}$
Lead Temperature (Soldering, 10 sec)		T_{LEAD}	260	$^\circ\text{C}$

Thermal Resistance





Parameter	Symbol	Min.	Typ.	Max.	Unit
IGBT Thermal Resistance, Junction-to-Case	R_{thJC}	-	-	0.38	$^\circ\text{C/W}$
Diode Thermal Resistance, Junction-to-Case	R_{thJC}	-	-	0.45	
Thermal Resistance, Junction-to-Ambient	R_{thJA}	-	-	40	





100A 650V Trench Fieldstop IGBT with anti-parallel diode SRE100N065FSUD8
Electrical Characteristics
 $T_J = 25\text{ }^\circ\text{C}$, unless otherwise specified.





Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit	
Statistic Characteristics							
Collector-emitter Breakdown Voltage	BV_{CES}	$V_{GE}=0V, I_C=250\mu A$	650			V	
Gate Threshold Voltage	$V_{GE(th)}$	$V_{CE}=V_{GE}, I_C=250\mu A$	4.0	4.8	6.0	V	
Collector-emitter saturation voltage	V_{CEsat}	$V_{GE}=15V, I_C=100A,$ $T_J=25\text{ }^\circ\text{C}$		1.46	2.0	V	
		$T_J=125\text{ }^\circ\text{C}$		1.68		V	
		$T_J=150\text{ }^\circ\text{C}$		1.75		V	
Zero Gate Voltage Collector Current	I_{CES}	$V_{CE}=650V, V_{GE}=0V$ $T_J=25\text{ }^\circ\text{C}$		0.1	40	μA	
		$T_J=150\text{ }^\circ\text{C}$			1	mA	
Gate-emitter Leakage Current	Forward	I_{GESF}	$V_{GE}=20V, V_{CE}=0V$		100	nA	
	Reverse	I_{GESR}	$V_{GE}=-20V, V_{CE}=0V$		-100	nA	
Dynamic Characteristics							
Input Capacitance	C_{IES}	$V_{CE}=25V, V_{GE}=0V,$ $f=1\text{ MHz}$		3750		pF	
Output Capacitance	C_{OES}			350			
Reverse Transfer Capacitance	C_{RES}			40			
Gate Resistance	R_G	$f=1\text{ MHz, Open Drain}$		1.7		Ω	
Turn-on Delay Time	$t_{d(on)}$	$T_J=25\text{ }^\circ\text{C}$ $V_{CC}=400V, I_C=100A$ $R_G=15\Omega, V_{GE}=0/15V$		50		ns	
Rise Time	t_r			110		ns	
Turn-off Delay Time	$t_{d(off)}$			300		ns	
Fall Time	t_f			68		ns	
Turn-on energy	E_{on}			5.85		mJ	
Turn-off energy	E_{off}			1.55		mJ	
Total switching energy	E_{ts}			7.4		mJ	
Turn-on Delay Time	$t_{d(on)}$		$T_J=150\text{ }^\circ\text{C}$ $V_{CC}=400V, I_C=100A$ $R_G=15\Omega, V_{GE}=0/15V$		45		ns
Rise Time	t_r				120		ns
Turn-off Delay Time	$t_{d(off)}$				395		ns
Fall Time	t_f			83		ns	
Turn-on energy	E_{on}			7.85		mJ	
Turn-off energy	E_{off}			2.55		mJ	
Total switching energy	E_{ts}			10.4		mJ	
Gate to Emitter Charge	Q_{GE}	$V_{CC}=400V, I_C=100A$ $V_{GE}=0\text{ to }15V$		65		nC	
Gate to Collector Charge	Q_{GC}			89			
Gate Charge Total	Q_G			215			

100A 650V Trench Fieldstop IGBT with anti-parallel diode SRE100N065FSUD8

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Reverse Diode Characteristics						
Drain-Source Diode Forward Voltage	V_F	$V_{GE}=0V, I_F=80A$ $T_J=25\text{ }^\circ\text{C}$		1.67	2.0	V
		$T_J=125\text{ }^\circ\text{C}$		1.50		
		$T_J=150\text{ }^\circ\text{C}$		1.43		
Reverse Recovery Time	t_{rr}	$T_J=25\text{ }^\circ\text{C}$		125		ns
Reverse Recovery Charge	Q_{rr}	$V_R=400V, I_F=100A$		1084		nC
Peak Reverse Recovery Current	I_{rrm}	$dI_F/dt=700A/\mu s$		18.5		A


Typical Performance Characteristics
Figure 3: IGBT FBSOA

 $I_C = f(V_{CE}); V_{GE} \geq 15/0V; T_j \leq 150\text{ }^\circ\text{C}$
Figure 4: IGBT transient thermal impedance

 $R_{th(j-c)} = f(t_p); \text{ duty cycle: } D = t_p/T$
Figure 5: Power dissipation

 $P_{tot} = f(T_c);$
Figure 6: Collector current vs. temperature

 $I_C = f(T_c); V_{GE} \geq 15V; T_j \leq 150\text{ }^\circ\text{C}$

100A 650V Trench Fieldstop IGBT with anti-parallel diode SRE100N065FSUD8
Figure 7: Typ. Output Characteristics

 $I_C = f(V_{CE}); T_j = 25\text{ }^\circ\text{C}; \text{parameter: } V_{GE}$
Figure 8: Saturation Voltage Characteristics

 $I_C = f(V_{CE}); T_j = 25\text{ }^\circ\text{C vs } 150\text{ }^\circ\text{C}$
Figure 9: IGBT switching energy losses

 $E = f(I_C); V_{CE} = 400\text{V}; T_j = 25\text{ }^\circ\text{C}; R_G = 15\text{ }\Omega$
Figure 10: IGBT switching energy losses

 $E = f(R_G); V_{CE} = 400\text{V}; T_j = 25\text{ }^\circ\text{C}; I_C = 100\text{A}$

100A 650V Trench Fieldstop IGBT with anti-parallel diode SRE100N065FSUD8
Figure 11: Typ. Collector Voltage vs. Temperature

Figure 12: Typ. emitter threshold voltage as a function of junction temperature

Figure 13: Typ. Gate Charge

Figure 14: Typ. Capacitances



100A 650V Trench Fieldstop IGBT with anti-parallel diode SRE100N065FSUD8

Figure 15: Collector-emitter Breakdown Voltage vs. temperature




$BV_{ces} = f(T_j)$;

Figure 16: Typ. diode forward current as a function of forward voltage





$I_F = f(V_{EC})$;


Figure 17: IGBT switching energy losses




$E = f(T_j)$; $V_{CE} = 400V$; $I_C = 100A$; $R_G = 15\Omega$


Test Circuits
1. Definition Switching times

2. Definition Switching losses


3. Definition Diode Switching Characteristics



4. Dynamic Test Circuit



Mechanical Dimensions
TO-247
Unit: mm


Symbol	Dimensions(mm)			Symbol	Dimensions(mm)		
	Min.	Typ.	Max.		Min.	Typ.	Max.
A	4.80	5.00	5.20	E2	-	5.00	-
A1	2.21	2.41	2.61	E3	-	2.50	-
A2	1.90	2.00	2.10	e	5.44(BSC)		
b	1.10	1.20	1.35	L	19.42	19.92	20.42
b1	-	2.00	-	L1	-	4.13	-
b2	-	3.00	-	P	3.50	3.60	3.70
c	0.55	0.60	0.75	P1	-	-	7.40
D	20.80	21.00	21.20	P2	-	2.50	-
D1	-	16.55	-	Q	-	5.80	-
D2	-	1.20	-	S	6.05	6.15	6.25
E	15.60	15.80	16.00	T	-	10.00	-
E1	-	13.30	-	U	-	6.20	-



Sanrise Technology Limited Company

<http://www.sanrise-tech.com>

IMPORTANT NOTICE

Shenzhen Sanrise Technology Co., LTD. reserves the right to make changes without further notice to any products or specifications herein. Shenzhen Sanrise Technology Co., LTD. does not assume any responsibility for use of any its products for any particular purpose, nor does Shenzhen Sanrise Technology Co., LTD. assume any liability arising out of the application or use of any its products or circuits. Shenzhen Sanrise Technology Co., LTD. does not convey any license under its patent rights or other rights nor the rights of others.

Main Site:

- Headquarter

Shenzhen Sanrise Technology Co., LTD.
A1206, Skyworth building, No. 008, gaoxinnan 1st Road,
Gaoxin District, Yuehai street, Nanshan District, ShenZhen,
P.R. China

Tel: +86-755-22953335

Fax: +86-755-22916878

- Shanghai Office

Shenzhen Sanrise Technology Co., LTD.
Rm.609, Building A, No. 666, Zhangheng Road,
Zhangjiang Hi-Tech Park, Shanghai, P.R.China

Tel: +86-21-68825918