

SRGPP3J

**GLASS PASSIVATED
FAST RECOVERY RECTIFIER**
VOLTAGE: 600V CURRENT: 3.0A




FEATURE

Molded case feature for auto insertion
High Switching Capability
Low leakage current
High surge capability
High temperature soldering guaranteed
250°C /10sec/0.375" lead length at 5 lbs tension
Glass Passivated chip

MECHANICAL DATA

Terminal: Plated axial leads solderable per
MIL-STD 202E, method 208C
Case: Molded with UL-94 Class V-0 recognized Flame
Retardant Epoxy
Polarity: color band denotes cathode
Mounting position: any

DO - 201AD



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(single-phase, half-wave, 60HZ, resistive or inductive load rating at 25°C, unless otherwise stated)

	SYMBOL	SRGPP3J	units
Maximum Recurrent Peak Reverse Voltage	V _{rrm}	600	V
Maximum RMS Voltage	V _{rms}	420	V
Maximum DC blocking Voltage	V _{dc}	600	V
Maximum Average Forward Rectified Current 3/8" lead length at T _a =55°C	I _{f(av)}	3.0	A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load	I _{fsm}	125.0	A
Maximum Instantaneous Forward Voltage at rated forward current at I _{f(av)} =3.5A	V _f	1.3	V
Maximum full load reverse current full cycle at T _L =75°C	I _{r(av)}	30	μA
Maximum DC Reverse Current at rated DC blocking voltage T _a =25°C T _L =55°C	I _r	5.0 100.0	μA μA
Typical Junction Capacitance (Note 1)	C _j	50.0	pF
Maximum Reverse Recovery Time (Note 2)	T _{rr}	90	nS
Storage and Operation Junction Temperature	T _{stg} , T _j	-55 to +150	°C

Note:

1. Measured at 1.0 MHz and applied voltage of 4.0Vdc
2. Test Condition I_f =0.5A, I_r =1.0A, I_{rr} =0.25A

RATINGS AND CHARACTERISTIC CURVES SRGPP3J

