

3.0A Surface Mount Schottky Rectifier

Features

- Low Profile in SMB Package
- High current capability, low forward voltage drop
- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- High temperature soldering guaranteed: 260° C/10 seconds, at terminals
- RoHS compliant



Mechanical Data

Case:	JEDEC DO-214AA, Molded plastic body
Terminals:	Solder plated, solderable per MIL-STD-750D, Method 2026
Polarity	Color band denotes the cathode end

Maximum Ratings & Electrical Characteristics ($T_{Ambient}=25^{\circ}C$ unless noted otherwise)

Symbols	Description	SS 32B	SS 33B	SS 34B	SS 35B	SS 36B	SS 38B	SS 39B	SS 310B	Unit	Conditions
VRRM	Maximum Repetitive Peak Reverse Voltage	20	30	40	50	60	80	90	100	V	
VRMS	Maximum RMS Voltage	14	21	28	35	42	56	63	70	V	
VDC	Maximum DC Blocking Voltage	20	30	40	50	60	80	90	100	V	
I(AV)	Maximum Average Forward Rectified Current (FIG.1)	3.0								A	
IFSM	Peak Forward Surge Current (JEDEC Method)	80.0								A	8.3ms single half sine-wave
VF	Maximum Instantaneous Forward Voltage at 3.0A	0.50			0.75		0.85			V	Pulse width=300μS, 1% duty cycle
IR	Maximum DC Reverse Current at Rated DC Blocking Voltage	0.5								mA	Tj = 25 °C
		20			10			Tj= 100 °C			
RθJA RθJL	Maximum Thermal Resistance, Junction to Ambient	17								° C/W	PCB mounted with copper pad area of 0.55 x 0.55" (14 x 14mm)
		55									
CJ	Typical Junction Capacitance (NOTE)	200								pf	VR=4V, f=1MHz
TJ	Operating Junction Temperature Range	-55 to +125			-55 to +150					° C	
TSTG	Storage Temperature Range	-55 to +150								° C	

3.0A Surface Mount Schottky Rectifier

SS32B - SS310B

Typical Characteristics Curves

Fig.1- Forward Current Derating Curve




Fig.2- Max. Non-Repetitive Forward Surge Current




Fig.3- Typical Forward Characteristics




Fig.4- Typical Reverse Characteristics






Fig.5- Typical Junction Capacitance



3.0A Surface Mount Schottky Rectifier

SS32B - SS310B

Dimensions in inches (mm)



How to contact us:

US HEADQUARTERS

28040 WEST HARRISON PARKWAY, VALENCIA, CA 91355-4162

Tel: (800) TAITRON (800) 824-8766 (661) 257-6060

Fax: (800) TAITFAX (800) 824-8329 (661) 257-6415

Email: taitron@taitroncomponents.com

Http://www.taitroncomponents.com

TAITRON COMPONENTS MEXICO, S.A .DE C.V.

BOULEVARD CENTRAL 5000 INTERIOR 5 PARQUE INDUSTRIAL ATITALAQUIA, HIDALGO C.P.

42970 MEXICO

Tel: +52-55-5560-1519

Fax: +52-55-5560-2190

TAITRON COMPONENTS INCORPORATED REPRESENTAÇÕES DO BRASIL LTDA

RUA DOMINGOS DE MORAIS, 2777, 2.ANDAR, SALA 24 SAÚDE - SÃO PAULO-SP 04035-001 BRAZIL

Tel: +55-11-5574-7949

Fax: +55-11-5572-0052

TAITRON COMPONENTS INCORPORATED, SHANGHAI REPRESENTATIVE OFFICE

CROSS REGION PLAZA, 899 LINGLING ROAD, SUITE 18C, SHANGHAI, 200030, CHINA

Tel: +86-21-5424-9942

Fax: +86-21-5424-9931