


Absolute maximum ratings


(Ta=25°C)

Symbol	Ratings		Unit
	NPN	PNP	
V _{CB0}	60	−60	V
V _{CEO}	60	−60	V
V _{EB0}	6	−6	V
I _C	2	−2	A
I _{CP}	4 (PW≤1ms, Du≤25%)	−4 (PW≤1ms, Du≤25%)	A
I _B	0.5	−0.5	A
P _T	4 (T _a =25°C)		W
	20 (T _c =25°C)		
T _j	150		°C
T _{stg}	−40 to +150		°C
θ _{j-c}	6.25		°C/W

Equivalent circuit diagram



Characteristic curves



Electrical characteristics

($T_a=25^\circ\text{C}$)

Symbol	NPN					PNP				
	Specification			Unit	Conditions	Specification			Unit	Conditions
	min	typ	max			min	typ	max		
I_{CBO}			10	μA	$V_{CB}=60\text{V}$			-10	μA	$V_{CB}=-60\text{V}$
I_{EBO}			5	mA	$V_{EB}=6\text{V}$			-5	mA	$V_{EB}=-6\text{V}$
V_{CEO}	60			V	$I_C=10\text{mA}$	-60			V	$I_C=-10\text{mA}$
h_{FE}	2000	5000	12000		$V_{CE}=4\text{V}$, $I_C=1\text{A}$	2000	4000	10000		$V_{CE}=-4\text{V}$, $I_C=-1\text{A}$
$V_{CE(sat)}$		1.1	1.5	V	$I_C=1\text{A}$, $I_B=2\text{mA}$		-1.2	-1.5	V	$I_C=-1\text{A}$, $I_B=-2\text{mA}$
$V_{BE(sat)}$		1.8	2.2	V			-1.9	-2.2	V	
t_{on}		0.5		μs	$V_{CC}\approx 30\text{V}$, $I_C=1\text{A}$, $I_B=\pm 2\text{mA}$		0.4		μs	$V_{CC}\approx -30\text{V}$, $I_C=-1\text{A}$, $I_B=\pm 2\text{mA}$
t_{stg}		4.5		μs			1.0		μs	
t_f		1.2		μs			0.4		μs	
f_T		50		MHz	$V_{CE}=12\text{V}$, $I_E=-0.1\text{A}$		100		MHz	$V_{CE}=-12\text{V}$, $I_E=0.1\text{A}$
C_{ob}		20		pF	$V_{CE}=10\text{V}$, $f=1\text{MHz}$		30		pF	$V_{CE}=-10\text{V}$, $f=1\text{MHz}$
V_{FEC}		1.3	1.8	V	$I_{FEC}=1\text{A}$		-1.3	-1.8	V	$I_{FEC}=-1\text{A}$

Characteristic curves

