


## Features

- Low saturation switching application
- Power amplifier
- High Voltage :  $V_{CEO} = -80V$  Min.
- Complement to STD1408PI


## PIN Connection



## Ordering Information

Type NO.	Marking	Package Code
STB1017PI	STB1017	TO-220F-3L

## Marking Diagram

	Column 1 : Manufacturer Column 2 : Production Information - Δ : Factory Management Code - YMDD : Date Code (Year, Month, Date) Column 3 : Device Code
--	---

## Absolute maximum ratings

Characteristic	Symbol	Rating	Unit
Collector-Base voltage	$V_{CBO}$	-80	V
Collector-Emitter voltage	$V_{CEO}$	-80	V
Emitter-base voltage	$V_{EBO}$	-5	V
Collector current	$I_C$	-4	A
	$I_{CP}^*$	-8	A(Pulse)
Collector Power dissipation ( $T_c = 25^\circ C$ )	$P_C$	15	W
Junction temperature	$T_j$	150	$^\circ C$
Storage temperature	$T_{stg}$	-55 ~ 150	$^\circ C$

\* : Single pulse,  $tp = 300 \mu s$

Characteristic		Symbol	Typ.	Max	Unit
Thermal resistance	Junction-case	$R_{th(J-C)}$	-	8.33	$^\circ C/W$
	Junction-ambient	$R_{th(J-a)}$	-	62.5	

## Electrical Characteristics

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector cut-off current	$I_{CBO}$	$V_{CB} = -80V, I_E = 0$	-	-	-10	$\mu A$
Emitter cut-off current	$I_{EBO}$	$V_{EB} = -5V, I_C = 0$	-	-	-10	$\mu A$
Collector-Emitter breakdown voltage	$V_{(BR)CEO}$	$I_C = -50mA, I_B = 0$	-80	-	-	V
DC current gain	$h_{FE}$	$V_{CE} = -5V, I_C = -0.5A$	120	-	240	-
		$V_{CE} = -5V, I_C = -3A$	40	-	-	-
Collector-Emitter saturation voltage	$V_{CE(sat)}$	$I_C = -3A, I_B = -0.3A$	-	-1.0	-1.7	V
Base-Emitter saturation voltage	$V_{BE(on)}$	$V_{CE} = -5V, I_B = -3A$	-	-1.0	-1.5	V
Transition frequency	$f_T$	$V_{CB} = -5V, I_C = -0.5A$	-	9	-	MHz
Collector output capacitance	$C_{ob}$	$V_{CB} = -10V, I_E = 0, f = 1MHz$	-	60	-	pF

\*  $h_{FE}$  rank : 120~240 Only

Electrical Characteristic Curves

Fig. 1  $P_C - T_a$




Fig. 2  $I_C - V_{BE}$




Fig. 3  $I_C - V_{CE}$




Fig. 4  $h_{FE} - I_C$




Fig. 5  $V_{CE(sat)} - I_C$





Fig. 6  $V_{BE(sat)} - I_C$



Electrical Characteristic Curves

Fig. 7  $C_{Ob} - V_{CB}$






Fig. 8 Safe Operating Area



## Outline Dimension



SYMBOL	MILLIMETERS			NOTE
	MINIMUM	NOMINAL	MAXIMUM	
A	-	-	4.60	
A1	2.45	2.50	2.55	
A2	1.95	2.00	2.05	
b	0.65	0.75	0.85	
b1	1.07	1.27	1.47	
C	0.40	0.50	0.60	
C1	2.70	2.80	2.90	
D	9.90	10.00	10.10	
E	28.00	-	28.60	
E1	15.50	15.60	15.70	
E2	12.30	12.40	12.50	
E3	9.15	9.20	9.25	
F	3.30	3.40	3.50	
G	3.10	3.20	3.30	
e	2.54 BSC			
L	12.40	-	13.00	
L1	3.46 BSC			

**The AUK Corp. products are intended for the use as components in general electronic equipment (Office and communication equipment, measuring equipment, home appliance, etc.).**

**Please make sure that you consult with us before you use these AUK Corp. products in equipments which require high quality and / or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, transportation, combustion control, all types of safety device, etc.). AUK Corp. cannot accept liability to any damage which may occur in case these AUK Corp. products were used in the mentioned equipments without prior consultation with AUK Corp..**

**Specifications mentioned in this publication are subject to change without notice.**