

Descriptions

- General purpose application
- Switching application

Features


- Large collector current : $I_C = 600\text{mA}$
- Low collector saturation voltage
- Complementary pair with STA2907AN

Ordering Information

Type NO.	Marking	Package Code
STC2222AN	STC2222A	TO-92N

Outline Dimensions

unit : mm



Absolute maximum ratings

Ta=25°C

Characteristic	Symbol	Ratings	Unit
Collector-base voltage	V _{CBO}	75	V
Collector-emitter voltage	V _{CEO}	40	V
Emitter-base voltage	V _{EBO}	5	V
Collector current	I _C	600	mA
Collector power dissipation	P _C	400	mW
Junction temperature	T _J	150	°C
Storage temperature range	T _{stg}	-55~150	°C

Electrical Characteristics

Ta=25°C

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-emitter breakdown voltage	BV _{CEO}	I _C =10mA, I _B =0	40	-	-	V
Collector cut-off current	I _{CBO}	V _{CB} =75V, I _E =0	-	-	50	nA
Emitter cut-off current	I _{EBO}	V _{EB} =5V, I _C =0	-	-	50	nA
DC current gain	h _{FE}	V _{CE} =10V, I _C =10mA	75	-	-	-
Collector-emitter saturation voltage	V _{CE(sat)}	I _C =150mA, I _B =15mA	-	-	0.4	V
Base-emitter voltage	V _{BE}	V _{CE} =10V, I _C =10mA	-	0.65	0.85	V
Transition frequency	f _T	V _{CE} =20V, I _C =20mA	-	200	-	MHz
Collector output capacitance	C _{ob}	V _{CB} =10V, I _E =0, f=1MHz	-	6.0	-	pF

Electrical Characteristic Curves

Fig. 1 $P_C - T_a$




Fig. 2 $I_C - V_{BE}$




Fig. 3 $I_C - V_{CE}$




Fig. 4 $V_{CE(sat)} - I_C$




Fig. 5 $h_{FE} - I_C$





Fig. 6 $h_{FE} - I_C$



The AUK Corp. products are intended for the use as components in general electronic equipment (Office and communication equipment, measuring equipment, home appliance, etc.).

Please make sure that you consult with us before you use these AUK Corp. products in equipments which require high quality and / or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, transportation, combustion control, all types of safety device, etc.). AUK Corp. cannot accept liability to any damage which may occur in case these AUK Corp. products were used in the mentioned equipments without prior consultation with AUK Corp..

Specifications mentioned in this publication are subject to change without notice.