


## Features

- Low saturation switching application
- Voltage regulator application
- Low saturation :  $V_{CE(SAT)}=0.4V$  Max.
- High Voltage :  $V_{CEO}=60V$  Min.

## PIN Connection



## Ordering Information

Type NO.	Marking	Package Code
STC401D	STC401□	TO-252

□ : Year & Week Code

## Absolute maximum ratings

Characteristic	Symbol	Ratings	Unit
Collector-Base voltage	$V_{CBO}$	80	V
Collector-Emitter voltage	$V_{CEO}$	60	V
Emitter-base voltage	$V_{EBO}$	5	V
Collector current	$I_C$	1	A(DC)
	$I_{CP}^*$	2	A(Pulse)
Collector dissipation	$P_C(T_a=25^\circ C)$	1	W
	$P_C(T_C=25^\circ C)$	10	
Junction temperature	$T_j$	150	$^\circ C$
Storage temperature	$T_{stg}$	-55~150	$^\circ C$

\* : Single pulse,  $t_p=300 \mu s$

## Electrical Characteristics

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base breakdown voltage	$BV_{CBO}$	$I_C=100\ \mu A, I_E=0$	80	-	-	V
Collector-Emitter breakdown voltage	$BV_{CEO}$	$I_C=1mA, I_B=0$	60	-	-	V
Emitter-Base breakdown voltage	$BV_{EBO}$	$I_E=10mA, I_C=0$	5	-	-	V
Collector cut-off current	$I_{CBO}$	$V_{CB}=60V, I_E=0$	-	-	0.1	$\mu A$
Emitter cut-off current	$I_{EBO}$	$V_{EB}=5V, I_C=0$	-	-	0.1	$\mu A$
DC current gain	$h_{FE}^*$	$V_{CE}=2V, I_C=100mA$	200	-	400	-
		$V_{CE}=2V, I_C=1A$	80	-	-	
Base-Emitter on voltage	$V_{BE(ON)}$	$V_{CE}=2V, I_C=500mA$	-	-	1.2	V
Collector-Emitter saturation voltage	$V_{CE(sat)}$	$I_C=500mA, I_B=50mA$	-	-	0.4	V
Collector output capacitance	$C_{ob}$	$V_{CB}=10V, I_E=0, f=1MHz$	-	10	-	pF
Transition frequency	$f_T$	$V_{CB}=10V, I_C=50mA$	-	160	-	MHz

\*  $h_{FE}$  rank : 200~400 Only

Electrical Characteristic Curves

Fig. 1  $P_C - T_a$




Fig. 2  $V_{CE} - I_C$




Fig. 3  $h_{FE} - I_C$




Fig. 4  $h_{FE} - I_C$




Fig. 5  $h_{FE} - I_C$






Fig. 6  $h_{FE} - I_C$




## Electrical Characteristic Curves


**Fig. 7**  $C_{ob} - V_{CB}$




**Fig. 8**  $I_C - V_{CE}$




**Fig. 9**  $f_T - I_C$



**Fig. 10** Safe operating Area




Outline Dimension



SYMBOL	MILLIMETERS			NOTE
	MINIMUM	NOMINAL	MAXIMUM	
A	6.40	6.60	6.80	
B	5.90	6.10	6.30	
C	5.04	5.34	5.64	
D	0.50	0.70	0.90	
E	2.50	2.70	2.90	
F	2.10	2.30	2.50	
H	0.96 MAX			
I	2.20	2.30	2.40	
J	0.40	0.50	0.60	
K	1.60	1.80	2.00	
L	0.40	0.50	0.60	
M	0.81	0.91	1.01	
O	0.80	0.90	1.00	
P	0.90	1.00	1.10	
Q	0.95 MAX			
R	0.60	0.80	1.00	

※Recommend PCB solder land [Unit: mm]



**The AUK Corp. products are intended for the use as components in general electronic equipment (Office and communication equipment, measuring equipment, home appliance, etc.).**

**Please make sure that you consult with us before you use these AUK Corp. products in equipments which require high quality and / or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, transportation, combustion control, all types of safety device, etc.). AUK Corp. cannot accept liability to any damage which may occur in case these AUK Corp. products were used in the mentioned equipments without prior consultation with AUK Corp..**

**Specifications mentioned in this publication are subject to change without notice.**