



STU/D428S


N-Channel Logic Level Enhancement Mode Field Effect Transistor

PRODUCT SUMMARY


V _{DSS}	I _D	R _{DS(ON)} (m Ω) Typ
40V	50A	8 @ V _{GS} = 10V
		10 @ V _{GS} = 4.5V

FEATURES


- Super high dense cell design for low R_{DS(ON)}.
- Rugged and reliable.
- Surface Mount Package.
- ESD Protected.



STU SERIES
TO-252AA(D-PAK)



STD SERIES
TO-251(I-PAK)



ABSOLUTE MAXIMUM RATINGS (Ta=25°C unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V _{DS}	40	V
Gate-Source Voltage	V _{GS}	± 20	V
Drain Current-Continuous @T _C =25 C ° -Pulsed ^a	I _D	50	A
	I _{DM}	100	A
Drain-Source Diode Forward Current	I _S	20	A
Maximum Power Dissipation @T _C =25 C°	P _D	50	W
Operating and Storage Temperature Range	T _J , T _{STG}	-55 to 175	°C

THERMAL CHARACTERISTICS

Thermal Resistance, Junction-to-Case	R θ JC	3	°C/W
Thermal Resistance, Junction-to-Ambient	R θ JA	50	°C/W

STU/D428S

ELECTRICAL CHARACTERISTICS (T_c=25 °C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ ^c	Max	Unit
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} = 0V, I _D = 250uA	40			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 32V, V _{GS} = 0V			1	uA
Gate-Body Leakage	I _{GSS}	V _{GS} = ±20V, V _{DS} = 0V			±10	uA
ON CHARACTERISTICS ^a						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250uA	1	1.7	3	V
Drain-Source On-State Resistance	R _{DS(ON)}	V _{GS} = 10V, I _D = 10A		8	10	m ohm
		V _{GS} = 4.5V, I _D = 6A		10	13	m ohm
On-State Drain Current	I _{D(ON)}	V _{DS} = 10V, V _{GS} = 10V	30			A
Forward Transconductance	g _{FS}	V _{DS} = 10V, I _D = 10A		26		S
DYNAMIC CHARACTERISTICS ^b						
Input Capacitance	C _{ISS}	V _{DS} = 20V, V _{GS} = 0V f = 1.0MHz		1505		pF
Output Capacitance	C _{OSS}			220		pF
Reverse Transfer Capacitance	C _{RSS}			150		pF
Gate resistance	R _g	V _{GS} = 0V, V _{DS} = 0V, f = 1.0MHz		0.3		ohm
SWITCHING CHARACTERISTICS ^b						
Turn-On Delay Time	t _{D(ON)}	V _{DD} = 15V I _D = 1 A V _{GS} = 10V R _{GEN} = 6 ohm		23		ns
Rise Time	t _r			19		ns
Turn-Off Delay Time	t _{D(OFF)}			85		ns
Fall Time	t _f			27		ns
Total Gate Charge	Q _g	V _{DS} = 15V, I _D = 10A, V _{GS} = 10V		28		nC
		V _{DS} = 15V, I _D = 10A, V _{GS} = 4.5V		12.5		nC
Gate-Source Charge	Q _{gs}	V _{DS} = 15V, I _D = 10A V _{GS} = 10V		3		nC
Gate-Drain Charge	Q _{gd}			6		nC

STU/D428S

ELECTRICAL CHARACTERISTICS ($T_c=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
DRAIN-SOURCE DIODE CHARACTERISTICS ^a						
Diode Forward Voltage	V_{SD}	$V_{GS} = 0V, I_S = 10A$		0.95	1.3	V

Notes

a. Pulse Test: Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$.

b. Guaranteed by design, not subject to production testing.




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current and Gate Voltage




Figure 4. On-Resistance Variation with Drain Current and Temperature

STU/D428S




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Breakdown Voltage Variation with Temperature




Figure 7. On-Resistance vs. Gate-Source Voltage




Figure 8. Body Diode Forward Voltage Variation with Source Current

STU/D428S




Figure 9. Capacitance




Figure 10. Gate Charge




Figure 11.switching characteristics




Figure 12. Maximum Safe Operating Area

STU/D428S




Figure 13. Switching Test Circuit




Figure 14. Switching Waveforms





Figure 15. Normalized Thermal Transient Impedance Curve

STU/D428S

PACKAGE OUTLINE DIMENSIONS

TO-251




SYMBOLS	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	2.20	2.40	0.087	0.095
A1	1.100	1.300	0.043	0.051
B1	0.650	1.050	0.026	0.041
b	0.500	0.900	0.020	0.035
b1	0.400	0.800	0.016	0.32
C	0.400	0.600	0.016	0.024
D	6.700	7.300	0.264	0.287
D1	5.400	5.650	0.213	0.222
E	6.40	6.650	0.252	0.262
e	2.100	2.500	0.083	0.098
F	0.400	0.600	0.016	0.024
L	7.000	8.000	0.276	0.315
L1	1.300	1.700	0.051	0.067
L2	0.700	0.900	0.028	0.035
L3	1.400	1.800	0.055	0.071

STU/D428S

PACKAGE OUTLINE DIMENSIONS

TO-252




SYMBOLS	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	2.25	2.35	0.089	0.093
A1	0.95	1.05	0.037	0.041
b	0.77	0.85	0.030	0.033
b1	0.84	0.94	0.033	0.037
b2	5.30	5.45	0.209	0.215
C	0.49	0.53	0.019	0.021
D	6.00	6.20	0.236	0.244
E	6.40	6.60	0.252	0.260
E1	3.18	3.67	0.125	0.145
e	2.29	BSC	0.090	BSC
H	9.70	10.10	0.382	0.398
L	1.425	1.625	0.056	0.064
L1	0.650	0.850	0.026	0.033
L2	0.600	REF .	0.024	REF .


STU/D428S

TO251 Tube/TO-252 Tape and Reel Data

TO-251 Tube




TO-252 Carrier Tape



UNIT: 6

PACKAGE	A0	B0	K0	D0	D1	E	E 1	E 2	P0	P1	P2	T
TO-252 (16 B I)	6.80 +0.1 -0.1	10.3 +0.1 -0.1	2.50 +0.1 -0.1	榎2	榎1.5 +0.1 -0	16.0 +0.3 -0.3	1.75 +0.1 -0.1	7.5 +0.15 -0.15	8.0 +0.1 -0.1	4.0 +0.1 -0.1	2.0 +0.15 -0.15	0.3 +0.05 -0.05

TO-252 Reel



UNIT: 6

TAPE SIZE	REEL SIZE	M	N	W	T	H	K	S	G	R	V
16 b	榎 330	榎330 1 0.5	榎97 1 1.0	17.0 + 1.5 - 0	2.2	榎13.0 + 0.5 - 0.2	10.6	2.0 10.5	---	---	---