

www.DataSheet4U.com

Self-excitation Type Feedback Control Switching Regulator


◆ Features

- . Power MOSFET devices
- . Feedback control for high output voltage precision
- . Driver circuit on-chip
- . Overcurrent protection circuit on-chip
- . Pin compatible with all other devices in the same series of devices with 110 to 280W power ratings
- . Higher oscillator frequency allows the use of smaller pulse transformers

◆ Applications


- . CRT/CTV power supplies
- . Office automation equipment power supplies

◆ Block Diagram



Package Dimensions

unit:mm



Pin Functions

- (1) Amplifier circuit control
- (2) Ground
- (3) TR1 gate
- (4) Drive voltage input
- (5) Starting voltage input
- (6) OCP setting level input
- (7) OCP input-voltage dependency detection input
- (8) TR1 source
- (9) TR1 source
- (11) TR1 drain
- (12) TR1 drain

Specifications

◆ Maximum Ratings at Ta=25°C, Tc=25°C unless otherwise specified

Parameter	Symbol	Conditions	Ratings	UNIT
Operating substrate temperature	T _C max	Recommended value is 105°C	115	°C
AC input voltage	V _{AC}	Specified test circuit	140	V _{rms}
Operating temperature	T _{opr}		-10 to +85	°C
Storage temperature	T _{stg}		-30 to +115	°C
Maximum output power	W _o max	Specified test circuit V _O =135V	180	W

(TR1)

Drain current	I _D		10	A
Pulse drain current	I _{D(Pulse)}		35	A
Drain reverse current	I _{DR}		10	A
Gate-source voltage	V _{GSS}		±30	V
Allowable power dissipation	P _D		100	W
Chip junction temperature	T _j max		150	°C

(ZD1)

Allowable power dissipation	P _{ZD1}		500	mW
Chip junction temperature	T _{j(ZD1)} max		125	°C

◆ Recommended operating ranges at Ta=25°C

Parameter	Symbol	Conditions	Ratings	UNIT
Pin 4 input voltage	V ₄		±8 to ±24	V
Oscillator frequency	f _{OSC}		20 to 100	kHz

◆ Operating characteristics at Ta=25°C, Tc=25°C

(unless otherwise specified, specified test circuits)

Parameter	Symbol	Conditions	min	Typ	max	UNIT
(TR1)						
Drain-source breakdown voltage	V _{(BR)DSS}	I _D =1mA, V _{GS} =0V	500			V
Gate-source cutoff voltage	V _{GS(off)}	I _D =1mA, V _{DS} =10V	2.5	3.5	5.0	V
ON resistance	R _{DS(on)}	I _D =5A, V _{GS} =10V		0.6	0.9	Ω
Input capacitance	C _{iss}	V _{DS} =25V, V _{GS} =0V, f=1MHz		1400		pF
(ZD1)						
Zener voltage	V _Z	I _Z =5mA	23.7		26.3	V

◆ Series organization

www.DataSheet4U.com

These devices form a series with varying output power ratings

Type No.	Maximum ratings					Operating characteristics		
	V _{DSS} [V]	T _{stg} [°C]	T _C max [°C]	T _j max [°C]	I _D [A]	Input voltage [V]	Output power [W]	ON resistance [Ω]
STK73902	500	-30 to +115	+115	+150	6.0	85 to 132	110	1.4
STK73903					10.0		180	0.6
STK73904					12.0		210	0.55
STK73905					15.0		280	0.3
STK73906	900	-30 to +115	+115	+150	3.0	170 to 264	110	5.0
STK73907					5.0		180	3.0
STK73908					6.0		210	2.0
STK73909					8.0		280	1.2