

SWITCHING REGULATOR APPLICATIONS

Features


- High Voltage: $BV_{DSS}=500V(\text{Min.})$
- Low C_{rSS} : $C_{rSS}=8.4pF(\text{Typ.})$
- Low gate charge : $Q_g=17nC(\text{Typ.})$
- Low $R_{DS(on)}$: $R_{DS(on)}=1.5\Omega(\text{Max.})$

Ordering Information

Type NO.	Marking	Package Code
STK830P	STK830	TO-220AB-3L

Outline Dimensions

unit : mm



Absolute maximum ratings

(Tc=25°C)

Characteristic	Symbol	Rating	Unit	
Drain-source voltage	V_{DSS}	500	V	
Gate-source voltage	V_{GSS}	± 30	V	
Drain current (DC)	I_D	$T_C=25^\circ C$	4.5	A
		$T_C=100^\circ C$	2.7	A
Drain current (Pulsed) *	I_{DM}	18	A	
Drain power dissipation	P_D	71	W	
Avalanche current (Single) ②	I_{AS}	4.5	A	
Single pulsed avalanche energy ②	E_{AS}	250	mJ	
Avalanche current (Repetitive) ①	I_{AR}	4.5	A	
Repetitive avalanche energy ①	E_{AR}	5.0	mJ	
Junction temperature	T_J	150	°C	
Storage temperature range	T_{stg}	-55~150	°C	

* Limited by maximum junction temperature

Characteristic		Symbol	Typ.	Max	Unit
Thermal resistance	Junction-case	$R_{th(J-C)}$	-	1.75	°C/W
	Junction-ambient	$R_{th(J-A)}$	-	62.5	

Electrical Characteristics

(T_c=25°C)

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Drain-source breakdown voltage	V _{(BR)DSS}	I _D =250 μA, V _{GS} =0V	500	-	-	V
Gate threshold voltage	V _{GS(th)}	I _D =250 μA, V _{DS} =V _{GS}	2.0	-	4.0	V
Drain-source cut-off current	I _{DSS}	V _{DS} =500V, V _{GS} =0V	-	-	10	μA
Gate leakage current	I _{GSS}	V _{DS} =0V, V _{GS} =±30V	-	-	±100	nA
Drain-source on-resistance ④	R _{DS(on)}	V _{GS} =10V, I _D =2.25A	-	-	1.5	Ω
Forward transfer conductance ④	g _{fs}	V _{DS} =10V, I _D =2.25A	-	3.3	-	S
Input capacitance	C _{iss}	V _{GS} =0V, V _{DS} =25V f=1 MHz	-	550	830	pF
Output capacitance	C _{oss}		-	46	70	
Reverse transfer capacitance	C _{rss}		-	8.4	15	
Turn-on delay time	t _{d(on)}	V _{DD} =250V, I _D =4.5A R _G =12Ω	-	12	-	ns
Rise time	t _r		-	46	-	
Turn-off delay time	t _{d(off)}		-	50	-	
Fall time	t _f		-	48	-	
Total gate charge	Q _g	V _{DS} =250V, V _{GS} =10V I _D =4.5A	-	17	26	nC
Gate-source charge	Q _{gs}		-	2.6	4.0	
Gate-drain charge	Q _{gd}		-	5.8	9.0	

Source-Drain Diode Ratings and Characteristics

(T_c=25°C)

Characteristic	Symbol	Test Condition	Min	Typ	Max	Unit
Source current (DC)	I _S	Integral reverse diode in the MOSFET	-	-	4.5	A
Source current (Pulsed) ①	I _{SP}		-	-	18	
Forward voltage ④	V _{SD}	V _{GS} =0V, I _S =4.5A	-	-	1.4	V
Reverse recovery time	t _{rr}	I _S =4.5A, V _{GS} =0V dI _S /dt=100A/μs	-	188	-	ns
Reverse recovery charge	Q _{rr}		-	2.1	-	μC

Note ;

- ① Repetitive rating : Pulse width limited by maximum junction temperature
- ② L=20mH, I_{AS}=4.5A, V_{DD}=50V, R_G=27Ω
- ③ Pulse Test : Pulse width≤ 400 μs, Duty cycle≤ 2%
- ④ Essentially independent of operating temperature

Electrical Characteristic Curves

Fig. 1 $I_D - V_{DS}$




Fig. 2 $I_D - V_{GS}$




Fig. 3 $R_{DS(on)} - I_D$




Fig. 4 $I_S - V_{SD}$




Fig. 5 Capacitance - V_{DS}




Fig. 6 $V_{GS} - Q_G$




Fig. 7 $V_{(BR)DSS} - T_J$




Fig. 8 $R_{DS(on)} - T_J$




Fig. 9 $I_D - T_C$




Fig. 10 Safe Operating Area




Fig. 11 Gate Charge Test Circuit & Waveform




Fig. 12 Switching Time Test Circuit & Waveform




Fig. 13 E_{AS} Test Circuit & Waveform





Fig. 14 Peak Diode Recovery dv/dt Test Circuit & Waveform



The AUK Corp. products are intended for the use as components in general electronic equipment (Office and communication equipment, measuring equipment, home appliance, etc.).

Please make sure that you consult with us before you use these AUK Corp. products in equipments which require high quality and / or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, transportation, combustion control, all types of safety device, etc.). AUK Corp. cannot accept liability to any damage which may occur in case these AUK Corp. products were used in the mentioned equipments without prior consultation with AUK Corp..

Specifications mentioned in this publication are subject to change without notice.