


ST KSB564

PNP Silicon Epitaxial Planar Transistor

Audio Frequency Power amplifier applications.

The transistor is subdivided into three group, O, Y and G according to its DC current gain.

On special request, these transistors can be manufactured in different pin configurations.




1. Emitter 2. Collector 3. Base

TO-92 Plastic Package
Weight approx. 0.19g

Absolute Maximum Ratings (Ta=25°C)

	Symbol	Value	Unit
Collector Base Voltage	$-V_{CBO}$	30	V
Collector Emitter Voltage	$-V_{CEO}$	25	V
Emitter Base Voltage	$-V_{EBO}$	5	V
Collector Current	$-I_C$	800	mA
Power Dissipation	P_{tot}	625	mW
Junction Temperature	T_j	150	°C
Storage Temperature Range	T_s	-55 to +150	°C



SEMTECH ELECTRONICS LTD.
(Subsidiary of Sino-Tech International Holdings Limited, a company
listed on the Hong Kong Stock Exchange, Stock Code: 724)




Dated : 07/12/2002


ST KSB564

Characteristics at $T_{amb}=25^{\circ}C$

	Symbol	Min.	Typ.	Max.	Unit
DC Current Gain at $-V_{CE}=1V$, $-I_C=100mA$					
Current Gain Group O	h_{FE}	70	-	140	-
Y	h_{FE}	120	-	240	-
G	h_{FE}	200	-	400	-
Collector Emitter Breakdown Voltage at $-I_C=10mA$	$-V_{(BR)CEO}$	25	-	-	V
Collector Base Breakdown Voltage at $-I_C=100\mu A$	$-V_{(BR)CBO}$	30	-	-	V
Emitter Base Breakdown Voltage at $-I_E=100\mu A$	$-V_{(BR)EBO}$	5	-	-	V
Collector Cutoff Current at $-V_{CB}=30V$	$-I_{CBO}$	-	-	0.1	μA
Collector Saturation Voltage at $-I_C=500mA$, $-I_B=50mA$	$-V_{CE(sat)}$	-	-	0.5	V
Base Saturation Voltage at $-I_C=500mA$, $-I_B=50mA$	$-V_{BE(sat)}$	-	-	1.2	V
Collector Output Capacitance at $-V_{CB}=6V$, $f=1MHz$	C_{OB}	-	18	-	pF
Transition Frequency at $-V_{CE}=6V$, $-I_C=10mA$	f_T	-	110	-	MHz



SEMTECH ELECTRONICS LTD.
(Subsidiary of Sino-Tech International Holdings Limited, a company
listed on the Hong Kong Stock Exchange, Stock Code: 724)



Dated : 07/12/2002