





N-Channel Enhancement Mode Field Effect Transistor

PRODUCT SUMMARY

V _{DSS}	I _D	R _{DS(ON)} (mΩ) Max
55V	5 A	50 @ V _{GS} = 10V
		70 @ V _{GS} = 4.5V

FEATURES

- Super high dense cell design for low R_{DS(ON)}.
- Rugged and reliable.
- Surface Mount Package.



ABSOLUTE MAXIMUM RATINGS (T_A=25°C unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage Rating	V _{spike} ^d	60	V
Drain-Source Voltage	V _{DS}	55	V
Gate-Source Voltage	V _{GS}	±20	V
Drain Current-Continuous @ T _J =25°C -Pulsed ^a	I _D	5	A
	I _{DM}	20	A
Drain-Source Diode Forward Current ^b	I _S	1.7	A
Maximum Power Dissipation ^b	P _D	2.5	W
Operating Junction and Storage Temperature Range	T _J , T _{STG}	-55 to 150	°C

THERMAL CHARACTERISTICS

Thermal Resistance, Junction-to-Ambient ^a	R _{θJA}	50	°C/W
--	------------------	----	------

STM4550

ELECTRICAL CHARACTERISTICS (T_A=25 °C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ ^c	Max	Unit
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250uA	55			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =44V, V _{GS} =0V			1	uA
Gate-Body Leakage	I _{GSS}	V _{GS} = ±20V, V _{DS} =0V			±100	nA
ON CHARACTERISTICS ^a						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D = 250uA	1	1.8	3	V
Drain-Source On-State Resistance	R _{DS(ON)}	V _{GS} =10V, I _D = 5A		40	50	m ohm
		V _{GS} =4.5V, I _D = 3A		50	70	m ohm
On-State Drain Current	I _{D(ON)}	V _{DS} = 10V, V _{GS} = 10V	20			A
Forward Transconductance	g _{FS}	V _{DS} = 10V, I _D =5A		22		S
DYNAMIC CHARACTERISTICS ^b						
Input Capacitance	C _{ISS}	V _{DS} =20V, V _{GS} = 0V f =1.0MHz		689		pF
Output Capacitance	C _{OSS}			92		pF
Reverse Transfer Capacitance	C _{RSS}			55		pF
SWITCHING CHARACTERISTICS ^b						
Turn-On Delay Time	t _{D(ON)}	V _{DD} = 30V I _D = 1A V _{GS} = 10V R _{GEN} = 6 ohm		11		ns
Rise Time	t _r			10.9		ns
Turn-Off Delay Time	t _{D(OFF)}			23		ns
Fall Time	t _f			5		ns
Total Gate Charge	Q _g	V _{DS} =15V, I _D = 5A, V _{GS} =10V		13.3		nC
		V _{DS} =15V, I _D = 5A, V _{GS} =4.5V		6.2		nC
Gate-Source Charge	Q _{gs}	V _{DS} =15V, I _D = 5A V _{GS} =10V		1.7		nC
Gate-Drain Charge	Q _{gd}			2.8		nC

STM4550

ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ ^c	Max	Unit
DRAIN-SOURCE DIODE CHARACTERISTICS ^b						
Diode Forward Voltage	V_{SD}	$V_{GS} = 0\text{V}$, $I_S = 1.7\text{A}$		0.78	1.2	V

Notes

a.Surface Mounted on FR4 Board, $t \leq 10\text{sec}$.

b.Pulse Test:Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$.

c.Guaranteed by design, not subject to production testing.

d.Guaranteed when external $R_g=6\text{ ohm}$ and $t_f < t_f \text{ max}$.




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current and Gate Voltage






Figure 4. On-Resistance Variation with Drain Current and Temperature

STM4550




Tj, Junction Temperature (°C)

Figure 5. Gate Threshold Variation with Temperature




Tj, Junction Temperature (°C)

Figure 6. Breakdown Voltage Variation with Temperature



VGS, Gate-Source Voltage (V)

Figure 7. On-Resistance vs. Gate-Source Voltage



VSD, Body Diode Forward Voltage (V)

Figure 8. Body Diode Forward Voltage Variation with Source Current

STM4550




Figure 9. Capacitance




Figure 10. Gate Charge




Figure 11. switching characteristics




Figure 12. Maximum Safe Operating Area

STM4550




Figure 13. S switching Test Circuit




Figure 14. Switching Waveforms





Figure 15. Normalized Thermal Transient Impedance Curve

STM4550

PACKAGE OUTLINE DIMENSIONS

SO-8




SYMBOLS	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	1.35	1.75	0.053	0.069
A1	0.10	0.25	0.004	0.010
D	4.80	4.98	0.189	0.196
E	3.81	3.99	0.150	0.157
H	5.79	6.20	0.228	0.244
L	0.41	1.27	0.016	0.050
θ	0°	8°	0°	8°

STM4550

SO-8 Tape and Reel Data


SO-8 Carrier Tape



unit:mm

PACKAGE	A0	B0	K0	D0	D1	E	E1	E2	P0	P1	P2	T
SOP 8N 150mil	6.40	5.20	2.10	$\phi 1.5$ (MIN)	$\phi 1.5$ + 0.1 - 0.0	12.0 ± 0.3	1.75	5.5 ± 0.05	8.0	4.0	2.0 ± 0.05	0.3 ± 0.05

SO-8 Reel



UNIT:mm

TAPE SIZE	REEL SIZE	M	N	W	W1	H	K	S	G	R	V
12 mm	$\phi 330$	330 ± 1	62 ± 1.5	12.4 + 0.2	16.8 - 0.4	$\phi 12.75$ + 0.15	---	2.0 ± 0.15	---	---	---