

**SUPER FAST  
GLASS PASSIVATED RECTIFIERS**

REVERSE VOLTAGE - **100 to 200** Volts  
FORWARD CURRENT - **10** Amperes


**FEATURES**

- Glass passivated chip
- Superfast switching time for high efficiency
- Low forward voltage drop and high current capability
- Low reverse leakage current
- High surge capacity
- Plastic package has UL flammability classification 94V-0
- Soft recovery characteristic

**MECHANICAL DATA**

- Case : TO-220AB molded plastic
- Polarity : As marked on the body
- Weight : 0.08 ounces, 2.24 grams
- Mounting position : Any
- Max. mounting torque = 0.5 N.m (5.1 Kgf.cm)

**TO-220AB**



**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Ratings at 25°C ambient temperature unless otherwise specified.

CHARACTERISTICS	SYMBOL	STPRA1010CT	STPRA1020CT	UNIT
Maximum Recurrent Peak Reverse Voltage	VRRM	100	200	V
Maximum RMS Voltage	VRMS	70	140	V
Maximum DC Blocking Voltage	VDC	100	200	V
Maximum Average Forward Rectified Current @Tc=110°C	I(AV)	10		A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load	IFSM	55		A
Maximum forward Voltage IF=5A@TJ=25°C Pulse Width =300us Duty cycle IF=5A@TJ=125°C IF=10A@TJ=25°C IF=10A@TJ=125°C	VF	1.1 1.0 1.25 1.20		V
Maximum DC Reverse Current at Rated DC Blocking Voltage @TJ=25°C @TJ=100°C	IR	50 600		uA
Typical Junction Capacitance per element (Note 1)	CJ	25		pF
Maximum Reverse Recovery Time (Note 2)	TRR	30		ns
Typical Thermal Resistance (Note 3)	R $\theta$ JC	4.0		°C/W
Operating and Storage Temperature Range	TJ,TSTG	-55 to +150		°C

NOTES : 1.Measured at 1.0MHz and applied reverse voltage of 4.0V DC.  
2.Reverse Recovery Test Conditions:IF=0.5A,IR=1.0A,IRR 0.25A.  
3.Device mounted on 75 mm x 75 mm x 2 mm Cu Plate.

REV. 3, Sep-2010, KTGC19

FIG.1 - FORWARD CURRENT DERATING CURVE




FIG.2 - MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3 - TYPICAL REVERSE CHARACTERISTICS




FIG.4 - TYPICAL FORWARD CHARACTERISTICS





FIG.5 - TYPICAL JUNCTION CAPACITANCE



## **Important Notice and Disclaimer**

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.