



STPS2L25U


LOW DROP POWER SCHOTTKY RECTIFIER

MAIN PRODUCT CHARACTERISTICS

$I_F(AV)$	2 A
V_{RRM}	25 V
$T_j(max)$	150 °C
$V_F(max)$	0.375 V

FEATURES AND BENEFITS

- VERY LOW FORWARD VOLTAGE DROP FOR LESS POWER DISSIPATION
- OPTIMIZED CONDUCTION/REVERSE LOSSES TRADE-OFF WHICH MEANS THE HIGHEST EFFICIENCY IN THE APPLICATIONS



SMB
JEDEC DO-214AA

DESCRIPTION

Single Schottky rectifier suited to Switched Mode Power Supplies and high frequency DC to DC converters.

Packaged in SMB (JEDEC DO214-AA), this device is especially intended for use in parallel with MOS-FETs in synchronous rectification.

ABSOLUTE RATINGS (limiting values)

Symbol	Parameter		Value	Unit
V_{RRM}	Repetitive peak reverse voltage		25	V
$I_F(RMS)$	RMS forward current		10	A
$I_F(AV)$	Average forward current	$T_L = 125^\circ\text{C} \quad \delta = 0.5$	2	A
I_{FSM}	Surge non repetitive forward current	$t_p = 10 \text{ ms}$ Sinusoidal	75	A
I_{RRM}	Repetitive peak reverse current	$t_p = 2 \mu\text{s}$ square $F = 1\text{kHz}$	1	A
I_{RSM}	Non repetitive peak reverse current	$t_p = 100 \mu\text{s}$ square	1	A
T_{stg}	Storage temperature range		- 65 to + 150	°C
T_j	Maximum operating junction temperature *		150	°C
dV/dt	Critical rate of rise of reverse voltage		10000	V/ μs

* : $\frac{dP_{tot}}{dT_j} < \frac{1}{R_{th(j-a)}}$ thermal runaway condition for a diode on its own heatsink

STPS2L25U

THERMAL RESISTANCES

Symbol	Parameter	Value	Unit
$R_{th(j-l)}$	Junction to lead	25	°C/W

STATIC ELECTRICAL CHARACTERISTICS

Symbol	Tests Conditions	Tests Conditions	Min.	Typ.	Max.	Unit
I_R *	Reverse leakage current	$T_j = 25^{\circ}C$	$V_R = V_{RRM}$		90	μA
		$T_j = 125^{\circ}C$		15	30	mA
V_F *	Forward voltage drop	$T_j = 25^{\circ}C$	$I_F = 2\text{ A}$		0.45	V
		$T_j = 125^{\circ}C$		0.325	0.375	
		$T_j = 25^{\circ}C$	$I_F = 4\text{ A}$		0.53	
		$T_j = 125^{\circ}C$		0.43	0.51	

Pulse test : * $t_p = 380\text{ }\mu s$, $\delta < 2\%$

To evaluate the maximum conduction losses use the following equation :
 $P = 0.24 \times I_{F(AV)} + 0.068 I_{F(RMS)}^2$

Fig. 1: Average forward power dissipation versus average forward current.




Fig. 2: Average forward current versus ambient temperature (delta=0.5).











Fig. 3: Non repetitive surge peak forward current versus overload duration (maximum values).**Fig. 4:** Relative variation of thermal impedance junction to ambient versus pulse duration.**Fig. 5:** Reverse leakage current versus reverse voltage applied (typical values).**Fig. 6:** Junction capacitance versus reverse voltage applied (typical values).**Fig. 7:** Forward voltage drop versus forward current (maximum values).**Fig. 8:** Thermal resistance junction to ambient versus copper surface under each lead (Epoxy printed circuit board FR4, copper thickness: 35μm).

STPS2L25U**PACKAGE MECHANICAL DATA****SMB**

REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A1	1.90	2.45	0.075	0.096
A2	0.05	0.20	0.002	0.008
b	1.95	2.20	0.077	0.087
c	0.15	0.41	0.006	0.016
E	5.10	5.60	0.201	0.220
E1	4.05	4.60	0.159	0.181
D	3.30	3.95	0.130	0.156
L	0.75	1.60	0.030	0.063

FOOT PRINT DIMENSIONS (in millimeters)

Ordering type	Marking	Package	Weight	Base qty	Delivery mode
STPS2L25U	G23	SMB	0.107g	2500	Tape & reel

- Band indicates cathode
- Epoxy meets UL94,V0

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 1999 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - China - Finland - France - Germany - Hong Kong - India - Italy - Japan - Malaysia
Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - U.S.A.

<http://www.st.com>