



N-channel 600 V, 0.8 Ω typ., 5 A MDmesh™ II Power MOSFETs in DPAK, TO-220FP and IPAK packages



AM01475v1_noZen

Features

| Order code | V_{DS} | $R_{DS(on)}$ max. | I_D | Package |
|------------|----------|-------------------|-------|----------|
| STD7NM60N | 600 V | 0.9 Ω | 5 A | DPAK |
| STF7NM60N | | | | TO-220FP |
| STU7NM60N | | | | IPAK |

- 100% avalanche tested
- Low input capacitance and gate charge
- Low gate input resistance

Applications

- Switching applications

Description

These devices are N-channel Power MOSFETs developed using the second generation of MDmesh™ technology. These revolutionary Power MOSFETs associate a vertical structure to the company's strip layout to yield one of the world's lowest on-resistance and gate charge. They are therefore suitable for the most demanding high-efficiency converters.

Product status link

[STD7NM60N](#)
[STF7NM60N](#)
[STU7NM60N](#)

1 Electrical ratings

Table 1. Absolute maximum ratings

| Symbol | Parameter | Value | | Unit |
|-------------------------|---|------------|-------------------|------|
| | | DPAK, IPAK | TO-220FP | |
| V_{DS} | Drain-source voltage | 600 | | V |
| V_{GS} | Gate-source voltage | ±25 | | V |
| I_D | Drain current (continuous) at $T_C = 25\text{ °C}$ | 5 | 5 ⁽¹⁾ | A |
| I_D | Drain current (continuous) at $T_C = 100\text{ °C}$ | 3 | 3 ⁽¹⁾ | A |
| I_{DM} ⁽²⁾ | Drain current (pulsed) | 20 | 20 ⁽¹⁾ | A |
| P_{TOT} | Total dissipation at $T_C = 25\text{ °C}$ | 45 | 20 | W |
| V_{ISO} | Insulation withstand voltage (RMS) from all three leads to external heat-sink ($t = 1\text{ s}$, $T_C = 25\text{ °C}$) | 2.5 | | kV |
| dv/dt ⁽³⁾ | Peak diode recovery voltage slope | 15 | | V/ns |
| T_J | Operating junction temperature range | -55 to 150 | | °C |
| T_{stg} | Storage temperature range | | | |

- Limited by maximum junction temperature.
- Pulse width limited by safe operating area.
- $I_{SD} \leq 5\text{ A}$, $di/dt \leq 100\text{ A}/\mu\text{s}$, $V_{DSpeak} \leq V_{(BR)DSS}$, $V_{DD} = 80\% V_{(BR)DSS}$.

Table 2. Thermal data

| Symbol | Parameter | Value | | | Unit |
|------------------------------|-------------------------------------|-------|----------|------|------|
| | | DPAK | TO-220FP | IPAK | |
| $R_{thj-case}$ | Thermal resistance junction-case | 2.78 | 6.25 | 2.78 | °C/W |
| $R_{thj-amb}$ | Thermal resistance junction-ambient | | 62.5 | 100 | °C/W |
| $R_{thj-pcb}$ ⁽¹⁾ | Thermal resistance junction-pcb | 50 | | | °C/W |

- When mounted on 1inch² FR-4 board, 2 oz Cu.

Table 3. Avalanche characteristics

| Symbol | Parameter | Value | Unit |
|-------------------------|---|-------|------|
| I_{AS} ⁽¹⁾ | Avalanche current, repetitive or not-repetitive | 2 | A |
| E_{AS} ⁽²⁾ | Single pulse avalanche energy | 119 | mJ |

- Pulse width limited by T_J max.
- Starting $T_J = 25\text{ °C}$, $I_D = I_{AS}$, $V_{DD} = 50\text{ V}$.

2 Electrical characteristics

($T_{CASE} = 25\text{ °C}$ unless otherwise specified)

Table 4. On/off states

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|---------------|-----------------------------------|--|------|------|------|---------------|
| $V_{(BR)DSS}$ | Drain-source breakdown voltage | $I_D = 1\text{ mA}$, $V_{GS} = 0\text{ V}$ | 600 | | | V |
| I_{DSS} | Zero gate voltage drain current | $V_{GS} = 0\text{ V}$, $V_{DS} = 600\text{ V}$ | | | 1 | μA |
| | | $V_{GS} = 0\text{ V}$, $V_{DS} = 600\text{ V}$, $T_C = 125\text{ °C}$ ⁽¹⁾ | | | 100 | μA |
| I_{GSS} | Gate body leakage current | $V_{DS} = 0\text{ V}$, $V_{GS} = \pm 20\text{ V}$ | | | 100 | nA |
| $V_{GS(th)}$ | Gate threshold voltage | $V_{DS} = V_{GS}$, $I_D = 250\text{ }\mu\text{A}$ | 2 | 3 | 4 | V |
| $R_{DS(on)}$ | Static drain-source on resistance | $V_{GS} = 10\text{ V}$, $I_D = 2.5\text{ A}$ | | 0.8 | 0.9 | Ω |

1. Defined by design, not subject to production test.

Table 5. Dynamic

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|----------------------------|-------------------------------------|---|------|------|------|---------------|
| C_{iss} | Input capacitance | $V_{DS} = 50\text{ V}$, $f = 1\text{ MHz}$, $V_{GS} = 0\text{ V}$ | - | 363 | - | μF |
| C_{oss} | Output capacitance | | | 24.6 | | |
| C_{rSS} | Reverse transfer capacitance | | | 1.1 | | |
| $C_{oss\text{ eq.}}^{(1)}$ | Equivalent capacitance time related | $V_{DS} = 0\text{ to }480\text{ V}$, $V_{GS} = 0\text{ V}$ | - | 130 | - | μF |
| R_G | Intrinsic gate resistance | $f = 1\text{ MHz}$ open drain | - | 5.4 | - | Ω |
| Q_g | Total gate charge | $V_{DD} = 480\text{ V}$, $I_D = 5\text{ A}$, $V_{GS} = 0\text{ to }10\text{ V}$ (see Figure 14. Test circuit for gate charge behavior) | - | 14 | - | nC |
| Q_{gs} | Gate-source charge | | | 2.7 | | |
| Q_{gd} | Gate-drain charge | | | 7.7 | | |

1. $C_{oss\text{ eq.}}$ is defined as a constant equivalent capacitance giving the same charging time as C_{oss} when V_{DS} increases from 0 to 80% V_{DSS} .

Table 6. Switching times

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|--------------|---------------------|---|------|------|------|------|
| $t_{d(on)}$ | Turn-on delay time | $V_{DD} = 300\text{ V}$, $I_D = 2.5\text{ A}$, $R_G = 4.7\text{ }\Omega$, $V_{GS} = 10\text{ V}$ | - | 7 | - | ns |
| t_r | Rise time | | | 10 | | |
| $t_{d(off)}$ | Turn-off delay time | (see Figure 13. Test circuit for resistive load switching times and Figure 18. Switching time waveform) | - | 26 | - | ns |
| t_f | Fall time | | | 12 | | |

Table 7. Source drain diode

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|-----------------|-------------------------------|---|------|------|------|---------------|
| I_{SD} | Source-drain current | | - | | 5 | A |
| $I_{SDM}^{(1)}$ | Source-drain current (pulsed) | | | | 20 | |
| $V_{SD}^{(2)}$ | Forward on voltage | $I_{SD} = 5\text{ A}$, $V_{GS} = 0\text{ V}$ | - | | 1.3 | V |
| t_{rr} | Reverse recovery time | $I_{SD} = 5\text{ A}$, $di/dt = 100\text{ A}/\mu\text{s}$ | - | 213 | | ns |
| Q_{rr} | Reverse recovery charge | $V_{DD} = 60\text{ V}$ (see Figure 15. Test circuit for inductive load switching and diode recovery times) | | 1.5 | | μC |
| I_{RRM} | Reverse recovery current | | | 14 | | A |
| t_{rr} | Reverse recovery time | $I_{SD} = 5\text{ A}$, $di/dt = 100\text{ A}/\mu\text{s}$ | - | 265 | | ns |
| Q_{rr} | Reverse recovery charge | $V_{DD} = 60\text{ V}$, $T_j = 150\text{ }^\circ\text{C}$ (see Figure 15. Test circuit for inductive load switching and diode recovery times) | | 1.8 | | μC |
| I_{RRM} | Reverse recovery current | | | 14 | | A |

1. Pulse width limited by safe operating area.
2. Pulsed: pulse duration = 300 μs , duty cycle 1.5%.

2.1 Electrical characteristics curves















Figure 1. Safe operating area for DPAK and IPAK

Figure 2. Thermal impedance for DPAK and IPAK

Figure 3. Safe operating area for TO-220FP

Figure 4. Thermal impedance for TO-220FP

Figure 5. Output characteristics

Figure 6. Transfer characteristics


Figure 7. Gate charge vs gate-source voltage

Figure 8. Static drain-source on-resistance

Figure 9. Capacitance variations

Figure 10. Normalized gate threshold voltage vs temperature

Figure 11. Normalized on-resistance vs temperature

Figure 12. Normalized V(BR)DSS vs temperature



3 Test circuits

Figure 13. Test circuit for resistive load switching times



AM01468v1

Figure 14. Test circuit for gate charge behavior



AM01469v1

Figure 15. Test circuit for inductive load switching and diode recovery times



AM01470v1

Figure 16. Unclamped inductive load test circuit


AM01471v1

Figure 17. Unclamped inductive waveform


AM01472v1

Figure 18. Switching time waveform



AM01473v1

4 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com. ECOPACK® is an ST trademark.

4.1 DPAK (TO-252) type A package information

Figure 19. DPAK (TO-252) type A package outline




0068772_A_25

Table 8. DPAK (TO-252) type A mechanical data

| Dim. | mm | | |
|------|-------|-------|-------|
| | Min. | Typ. | Max. |
| A | 2.20 | | 2.40 |
| A1 | 0.90 | | 1.10 |
| A2 | 0.03 | | 0.23 |
| b | 0.64 | | 0.90 |
| b4 | 5.20 | | 5.40 |
| c | 0.45 | | 0.60 |
| c2 | 0.48 | | 0.60 |
| D | 6.00 | | 6.20 |
| D1 | 4.95 | 5.10 | 5.25 |
| E | 6.40 | | 6.60 |
| E1 | 4.60 | 4.70 | 4.80 |
| e | 2.159 | 2.286 | 2.413 |
| e1 | 4.445 | 4.572 | 4.699 |
| H | 9.35 | | 10.10 |
| L | 1.00 | | 1.50 |
| (L1) | 2.60 | 2.80 | 3.00 |
| L2 | 0.65 | 0.80 | 0.95 |
| L4 | 0.60 | | 1.00 |
| R | | 0.20 | |
| V2 | 0° | | 8° |

4.2 DPAK (TO-252) type C package information

Figure 20. DPAK (TO-252) type C package outline



0068772_C_25

Table 9. DPAK (TO-252) type C mechanical data

| Dim. | mm | | |
|------|----------|-------|-------|
| | Min. | Typ. | Max. |
| A | 2.20 | 2.30 | 2.38 |
| A1 | 0.90 | 1.01 | 1.10 |
| A2 | 0.00 | | 0.10 |
| b | 0.72 | | 0.85 |
| b4 | 5.13 | 5.33 | 5.46 |
| c | 0.47 | | 0.60 |
| c2 | 0.47 | | 0.60 |
| D | 6.00 | 6.10 | 6.20 |
| D1 | 5.25 | | |
| E | 6.50 | 6.60 | 6.70 |
| E1 | 4.70 | | |
| e | 2.186 | 2.286 | 2.386 |
| H | 9.80 | 10.10 | 10.40 |
| L | 1.40 | 1.50 | 1.70 |
| L1 | 2.90 REF | | |
| L2 | 0.90 | | 1.25 |
| L3 | 0.51 BSC | | |
| L4 | 0.60 | 0.80 | 1.00 |
| L6 | 1.80 BSC | | |
| θ1 | 5° | 7° | 9° |
| θ2 | 5° | 7° | 9° |
| V2 | 0° | | 8° |

4.3 DPAK (TO-252) type E package information

Figure 21. DPAK (TO-252) type E package outline





Table 10. DPAK (TO-252) type E mechanical data


| Dim. | mm | | |
|------|------|-------|-------|
| | Min. | Typ. | Max. |
| A | 2.18 | | 2.39 |
| A2 | | | 0.13 |
| b | 0.65 | | 0.884 |
| b4 | 4.95 | | 5.46 |
| c | 0.46 | | 0.61 |
| c2 | 0.46 | | 0.60 |
| D | 5.97 | | 6.22 |
| D1 | 5.21 | | |
| E | 6.35 | | 6.73 |
| E1 | 4.32 | | |
| e | | 2.286 | |
| e1 | | 4.572 | |
| H | 9.94 | | 10.34 |
| L | 1.50 | | 1.78 |
| L1 | | 2.74 | |
| L2 | 0.89 | | 1.27 |
| L4 | | | 1.02 |

Figure 22. DPAK (TO-252) recommended footprint (dimensions are in mm)



FP_0068772_25

4.4 DPAK (TO-252) packing information

Figure 23. DPAK (TO-252) tape outline



AM08852v1

Figure 24. DPAK (TO-252) reel outline



AM06038v1

Table 11. DPAK (TO-252) tape and reel mechanical data

| Tape | | | Reel | | |
|------|------|------|-----------|------|------|
| Dim. | mm | | Dim. | mm | |
| | Min. | Max. | | Min. | Max. |
| A0 | 6.8 | 7 | A | | 330 |
| B0 | 10.4 | 10.6 | B | 1.5 | |
| B1 | | 12.1 | C | 12.8 | 13.2 |
| D | 1.5 | 1.6 | D | 20.2 | |
| D1 | 1.5 | | G | 16.4 | 18.4 |
| E | 1.65 | 1.85 | N | 50 | |
| F | 7.4 | 7.6 | T | | 22.4 |
| K0 | 2.55 | 2.75 | | | |
| P0 | 3.9 | 4.1 | Base qty. | | 2500 |
| P1 | 7.9 | 8.1 | Bulk qty. | | 2500 |
| P2 | 1.9 | 2.1 | | | |
| R | 40 | | | | |
| T | 0.25 | 0.35 | | | |
| W | 15.7 | 16.3 | | | |

4.5 TO-220FP package information

Figure 25. TO-220FP package outline




7012510_Rev_12_B

Table 12. TO-220FP package mechanical data

| Dim. | mm | | |
|------|------|------|------|
| | Min. | Typ. | Max. |
| A | 4.4 | | 4.6 |
| B | 2.5 | | 2.7 |
| D | 2.5 | | 2.75 |
| E | 0.45 | | 0.7 |
| F | 0.75 | | 1 |
| F1 | 1.15 | | 1.70 |
| F2 | 1.15 | | 1.70 |
| G | 4.95 | | 5.2 |
| G1 | 2.4 | | 2.7 |
| H | 10 | | 10.4 |
| L2 | | 16 | |
| L3 | 28.6 | | 30.6 |
| L4 | 9.8 | | 10.6 |
| L5 | 2.9 | | 3.6 |
| L6 | 15.9 | | 16.4 |
| L7 | 9 | | 9.3 |
| Dia | 3 | | 3.2 |

4.6 IPAK (TO-251) type A package information

Figure 26. IPAK (TO-251) type A package outline




0068771_IK_typeA_rev14

Table 13. IPAK (TO-251) type A package mechanical data

| Dim. | mm | | |
|------|------|-------|------|
| | Min. | Typ. | Max. |
| A | 2.20 | | 2.40 |
| A1 | 0.90 | | 1.10 |
| b | 0.64 | | 0.90 |
| b2 | | | 0.95 |
| b4 | 5.20 | | 5.40 |
| B5 | | 0.30 | |
| c | 0.45 | | 0.60 |
| c2 | 0.48 | | 0.60 |
| D | 6.00 | | 6.20 |
| E | 6.40 | | 6.60 |
| e | | 2.28 | |
| e1 | 4.40 | | 4.60 |
| H | | 16.10 | |
| L | 9.00 | | 9.40 |
| L1 | 0.80 | | 1.20 |
| L2 | | 0.80 | 1.00 |
| V1 | | 10° | |

4.7 IPAK (TO-251) type C package information

Figure 27. IPAK (TO-251) type C package outline



0068771_IK_typeC_rev14

Table 14. IPAK (TO-251) type C package mechanical data

| Dim. | mm | | |
|------|-------|-------|-------|
| | Min. | Typ. | Max. |
| A | 2.20 | 2.30 | 2.35 |
| A1 | 0.90 | 1.00 | 1.10 |
| b | 0.66 | | 0.79 |
| b2 | | | 0.90 |
| b4 | 5.23 | 5.33 | 5.43 |
| c | 0.46 | | 0.59 |
| c2 | 0.46 | | 0.59 |
| D | 6.00 | 6.10 | 6.20 |
| D1 | 5.20 | 5.37 | 5.55 |
| E | 6.50 | 6.60 | 6.70 |
| E1 | 4.60 | 4.78 | 4.95 |
| e | 2.20 | 2.25 | 2.30 |
| e1 | 4.40 | 4.50 | 4.60 |
| H | 16.18 | 16.48 | 16.78 |
| L | 9.00 | 9.30 | 9.60 |
| L1 | 0.80 | 1.00 | 1.20 |
| L2 | 0.90 | 1.08 | 1.25 |
| θ1 | 3° | 5° | 7° |
| θ2 | 1° | 3° | 5° |

5 Ordering information

Table 15. Order codes

| Order code | Marking | Package | Packing |
|------------|---------|----------|---------------|
| STD7NM60N | 7NM60N | DPAK | Tape and reel |
| STF7NM60N | | TO-220FP | Tube |
| STU7NM60N | | IPAK | |

Revision history

Table 16. Document revision history

| Date | Version | Changes |
|-------------|---------|--|
| 29-Oct-2009 | 1 | First release. |
| 19-Jul-2010 | 2 | Corrected values in Table 3: Thermal data. |
| 11-Oct-2010 | 3 | Inserted new value in Table 6: Dynamic |
| 04-Nov-2010 | | Changed $R_{DS(on)}$ typical value. |
| 05-Sep-2018 | | <p>The part number STP7NM60N has been moved to a separate datasheet.</p> <p>Removed maturity status indication from cover page. The document status is production data.</p> <p>Updated title and features in cover page.</p> <p>Updated Section 1 Electrical ratings, Section 2 Electrical characteristics and Section 4 Package information.</p> <p>Minor text changes.</p> |

Contents

| | | |
|------------|--|-----------|
| 1 | Electrical ratings | 2 |
| 2 | Electrical characteristics | 3 |
| 2.1 | Electrical characteristics curves | 5 |
| 3 | Test circuits | 7 |
| 4 | Package information | 8 |
| 4.1 | DPAK (TO-252) type A package information | 8 |
| 4.2 | DPAK (TO-252) type C package information | 10 |
| 4.3 | DPAK (TO-252) type E package information | 12 |
| 4.4 | DPAK (TO-252) packing information | 14 |
| 4.5 | TO-220FP package information | 16 |
| 4.6 | IPAK (TO-251) type A package information | 18 |
| 4.7 | IPAK (TO-251) type C package information | 20 |
| 5 | Ordering information | 23 |
| | Revision history | 24 |

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2018 STMicroelectronics – All rights reserved