



N- and P-Channel 40-V (D-S) MOSFET

PRODUCT SUMMARY



	V _{DS} (V)	r _{DS(on)} (Ω)	I _D (A)	Q _g (Typ)
N-Channel	40	0.040 at V _{GS} = 10 V	5.2	8
		0.045 at V _{GS} = 4.5 V	4.9	
P-Channel	-40	0.054 at V _{GS} = -10 V	-4.5	9
		0.072 at V _{GS} = -4.5 V	-3.9	

FEATURES


- TrenchFET® Power MOSFET
- 100 % R_g Tested
- UIS Tested

APPLICATIONS

- CCFL Inverter

RoHS
COMPLIANT

N-Channel MOSFET



P-Channel MOSFET

Ordering Information: Si4565DY-T1-E3 (Lead (Pb)-free)

ABSOLUTE MAXIMUM RATINGS (T_A = 25 °C UNLESS OTHERWISE NOTED)

Parameter		Symbol	N-Channel		P-Channel		Unit
			10 secs	Steady State	10 secs	Steady State	
Drain-Source Voltage		V _{DS}	40		−40		V
Gate-Source Voltage		V _{GS}	± 12		± 16		
Continuous Drain Current (T _J = 150 °C) ^a	T _A = 25 °C	I _D	5.2	3.9	−4.5	−3.3	A
	T _A = 70 °C		4.2	3.1	−3.6	−2.7	
Pulsed Drain Current		I _{DM}	30				
Continuous Source Current (Diode Conduction) ^a		I _S	1.7	0.9	−1.7	−0.9	
Avalanche Current	L = 0.1 mH	I _{AS}	13		16		
Single Pulse Avalanche Energy		E _{AS}	8.5		13		mJ
Maximum Power Dissipatio ^a	T _A = 25 °C	P _D	2.0	1.1	2	1.1	W
	T _A = 70 °C		1.3	0.7	1.3	0.7	
Operating Junction and Storage Temperature Range		T _J , T _{stg}	−55 to 150				°C

THERMAL RESISTANCE RATINGS

Parameter		Symbol	N-Channel		P-Channel		Unit
			Typ	Max	Typ	Max	
Maximum Junction-to-Ambient ^a	t ≤ 10 sec	R _{thJA}	52	62.5	50	62.5	°C/W
	Steady State		90	110	85	110	
Maximum Junction-to-Foot (Drain)	Steady State	R _{thJF}	32	40	30	40	

Notes

a. Surface Mounted on 1" x 1" FR4 Board.

SPECIFICATIONS (T _J = 25 °C UNLESS OTHERWISE NOTED)							
Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Static							
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250 μA	N-Ch	0.6		1.6	V
		V _{DS} = V _{GS} , I _D = −250 μA	P-Ch	−0.8		−2.2	
V _{DS} Temperature Coefficient	ΔV _{DS} /T _J	I _D = 250 μA	N-Ch		40		mV/°C
			P-Ch		−40		
V _{GS(th)} Temperature Coefficient	ΔV _{GS(th)} /T _J		N-Ch		−3.8		
			P-Ch		3.4		
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ± 12 V	N-Ch			± 100	nA
		V _{DS} = 0 V, V _{GS} = ± 16 V	P-Ch			± 100	
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 40 V, V _{GS} = 0 V	N-Ch			1	μA
		V _{DS} = −40 V, V _{GS} = 0 V	P-Ch			−1	
		V _{DS} = 40 V, V _{GS} = 0 V, T _J = 55 °C	N-Ch			10	
		V _{DS} = −40 V, V _{GS} = 0 V, T _J = 55 °C	P-Ch			−10	
On-State Drain Current ^a	I _{D(on)}	V _{DS} ≥ 5 V, V _{GS} = 10 V	N-Ch	20			A
		V _{DS} ≤ −5 V, V _{GS} = −10 V	P-Ch	−20			
Drain-Source On-State Resistance ^a	r _{DS(on)}	V _{GS} = 10 V, I _D = 5.2 A	N-Ch		0.033	0.040	Ω
		V _{GS} = −10 V, I _D = −4.5 A	P-Ch		0.045	0.054	
		V _{GS} = 4.5 V, I _D = 4.9 A	N-Ch		0.037	0.045	
		V _{GS} = −4.5 V, I _D = −3.9 A	P-Ch		0.059	0.072	
Forward Transconductance ^a	g _{fs}	V _{DS} = 15 V, I _D = 5.2 A	N-Ch		18		S
		V _{DS} = −15 V, I _D = −4.5 A	P-Ch		13		
Diode Forward Voltage ^a	V _{SD}	I _S = 1.7 A, V _{GS} = 0 V	N-Ch		0.75	1.2	V
		I _S = −1.7 A, V _{GS} = 0 V	P-Ch		−0.79	−1.2	
Dynamic ^b							
Input Capacitance	C _{iss}	N-Channel V _{DS} = 20 V, V _{GS} = 0 V, f = 1 MHz P-Channel V _{DS} = −20 V, V _{GS} = 0 V, f = 1 MHz	N-Ch		700		pF
			P-Ch		805		
					76		
Output Capacitance	C _{oss}		N-Ch		120		
			P-Ch		45		
Reverse Transfer Capacitance	C _{rss}		N-Ch		85		
			P-Ch				
Total Gate Charge	Q _g	N-Channel V _{DS} = 20 V, V _{GS} = 4.5 V, I _D = 5.2 A P-Channel V _{DS} = −20 V, V _{GS} = −4.5 V, I _D = −4.5 A	N-Ch		8	12	nC
			P-Ch		9	14	
			N-Ch		1.5		
			P-Ch		2		
Gate-Source Charge	Q _{gs}		N-Ch		2.4		
			P-Ch		3.6		
Gate-Drain Charge	Q _{gd}		N-Ch		1.9	2.9	Ω
			P-Ch		11.5	18	
Gate Resistance	R _g		N-Ch		7	11	
			P-Ch		8	13	
Turn-On Delay Time	t _{d(on)}	N-Channel V _{DD} = 15 V, R _L = 15 Ω I _D ≅ 1 A, V _{GEN} = 10 V, R _g = 6 Ω P-Channel V _{DD} = −15 V, R _L = 15 Ω I _D ≅ −1 A, V _{GEN} = −10 V, R _g = 6 Ω	N-Ch		11	17	ns
			P-Ch		12	18	
			N-Ch		27	40	
			P-Ch		74	110	
Turn-Off Delay Time	t _{d(off)}		N-Ch		8	13	
			P-Ch		38	60	
Fall Time	t _f		N-Ch		25	40	ns
			P-Ch		27	45	
Source-Drain Reverse Recovery Time	t _{rr}	I _F = 1.7 A, di/dt = 100 A/μs	N-Ch		17	26	nC
		I _F = −1.7 A, di/dt = 100 A/μs	P-Ch		17	26	
Body Diode Reverse Recovery Charge	Q _{rr}	I _F = 1.7 A, di/dt = 100 A/μs	N-Ch				
		I _F = −1.7 A, di/dt = 100 A/μs	P-Ch				

Notes

- a. Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2 %.
b. Guaranteed by design, not subject to production testing.


Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.




TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)

N-CHANNEL


Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current




Capacitance



Gate Charge




On-Resistance vs. Junction Temperature




TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)

N-CHANNEL


Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage




Threshold Voltage



Single Pulse Power, Junction-to-Ambient





Safe Operating Area, Junction-to-Foot







TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)

N-CHANNEL



TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)


P-CHANNEL




TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)

P-CHANNEL


On-Resistance vs. Drain Current




Capacitance




Gate Charge




On-Resistance vs. Junction Temperature



Source-Drain Diode Forward Voltage







On-Resistance vs. Gate-to-Source Voltage






TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)

P-CHANNEL



TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)**P-CHANNEL**

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see <http://www.vishay.com/ppg?73224>.



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.