




Thyristors T2800 T2802 Series



8-A Silicon Triacs

Three-Lead Plastic Types for
Power-Control and Power-Switching Applications

Features:

- ▣ 100-A Peak Surge Full-Cycle Current Ratings
- ▣ Shorted-Emitter Center-Gate Design
- ▣ Low Switching Losses
- ▣ Low Thermal Resistance
- ▣ Package Design Facilitates Mounting on a Printed-Circuit Board

Voltage Package	200 V	300 V	400 V	500 V	600 V
	Types	Types	Types	Types	Types
TO-220AB	T2800B (40668)	T2800C	T2800D (40669)	T2800E	T2800M (40670)
	T2802B	T2802C	T2802D	T2802E	T2802M

Numbers in parentheses are former RCA type numbers.

The RCA-T2800 and T2802 series triacs are gate-controlled full-wave silicon switches utilizing a plastic case with three leads to facilitate mounting on printed-circuit boards. They are intended for the control of ac loads in such applications as motor controls, light dimmers, heating controls, and power-switching systems.

These devices are designed to switch from an off-state to an on-state for either polarity of applied voltage with positive or negative gate triggering voltages. They have an on-state current

rating of 8 amperes at a T_C of 80°C and repetitive off-state voltage ratings of 200, 300, 400, 500 and 600 volts.

The T2802 series triacs are characterized for I^+ , III^- gate triggering modes only and should suit a wide range of applications that employ diac or anode on/off triggering.

The plastic package design provides not only ease of mounting but also low thermal impedance, which allows operation at high case temperatures and permits reduced heat-sink size.

MAXIMUM RATINGS, Absolute-Maximum Values:

For Operation with Sinusoidal Supply Voltage at Frequencies up to 50/60 Hz and with Resistive or Inductive Load.

	T2800B T2802B	T2800C T2802C	T2800D T2802D	T2800E T2802E	T2800M T2802M		
REPETITIVE PEAK OFF-STATE VOLTAGE: ^a Gate open, $T_J = -65$ to 100°C	V_{DROM}	200	300	400	500	600	V
RMS ON-STATE CURRENT (Conduction angle = 360°): Case temperature $T_C = 80^\circ\text{C}$	$I_T(RMS)$	8					A
For other conditions		See Fig. 3					
PEAK SURGE (NON-REPETITIVE) ON-STATE CURRENT: For one cycle of applied principal voltage 60 Hz (sinusoidal), $T_C = 80^\circ\text{C}$	I_{TSM}	100					A
50 Hz (sinusoidal), $T_C = 80^\circ\text{C}$		85					A
For more than one cycle of applied principal voltage		See Fig. 4					
RATE OF CHANGE OF ON-STATE CURRENT: $V_D = V_{DROM}$, $I_{GT} = 200$ mA, $t_r = 0.1$ μs (See Fig. 13) .	di/dt	70					A/ μs
FUSING CURRENT (for triac protection): $T_J = -65$ to 100°C , $t = 1.25$ to 10 ms	i^2t	50					A ² s
PEAK GATE-TRIGGER CURRENT: ^b For 1 μs max., See Fig. 5	I_{GTM}	4					A

• For either polarity of main terminal 2 voltage (V_{MT2}) with reference to main terminal 1.
 ▣ For either polarity of gate voltage (V_G) with reference to main terminal 1.
 ^ For temperature measurement reference point, see Dimensional Outline.

MAXIMUM RATINGS (Cont'd)

GATE POWER DISSIPATION:

Peak (For 1 μ s max., $I_{GT} \leq 4$ A, See Fig. 5)	P_{GM}	16	W
AVERAGE	$P_{G(AV)}$	0.35	W

TEMPERATURE RANGE:[▲]

Storage	T_{stg}	-65 to 150	$^{\circ}$ C
Operating (Case)	T_C	-65 to 100	$^{\circ}$ C

TERMINAL TEMPERATURE (During soldering):

For 10 s max. (terminals and case)	T_T	225	$^{\circ}$ C
------------------------------------	-------	-----	--------------

See preceding page for applicable footnotes.

ELECTRICAL CHARACTERISTICS, At Maximum Ratings Unless Otherwise Specified, and at Indicated Temperature

CHARACTERISTIC	SYMBOL	LIMITS For All Types Except as Specified			UNITS
		MIN.	TYP.	MAX.	
Peak Off-State Current: [●] Gate open, $T_J = 100^{\circ}$ C, $V_{DROM} = \text{Max. rated value}$	I_{DROM}	—	0.1	2	mA
Maximum On-State Voltage: [●] For $i_T = 30$ A (peak), $T_C = 25^{\circ}$ C (See Fig. 6)	v_{TM}	—	1.7	2	V
DC Holding Current: [●] Gate open, Initial principal current = 150 mA (dc) $v_D = 12$ V, $T_C = 25^{\circ}$ C, T2800 series T2802 series	I_{HO}	—	15 20	30 60	mA
For other case temperatures			See Fig. 7		
Critical Rate-of-Rise of Commutation Voltage: ^{●▲} For $v_D = V_{DROM}$, $i_T(\text{RMS}) = 8$ A, commutating di/dt = 4.3A/ms, gate unenergized, $T_C = 80^{\circ}$ C (See Fig. 14)	dv/dt	4	10	—	V/ μ s
Critical Rate-of-Rise of Off-State Voltage: [●] For $v_D = V_{DROM}$, exponential voltage rise, gate open, $T_C = 100^{\circ}$ C: T2800B, T2802B T2800C, T2802C T2800D, T2802D T2800E, T2802E T2800M, T2802M	dv/dt	100 85 75 65 60	300 275 250 225 200	— — — — —	V/ μ s
DC Gate-Trigger Current: ^{●■} Mode V_{MT2} V_G For $v_D = 12$ V (dc) $R_L = 12 \Omega$ $T_C = 25^{\circ}$ C	I_{GT}	— — — — — —	10 25 15 25 20 30	25 50 25 50 60 60	mA
For other case temperatures			See Figs. 9 & 10		
DC Gate-Trigger Voltage: ^{●■} For $v_D = 12$ V (dc), $R_L = 12 \Omega$, $T_C = 25^{\circ}$ C	V_{GT}	—	1.25	2.5	V
For other case temperatures			See Fig. 11		
For $v_D = V_{DROM}$, $R_L = 125 \Omega$, $T_C = 100^{\circ}$ C		0.2	—	—	
Gate-Controlled Turn-On Time: (Delay Time + Rise Time) For $v_D = V_{DROM}$, $I_{GT} = 80$ mA, $t_r = 0.1 \mu$ s, $i_T = 10$ A (peak), $T_C = 25^{\circ}$ C (See Figs. 12 & 15)	t_{gt}	—	1.6	2.5	μ s

See following page for applicable footnotes.

ELECTRICAL CHARACTERISTICS (Cont'd)

CHARACTERISTIC	SYMBOL	LIMITS For All Types Except as Specified			UNITS
		MIN.	TYP.	MAX.	
Thermal Resistance:					
Junction-to-Case	$R_{\theta JC}$	—	—	2.2	$^{\circ}\text{C/W}$
Junction-to-Ambient	$R_{\theta JA}$	—	—	60	

- For either polarity of main terminal 2 voltage (V_{MT2}) with reference to main terminal 1.
- For either polarity of gate voltage (V_G) with reference to main terminal 1.
- ▲ Variants of these devices having dv/dt characteristics selected specifically for inductive loads are available on special order; for additional information, contact your RCA Representative or your RCA Distributor.




Fig. 1 - Principal voltage-current characteristic.




Fig. 2 - Power dissipation vs. on-state current.




Fig. 3 - Maximum allowable case temperature vs. on-state current.




Fig. 5 - Gate pulse characteristics for all triggering modes.




Fig. 4 - Peak surge on-state current vs. surge current duration.




Fig. 6 - On-state current vs. on-state voltage.




Fig. 7 - DC holding current vs. case temperature.




Fig. 8 - Typical critical rate-of-rise of off-state voltage vs. case temperature.




Fig. 9 - DC gate-trigger current (for I⁺ and III⁺ triggering modes) vs. case temperature.




Fig. 10 - DC gate-trigger current (for I⁺ and III⁺ triggering modes) vs. case temperature for T2800 series only.




Fig. 11 - DC gate-trigger voltage vs. case temperature.




Fig. 12 - Turn-on time vs. gate-trigger current.




Fig. 13 - Rate-of-change of on-state current with time (defining di/dt).




Fig. 14 - Relationship between supply voltage and principal current (inductive load) showing reference points for definition of commutating voltage (dv/dt).





Fig. 15 - Relationship between off-state voltage, on-state current, and gate-trigger voltage showing reference points for definition of turn-on time (t_{gt}).



92CS-22765

Fig. 16 - Typical phase-control circuit for lamp dimming, heat control, and universal-motor speed control.

TERMINAL CONNECTIONS

Lead No. 1—Main Terminal 1
 Mounting Flange, Lead No. 2—Main Terminal 2
 Lead No. 3—Gate

AC INPUT VOLTAGE	120 V 60 Hz	240 V 60 Hz	240 V 50 Hz	
C ₁	0.1 μF 200 V	0.1 μF 400 V	0.1 μF 400 V	
C ₂	0.1 μF 100 V	0.1 μF 100 V	0.1 μF 100 V	
R ₁	100 kΩ ½ W	200 kΩ ½ W	250 kΩ ½ W	
R ₂	2.2 kΩ ½ W	3.3 kΩ ½ W	3.3 kΩ ½ W	
R ₃	15 kΩ ½ W	15 kΩ ½ W	15 kΩ ½ W	
SNUBBER NETWORK FOR BA (RMS)* INDUCTIVE LOAD	C _S	0.068 μF 200 V	0.1 μF 400 V	0.1 μF 400 V
	R _S	1.2 kΩ ½ W	1 kΩ ½ W	1 kΩ ½ W
RFI FILTER	C _F *	0.1 μF 200 V	0.1 μF 400 V	0.1 μF 400 V
	L _F *	100 μH	200 μH	200 μH
RCA TRIACS	T2800B	T2800D	T2800D	T2800D
	T2800C	T2802B	T2802D	T2802D
	T2802B	T2802B	T2802D	T2802D
	T2802C			

* For other RMS Current values refer to RCA Application Note AN-4745.

* Typical values for Lamp dimming circuits.