



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Product Description: SAW Filter 548.82MHz SMD 5x5mm.

TST Part No.: TB0723A

Customer Part No.: _____

Customer signature required
Company: _____
Division: _____
Approved by : _____
Date: _____

Checked by: Ricky Lee *Ricky*

Approved by: Francis Chen *Francis Chen*

Date: 2009/07/29

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

IF SAW Filter 548.82MHz(BW=77MHz) SMD 5X5mm

MODEL NO.: TB0723A

REV.1.0

A. MAXIMUM RATING:

1. Operating Temperature: -20 °C ~ +80 °C
2. Storage Temperature: -40 °C ~ +85 °C
3. Input power: 10dBm

RoHS Compliant
Lead free
Lead-free soldering

B. Characteristics :

Ambient Temperature: 25 °C

Characteristics	Value			Note
	Min.	Typ.	Max.	
Center frequency F_c MHz	-	551	-	-
Minimum Insertion loss I.L. dB	-	11.5	16.0	-
1dB BW MHz	77.0	79	-	
45dB BW MHz	-	103	106.0	
Passband Ripple ($F_c \pm 35\text{MH}$) dB	-	0.75	1.2	-
Attenuation (Reference to Minimum Insertion loss)				
10 ~ 438MHz dB	48	50	-	-
438 ~ 493MHz dB	40	55	-	-
602 ~ 680MHz dB	36	38	-	-
680 ~ 1000MHz dB	50	55	-	-
Temp Coefficient ppm/K	-	-94	-	-
Matching:				
1.The input of the filter will be matched to <u>50 ohm</u>				
2.The output of the filter will be matched to <u>50 ohm</u>				

C. Frequency Characteristics :

1. S21 Response: (span : 400MHz)




Fig1. Horizontal: 40MHz/Div Vertical: 10dB/Div

2. Group-Delay Ripple: (span : 100MHz)






Fig2. Horizontal: 10MHz/Div Vertical: 10nec/Div


3. S11 Smith Chart: (span : 400MHz)



4. S22 Smith Chart (span : 400MHz)




D. Measurement Circuit:



Z_{in} and Z_{out} are 50Ω .
 $C1=10\text{pF}$, $C2=10\text{pF}$


E. Outline Drawing:



- Pin C: RF input
- Pin G: RF output
- Pin H, D: Case Ground
- Pin A, B, E, F : Ground
- : Week Code (W01->A,W02->B,...W27->a,...,W52->z)
- △ : Product / Year Code, Unit : mm

Year	2005 2009	2006 2010	2007 2011	2008 2012
Product Code	B	b	<u>B</u>	<u>b</u>


F. PCB Footprint:



Unit: mm


H. PACKING:

1. REEL DIMENSION



Unit: mm

2. TAPE DIMENSION



Unit: mm

I. RECOMMENDED REFLOW PROFILE_:

