

SILICON PNP EPITAXIAL TYPE (PCT PROCESS)

TBC556
TBC557
TBC558

PRIMARILY INTENDED FOR USE DRIVER STAGE OF AUDIO AMPLIFIERS.


FEATURES:

- . High V_{CEO} : -65V (TBC556)
 -45V (TBC557)
 -30V (TBC558)
- . Low Noise

MAXIMUM RATINGS (Ta=25°C)

CHARACTERISTIC		SYMBOL	RATING	UNIT
Collector-Base Breakdown Voltage	TBC556	V _{(BR)CBO}	-80	V
	TBC557		-50	
	TBC558		-30	
Collector-Emitter Breakdown Voltage	TBC556	V _{(BR)CEO}	-65	V
	TBC557		-45	
	TBC558		-30	
Emitter-Base Breakdown Voltage		V _{(BR)EBO}	-5	V
Collector Current	DC	I _C	-100	mA
	Peak	I _{CP}	-200	
Base Current (Peak)		I _{BP}	-200	mA
Collector Power Dissipation		P _C	500	mW
Junction Temperature		T _j	150	°C
Storage Temperature Range		T _{stg}	-65 ~ 150	°C

Unit in mm



Weight : 0.21g

TBC556

TBC557

TBC558

ELECTRICAL CHARACTERISTICS ($T_a=25^{\circ}\text{C}$)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current	I_{CBO}	$V_{CB}=-30\text{V}, I_E=0$	-	-	-15	nA
Emitter Cut-off Current	I_{EBO}	$V_{EB}=-5\text{V}, I_C=0$	-	-	-1	μA
Collector-Emitter Breakdown Voltage	TBC556	$V_{(BR)CEO}$ $I_C=-1\text{mA}, I_B=0$	-65	-	-	V
	TBC557		-45	-	-	
	TBC558		-30	-	-	
DC Current Gain	h_{FE} (Note)	$V_{CE}=-5\text{V}, I_C=-2\text{mA}$	75	-	475	
Small Signal Current Gain	h_{fe}	$V_{CE}=-5\text{V}, I_C=-2\text{mA}$ $f=1\text{kHz}$	75	-	500	
Base-Emitter Voltage	V_{BE}	$V_{CE}=-5\text{V}, I_C=-2\text{mA}$	-600	-650	-750	mV
		$V_{CE}=-5\text{V}, I_C=-10\text{mA}$	-	-	-820	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=-10\text{mA}, I_B=-0.5\text{mA}$	-	-	-300	mV
		$I_C=-100\text{mA}, I_B=-5\text{mA}$	-	-	-650	
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C=-10\text{mA}, I_B=-0.5\text{mA}$	-	-700	-	mV
		$I_C=-100\text{mA}, I_B=-5\text{mA}$	-	-850	-	
Knee Voltage	V_{CEK}	$I_C=-10\text{mA}, I_B=\text{Value for Which}$ $I_C=-11\text{mA}, \text{ at } V_{CE}=-1\text{V}$	-	-250	-600	mV
Transition Frequency	f_T	$V_{CE}=-5\text{V}, I_C=-10\text{mA}$	-	300	-	MHz
Collector Output Capacitance	C_{ob}	$V_{CB}=-10\text{V}, f=1\text{MHz}$	-	4.5	-	pF
Noise Figure	NF	$V_{CE}=-5\text{V}, I_C=-0.2\text{mA}$ $R_g=2\text{k}\Omega, f=1\text{kHz}$	-	2	10	dB

Note: h_{FE} Classification 556, 557, 558, : 75~250
 556-A, 557-A, 558-A : 125~250
 556-B, 557-B, 558-B : 220~475