



Features

- Low current
- Low voltage
- Halogen free
- Qualified to AEC-Q101 standards for high reliability

HF

Mechanical Data

- Case: SOT-23
- Molding compound: UL flammability classification rating 94V-0
- Terminals: Tin-plated; solderability per MIL-STD-202, Method 208



SOT-23

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
TBC856A/B	SOT-23	3000 pcs / Tape & Reel	3A/3B
TBC857A/B/C	SOT-23	3000 pcs / Tape & Reel	3E/3F/3G
TBC858A/B/C	SOT-23	3000 pcs / Tape & Reel	3J/3K/3L

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	TBC856	TBC857	TBC858	Unit
Collector-Base Voltage	V _{CBO}	-80	-50	-30	V
Collector-Emitter Voltage	V _{CEO}	-65	-45	-30	V
Emitter-Base Voltage	V _{EBO}	-5	-5	-5	V
Collector Current (Continuous)	I _C	-100			mA
Collector Current (Peak)	I _{CM}	-200			mA

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation (T _A = 25°C)	P _D	250	mW
Thermal Resistance Junction-to-Air *1	R _{θJA}	409	°C/W
Thermal Resistance Junction-to-Case *1	R _{θJC}	225	°C/W
Thermal Resistance Junction-to-Lead *1	R _{θJL}	197	°C/W
Operating Junction Temperature	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-55 ~ +150	°C

Note 1: The data tested by surface mounted on a 15mm * 15mm * 1mm FR4-epoxy P.C.B

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage TBC856	$V_{(BR)CBO}$	$I_C = -10\mu\text{A}, I_E = 0$	-80	-	-	V
Collector-Base Breakdown Voltage TBC857			-50	-	-	
Collector-Base Breakdown Voltage TBC858			-30	-	-	
Collector-Emitter Breakdown Voltage TBC856	$V_{(BR)CEO}$	$I_C = -10\text{mA}, I_B = 0$	-65	-	-	V
Collector-Emitter Breakdown Voltage TBC857			-45	-	-	V
Collector-Emitter Breakdown Voltage TBC858			-30	-	-	V
Emitter-Base Breakdown Voltage TBC856	$V_{(BR)EBO}$	$I_E = -1\mu\text{A}, I_C = 0$	-5	-	-	V
Emitter-Base Breakdown Voltage TBC857			-5	-	-	V
Emitter-Base Breakdown Voltage TBC858			-5	-	-	V
Collector Cut-off Current	I_{CBO}	$V_{CB} = -30\text{V}, I_E = 0$	-	-	-15	nA
Emitter-base Cut-off Current	I_{EBO}	$V_{EB} = -5\text{V}, I_C = 0$	-	-	-100	nA
DC Current Gain TBC856/857/858A	h_{FE}	$V_{CE} = -5\text{V}, I_C = -2\text{mA}$	125	-	250	-
DC Current Gain TBC856/857/858B			220	-	475	-
DC Current Gain TBC857/858C			420	-	800	-
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = -10\text{mA}, I_B = -0.5\text{mA}$	-	-	-0.3	V
		$I_C = -100\text{mA}, I_B = -5\text{mA}$	-	-	-0.65	V
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = -10\text{mA}, I_B = -0.5\text{mA}$	-	-0.70	-	V
		$I_C = -100\text{mA}, I_B = -5\text{mA}$	-	-0.85	-	V
Base-Emitter Voltage	$V_{BE(ON)}$	$V_{CE} = -5\text{V}, I_C = -2\text{mA}$	-0.6	0.65	-0.75	V
		$V_{CE} = -5\text{V}, I_C = -10\text{mA}$	-	-	-0.82	V
Transition Frequency	f_T	$V_{CE} = -5\text{V}, I_C = -10\text{mA}$ $f = 100\text{MHz}$	100	-	-	MHz
Collector Capacitance	C_C	$V_{CB} = -10\text{V}, I_E = I_C = 0$ $f = 1\text{MHz}$	-	4.5	-	pF

Ratings and Characteristic Curves-TBC856/857/858A (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 h_{FE} vs. I_C




Fig 2 $V_{CE(sat)}$ vs. I_C




Fig 3 $V_{BE(sat)}$ vs. I_C




Fig 4 $V_{BE(on)}$ vs. I_C

Ratings and Characteristic Curves-TBC856/857/858B (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 h_{FE} vs. I_C




Fig 2 $V_{CE(sat)}$ vs. I_C




Fig 3 $V_{BE(sat)}$ vs. I_C




Fig 4 $V_{BE(on)}$ vs. I_C

Ratings and Characteristic Curves-TBC857/858C (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 h_{FE} vs. I_C




Fig 2 $V_{CE(sat)}$ vs. I_C




Fig 3 $V_{BE(sat)}$ vs. I_C





Fig 4 $V_{BE(on)}$ vs. I_C


Package Outline Dimensions (Unit: mm)



SOT-23		
Dimension	Min.	Max.
A	2.70	3.10
B	1.10	1.50
C	0.9	1.1
D	0.3	0.5
E	0.35	0.48
G	1.80	2.00
H	0.02	0.1
J	0.05	0.15
K	2.20	2.60

Package Outline Dimensions (Unit: mm)

SOT-23



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.