

TOSHIBA CMOS DIGITAL INTEGRATED CIRCUIT SILICON MONOLITHIC

TC9316F-027

DIGITAL TUNING SYSTEM (DTS-11)

The TC9316F-027 is a digital tuning system optimum for portable sets such as pocket radios, headphone stereo sets, etc... By combining TC9316F-027 with prescaler TD7101F or TD6134AF. 4-band of FM/MW/LW (TV)/SW are provided compatibly with worldwide destinations.

FEATURES

○ RECEIVING BAND

AREA	CODE		BAND	RECEIVING RANGE [Hz]	STEP [Hz]	Fref. [Hz]	IF [Hz]
	A1 / SW1	A0 / SW0					
U.S.A.	0	0	FM	* 87.5 ~ 108.0M	100 / 200k	6.25k	+ 10.7M
			MW	522 ~ 1620k	9k	3k	+ 450k
				520 ~ 1710k	10k	5k	
TV	2 ~ 13ch	1ch	3.125k	+ 10.7M			
General	0	1	FM	76.0 ~ 108.0M	50 / 100k	6.25k	+ 10.7M
			MW	522 ~ 1620k	9k	3k	+ 450k
				520 ~ 1710k	10k	5k	
LW	144 ~ 281k	1k	1k				
Europe	1	0	FM	87.5 ~ 108.0M	50 / 100k	6.25k	+ 10.7M
			MW	522 ~ 1620k	9k	3k	+ 450k
				520 ~ 1620k	10k	5k	
LW	144 ~ 281k	1k	1k				
Japan	1	1	FM	76.0 ~ 108.0M	50 / 100k	6.25k	- 10.7M
			MW	522 ~ 1629k	9k	3k	+ 450k
				520 ~ 1620k	10k	5k	
TV	1 ~ 12ch	1ch	3.125k	- 10.7M			
—	0	1	SW	5.95 ~ 15.6M	5k	5k	+ 450k
	1	0		3.8 ~ 12.5M			
	1	1		2.3 ~ 7.3M			
				9.5 ~ 26.1M			

* If step is 200kHz, range is 87.5~108.1 MHz.

980910EBA2

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The products described in this document are subject to the foreign exchange and foreign trade laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

- Station selection
 - Auto tuning
 - 1 push / 1 step
 - SW meter band scan
- Memory function
 - Fixed no fixed
 - Random no fixed
- Dual clock (12 / 24 Hour)
- Alarm timer function.
- Sleep function.

TC9316F-027 Layout

