


TCO-711STH TCO-745STH TCO-744STH

HALF DIP TTL



Features

- TTL logic output
- DIL-8 pin package compatible
- Hermetically sealed metal package
- Enable/Disable feature
- Case ground 4-pin for minimizing RF radiation

Absolute Maximum Ratings

Parameter	Symbol	Rating	Unit
Supply voltage	V _{CC}	-0.5 to +7.0	V
Input voltage	V _{IN}	-0.5 to V _{CC} +0.5	V
Output voltage	V _O	-0.5 to V _{CC} +0.5	V
Input current	I _{IN}	±10	mA
Output current	I _O	±25	mA
Storage temperature	T _{stg}	-55 to +125	°C

Specifications

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Frequency range	F _O	1.25	—	70	MHz	
Frequency stability	ΔF/F _O	-100 -50 -25	— — —	100 50 25	ppm ppm ppm	TCO-711STH *1 TCO-745STH TCO-744STH
Operating temperature	T _{opr}	0	25	70	°C	
Operating voltage	V _{CC}	4.5	5.0	5.5	V	DC
Operating current	I _{CC}	—	—	See Table A	mA	V _{CC} = 5.5V
Input voltage	V _{IH} V _{IL}	3.5 —	— —	— 1.5	V V	#1: V _{IH} or OPEN → Enable #1: V _{IL} or GND → Disable
Output voltage	V _{OH} V _{OL}	4.0 —	— —	— 0.4	V V	I _{OH} = -4mA I _{OL} = 16mA
Symmetry	SYM	45	50	55	%	at 1.4V
Rise/Fall time	t _r ,t _f	—	—	See Table A	ns	at 0.4V to 2.4V / at 2.4V to 0.4V
Fanout	n	—	—	10 5	— —	1.5 to 60MHz 60+ to 70MHz
Start-up time	t _{st}	—	—	4 10	ms ms	1.5 to 26MHz *2 26+ to 70MHz *2

*1 Inclusive of calibration tolerance at 25°C, operating temperature, operating voltage range.

*2 Rise time (0 to 4.5V) of V_{CC} > 150μs

Table A

Freq.	1.25+ to 10	10+ to 26	26+ to 50	50+ to 70	MHz
I _{CC}	10	15	35	50	mA
t _r ,t _f	5	5	5	5	ns

Test Circuit

See page 5 TEST-2.

Package outline

