

10A Avg.

600 Volts


FRED

TCU10B60-11A

■最大定格 Maximum Ratings

Item	Symbol	Conditions			Unit
くり返しピーク逆電圧 Repetitive Peak Reverse Voltage	V_{RRM}	600			V
平均整流電流 Average Rectified Forward Current	I_O	50Hz、正弦全波通電抵抗負荷 50Hz Full Sine Wave Resistive Load	$T_c=77^{\circ}C$	10	A
実効順電流 R.M.S. Forward Current	$I_F(RMS)$	11.1			A
サージ順電流 Surge Forward Current	I_{FSM}	60	50Hz正弦全波、1サイクル、非くり返し 50Hz Full Sine Wave, 1cycle, Non-repetitive		A
動作接合温度範囲 Operating Junction Temperature Range	T_{jw}	-40~+150			°C
保存温度範囲 Storage Temperature Range	T_{stg}	-40~+150			°C

■ **OUTLINE DRAWING(mm)**



■ APPROX. NET WEIGHT:1.45g

■電氣的・熱的特性 Electrical/Thermal Characteristics

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
ピーク逆電流 Peak Reverse Current	I_{RM}	$T_j = 25^\circ\text{C}$, $V_{RM} = V_{RRM}$, 一素子あたり Per Diode	—	—	30	μA
ピーク順電圧 Peak Forward Voltage	V_{FM}	$T_j = 25^\circ\text{C}$, $I_{FM} = 5\text{A}$, 一素子あたり Per Diode	—	2.3	2.7	V
逆回復時間 Reverse Recovery Time	t_{rr}	$I_{FM} = 5\text{A}$, $-di/dt = 50\text{ A}/\mu\text{s}$, $T_j = 25^\circ\text{C}$	—	19	30	ns
熱抵抗 Thermal Resistance	$R_{th(j-c)}$	接合部・ケース間 Junction to Case	—	—	3	$^\circ\text{C}/\text{W}$

■定格・特性曲線

FIG.1

順電壓特性
FORWARD CURRENT VS. VOLTAGE




FIG.2

平均順電力損失特性
AVERAGE FORWARD POWER DISSIPATION




FIG.3

平均順電流—ケース温度定格
AVERAGE FORWARD CURRENT VS. CASE TEMPERATURE




FIG.4

サージ順電流定格
SURGE CURRENT RATINGS
f=50Hz Sine Wave Non-Repetitive, No Load




FIG.5

サージ実効順電流定格
RMS SURGE CURRENT RATINGS
T_{amb}=40°C Non-Repetitive No Load

