


4.0x2.5mm



Pb Free

RoHS Conforming

Features

- VC-TCXO for Cellular Phone.
- Leadless type for auto pick-and-place.
- Miniature size. (4x2.5x1.2mm).
- Reflow soldering compatible.
- Low power consumption.


Specifications

Item	Symbol	Conditions	Min.	Max.	Units
Output Frequency Range	F _{OUT}		12.6	26	MHz
Frequency Stability	Δf/fo	vs Temperature	-2.0	+2.0	ppm
		vs Load	-0.2	+0.2	
		vs Voltage	-0.3	+0.3	
Storage Temp. Range	T _{STG}		-40	+85	°C
Operating Temp. Range	T _{OPR}		-30	+80	°C
Aging	Δf aging	Per Year	-1	1	ppm
Voltage control range	Δf/V	Positive	+/-8	+/-12	ppm
Supply Voltage	V _{DD}		2.4	5.5	Volt
Output Voltage	V _{out}	10k ohm // 10pF	0.8	—	Vp-p
Current Consumption (Maximum Loaded)	I _{DD}	12.6 ~ 15MHz	—	1.0	mA
		15 ~ 26MHz	—	1.5	
Duty Ratio	SYM	@50% V _{DD}	40	60	%
Harmonics	—		—	-5	dBc

Note: All electrical characteristics are defined at the maximum load and operating temperature range.

Dimensions

(Unit : mm)



Recommended Land Pattern

(Unit : mm)

