

VI TELEFILTER**Filter specification****TFS 70AV****1/5****Measurement condition**

Ambient temperature:	25	°C
Input power level:	0	dBm
Terminating impedance: *		
Input:	48 Ω	-34 pF
Output:	49 Ω	-35 pF

Characteristics

Remark:

The reference level for the relative attenuation a_{rel} of the TFS 70AV is the minimum of the pass band attenuation. This value is defined as the insertion loss a_e . The nominal frequency f_N is fixed at 70MHz without any tolerance. The values of relative attenuation a_{rel} are guaranteed for the whole operating temperature range. The frequency shift of the filter in the operating temperature range is included in the production tolerance scheme.

D a t a		typ. value		tolerance / limit		
Insertion loss (reference level)	A_e	13,5	dB	max.	14,5	dB
Nominal frequency	f_N				70,0	MHz
Passband	PB			f_N	± 5,0	MHz
Pass band ripple (p-p)		0,3	dB	max.	0,5	dB
Bandwidth **	BW					
0,5 dB		10,8	MHz	min.	10,0	MHz
40 dB		16	MHz	max.	18,25	MHz
Relative attenuation	a_{rel}					
$f_N - 20,0$ MHz ... $f_N - 9,125$ MHz		50	dB	min.	40	dB
$f_N + 9,125$ MHz ... $f_N + 20,0$ MHz		44	dB	min.	40	dB
Group delay ripple within PB (p-p)		45	ns	max.	90	ns
Phase linearity within PB		5,5	°	max.	11,5	°p-p
Operating temperature range	OTR				- 40 °C ... + 85°C	
Storage temperature range					- 40 °C ... + 85°C	
Temperature coefficient of frequency	TC_f ***	-73	ppm/K			

*) The terminating impedances depend on parasitics and q-values of matching elements and the board used, and are to be understood as reference values only. Should there be additional questions do not hesitate to ask for an application note or contact our design team.

**) at 25°C



***) $\Delta f_C(\text{Hz}) = TC_f(\text{ppm/K}) \times (T - T_A) \times f_{CAT}(\text{MHz})$

Generated:


Checked / Approved:

Tele Filter GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.


VI TELEFILTER**Filter specification****TFS 70AV****2/5****Filter characteristic****Construction and pin connection**

(All dimensions in mm)



1	Ground
2	Ground
3	Ground
4	Ground
5	Output
6	Output RF Return
7	Ground
8	Ground
9	Ground
10	Ground
11	Input
12	Input RF Return

Date code: Year + week
 T 2005
 U 2006
 V 2007
 ...

50 Ohm Test circuit

Tele Filter GmbH
 Potsdamer Straße 18
 D 14 513 TELTOW / Germany
 Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
 E-Mail: fft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

VI TELEFILTER**Filter specification****TFS 70AV****3/5****Stability characteristics**

After the following tests the filter shall meet the whole specification:

1. Shock: 500g, 1 ms, half sine wave, 3 shocks each plane;
DIN IEC 68 T2 - 27
2. Vibration: 10 Hz to 500 Hz, 0,35 mm or 5 g respectively, 1 octave per min, 10 cycles per plan, 3 plans;
DIN IEC 68 T2 - 6
3. Change of temperature: -55 °C to 125°C / 30 min. each / 10 cycles
DIN IEC 68 part 2 – 14 Test N
4. Resistance to solder heat (reflow): reflow possible: twice max.;
for temperature conditions refer to the attached "Air reflow temperature conditions" on page 4;


Packing

Tape & Reel: IEC 286 – 3, with exeption of value for N and minimum bending radius;
tape type II, embossed carrier tape with top cover tape on the upper side;


max. pieces of filters peer reel: 1700
reel of empty components at start: min. 300 mm
reel of empty components at start including leader: min. 500 mm
trailer: min. 300 mm

Tape (all dimensions in mm)

W : 24,00 +0,30/-0,10
Po : 4,00 ± 0,1
Do : 1,50 +0,1/-0
E : 1,75 ± 0,10
F : 11,50 ± 0,10
G(min) : 0,60
P2 : 2,00 ± 0,1
P1 : 12,00 ± 0,1
D1(min) : 1,50
Ao : 7,10 ± 0,10
Bo : 13,90 ± 0,10
Ct : 21,5 ± 0,1

**Reel (all dimensions in mm)**

A : 330
W1 : 24,4 +2/-0
W2(max) : 30,4
N(min) : 60
C : 13,0 +0,5/-0,2




The minimum bending radius is 45 mm.

Tele Filter GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Air reflow temperature conditions

Conditions	Exposure
Average ramp-up rate (30°C to 217°C)	less than 3°C/second
> 100°C	between 300 and 600 seconds
> 150°C	between 240 and 500 seconds
> 217°C	between 30 and 150 seconds
Peak temperature	max. 260°C
Time within 5°C of actual peak temperature	between 10 and 30 seconds
Cool-down rate (Peak to 50°C)	less than 6°C/second
Time from 30°C to Peak temperature	no greater than 300 seconds

Chip-mount air reflow profile

VI TELEFILTER**Filter specification****TFS 70AV****5/5****History**

Version	Reason of changes	Name	Date
1.0	- Generation of development specification	Chilla	09.11.2005
1.1	- Created filter specification - Added termination impedances - Delated 1dB bandwidth - Added filter characteristics - Added test circuit	Chilla	16.12.2005
1.2	- changed temperature coefficient of frequency	Chilla	16101.2006