

TIP150

SILICON DARLINGTON POWER TRANSISTORS

NPN epitaxial-base transistors in a monolithic Darlington circuit and housed in a TO-220 envelope.

High voltage, high forward and reverse energy designed for industrial and consumer applications.

Compliance to RoHS.

ABSOLUTE MAXIMUM RATINGS

Symbol	Ratings		Value	Unit
V_{CB0}	Collector-Base Voltage		300	V
V_{CEO}	Collector-Emitter Voltage		300	V
V_{EBO}	Emitter-Base Voltage		8	V
I_C	Collector Current		7	A
I_{CM}	Collector Peak Current (1)		10	A
I_B	Base Current		1.5	A
P_T	Power Dissipation at Case Temperature (2)	@ $T_{mb} < 25^\circ$	80	Watts
	Power Dissipation at free Air Temperature (3)		2	
t_J	Junction Temperature		-65 to +150	°C
t_s	Storage Temperature range		-65 to +150	
t_L	Lead Temperature 3.2 mm from case for 10 seconde		260	

1. This value applies for $t_p < 5ms$, duty cycle $< 10\%$.
2. Derate linearly to 150°C case temperature at the rate of 0.64 W/°C.
3. Derate linearly to 150°C free air temperature at the rate of 16 mW/°C.

THERMAL CHARACTERISTICS

Symbol	Ratings	Value	Unit
R_{thJC}	From Junction to Case Thermal Resistance	2.5	°C/W
R_{thJA}	From Junction to Free-Air Thermal Resistance	62.5	

TIP150

ELECTRICAL CHARACTERISTICS

TC=25°C unless otherwise noted

Symbol	Ratings	Test Condition(s)	Min	Typ	Max	Unit
V_{CBO}	Collector-Base Breakdown Voltage	$I_C = 1 \text{ mA}, I_E = 0$	300	-	-	V
V_{CEO}	Collector-Emitter Breakdown Voltage (4)	$I_C = 10 \text{ mA}, I_B = 0$	300	-	-	V
I_{CEO}	Collector-Emitter Cutoff Current	$I_B = 0, V_{CE} = 300 \text{ V}$	-	-	250	μA
$I_{CEOX(sus)}$	Collector-Emitter sustaining Current	$I_E = 0, V_{CLAMP} = V_{CEO}$	7	-	-	A
I_{EBO}	Emitter Cutoff Current	$V_{EB} = 8 \text{ V}, I_C = 0$	-	-	15	mA
$V_{CE(SAT)}$	Collector-Emitter saturation Voltage (4-5)	$I_C = 1 \text{ A}, I_B = 10 \text{ mA}$	-	-	1.5	V
		$I_C = 2 \text{ A}, I_B = 100 \text{ mA}$	-	-	1.5	
		$I_C = 5 \text{ A}, I_B = 250 \text{ mA}$	-	-	2	
$V_{BE(SAT)}$	Base-Emitter Saturation Voltage (4-5)	$I_C = 2 \text{ A}, I_B = 100 \text{ mA}$	-	-	2.2	V
		$I_C = 5 \text{ A}, I_B = 250 \text{ mA}$	-	-	2.3	
h_{FE}	Forward Current transfer ratio (4-5)	$V_{CE} = 5.0 \text{ V}, I_C = 2.5 \text{ A}$	150	-	-	-
		$V_{CE} = 5.0 \text{ V}, I_C = 5 \text{ A}$	50	-	-	
		$V_{CE} = 5.0 \text{ V}, I_C = 7 \text{ A}$	15	-	-	
h_{fe}	Small Signal Forward Current transfer ratio	$V_{CE} = 5.0 \text{ V}, I_C = 0.5 \text{ A}$ $f = 1 \text{ kHz}$	200	-	-	-
V_F	Diode forward Voltage	$I_F = 7 \text{ A}$	-	-	3.5	V
C_{OB}	Output Capacitance	$I_E = 0; V_{CB} = 10 \text{ V}$ $f = 1 \text{ MHz}$	-	-	150	pF

SWITCHING TIMES.


Symbol	Ratings	Test Condition(s)	Min	Typ	Max	Unit
t_d	Delay Time	$V_{CC} = 250 \text{ V}; I_C = 5 \text{ A}$ $I_{B1} = -I_{B2} = 250 \text{ mA}$ $t_p = 20 \mu\text{s}, \text{ duty cycle } < 2\%$	-	0.03	-	μs
t_r	Rise time		-	0.18	-	
t_s	Storage Time		-	3.5	-	
t_f	Fall Time		-	1.6	-	

- These parameters must be measured using pulse techniques, t_p 300 μs , Duty Cycle $< 2.0\%$
- These parameters must be measured using voltage-sensing contacts, separate from the current carrying contacts.

TIP150

MECHANICAL DATA CASE TO-220

DIMENSIONS (mm)		
	Min.	Max.
A	9,90	10,30
B	15,65	15,90
C	13,20	13,40
D	6,45	6,65
E	4,30	4,50
F	2,70	3,15
G	2,60	3,00
H	15,75	17,15
L	1,15	1,40
M	3,50	3,70
N	-	1,37
P	0,46	0,55
R	2,50	2,70
S	4,98	5,08
T	2,49	2,54
U	0,70	0,90



Pin 1 :	Base
Pin 2 :	Collector
Pin 3 :	Emitter
Package	Collector

Revised August 2012

Information furnished is believed to be accurate and reliable. However, Comset Semiconductors assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. Data are subject to change without notice. Comset Semiconductors makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Comset Semiconductors assume any liability arising out of the application or use of any product and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Comset Semiconductors' products are not authorized for use as critical components in life support devices or systems.