


HIGH POWER AMPLIFIER APPLICATION.

### FEATURES

- Complementary to TIP33C.
- Recommended for 45W 50W Audio Frequency Amplifier Output Stage.

### MAXIMUM RATING (Ta=25 )

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Base Voltage	$V_{CBO}$	-100	V
Collector-Emitter Voltage	$V_{CEO}$	-100	V
Emitter-Base Voltage	$V_{EBO}$	-6	V
Collector Current	$I_C$	-10	A
Base Current	$I_B$	-3	A
Collector Power Dissipation (Tc=25 )	$P_C$	80	W
Junction Temperature	$T_j$	150	
Storage Temperature Range	$T_{stg}$	-55 150	



### ELECTRICAL CHARACTERISTICS (Ta=25 )

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current	$I_{CBO}$	$V_{CB}=-100V, I_E=0$	-	-	-10	$\mu A$
Emitter Cut-off Current	$I_{EBO}$	$V_{EB}=-6V, I_C=0$	-	-	-10	$\mu A$
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C=-25mA, I_B=0$	-100	-	-	V
DC Current Gain	$h_{FE}$ (Note)	$V_{CE}=-4V, I_C=-2A$	55	-	160	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=-4A, I_B=-0.4A$	-	-	-1.0	V
Transition Frequency	$f_T$	$V_{CE}=-12V, I_C=-0.5A$	-	20	-	MHz
Collector Output Capacitance	$C_{ob}$	$V_{CB}=-10V, I_E=0, f=1MHz$	-	150	-	pF

Note :  $h_{FE}$  Classification R:55~110, O:80~160

# TIP34C

