

Land-Mobile Price List

TK-760G/860G Compact Multi-Mode FM Mobiles

Model	Description	List
VHF <i>Includes: KMC-27B mic., DC power cable, mounting bracket</i>		
TK-760GK	148-174 MHz 25W, 128 CH	\$472.00
TK-760GK2	136-162 MHz 25W, 128 CH	472.00
TK-760HGK	148-174 MHz 50W, 128 CH	565.00
TK-760HGK2	136-162 MHz 50W, 128 CH	565.00
UHF <i>Includes: KMC-27B mic., DC power cable, mounting bracket</i>		
TK-860GK	450-490 MHz 25W, 128 CH	502.00
TK-860GK2	485-512 MHz 25W, 128 CH	502.00
TK-860GK3	400-430 MHz 25W, 128 CH	502.00
TK-860HGK	450-490 MHz 40W, 128 CH	598.00
TK-860HGK2	485-512 MHz 40W, 128 CH	598.00
TK-860HGK3	400-430 MHz 40W, 128 CH	598.00

TK-760G/860G FEATURES:

- 128 Channel Capacity
- Flexible Channel Groups
- Conventional
- Scan with Priority
- Multi-group/Single-group Scan
- 8 Character Alpha CH. Display (13 segment)
- Lighted LCD Display
- Power On LCD Text Message
- 10 Programmable Back-lit PF Keys
- DTMF Store & Send Dialing
- Operator Selectable QT/DQT (OST)
- 2 Tone Encode (10 code pairs selectable)
- Front Panel Self-Programming Mode
- Panel Test & Tuning Modes
- 12.5 / 25 kHz Channel Spacing (per channel)
- High/Low Power per Channel
- Companded Audio Per Channel (Narrow ch. only)
- Built-in 4 W Speaker
- 2 Color LED Indicator
- Inverting Front Panel
- Home Channel Function
- Key Lock Function
- QT/DQT Encode/Decode
- DTMF Decode & DTMF DBD
- 2-Tone Decode & 2-Tone Encode
- DTMF ANI Encode
- DTMF Auto Dial Memory (9 memories)
- Auto-Redial (PF Key Function)
- Busy Channel Lockout
- Talk Around & Time Out Timer
- Minimum Volume Setting
- Power/Control/Warn Tone On/Off
- Tone Volume Setting
- Off Hook Decode (2-Tone/DTMF Decode)
- Off Hook Horn Alert
- PC Programming & Tuning
- Clone Enable/Disable
- Mobile-Portable Cloning



- Flash ROM Memory
- Embedded Message
- MIL-STD 810 C, D & E
- Horn Alert Output (req. KAP-1, KCT-19, & wire)
- Ignition-Sense Power On (req. KCT-18 & KCT-19)
- Ignition-Sense Horn Alert Disable (req. KAP-1, KCT-19, KCT-18, & wire to horn relay)
- Public Address Output Option (req. KAP-1, KCT-19 & Speaker)
- AUX Manual Relay Output Option (req. KAP-1, KCT-19 & wire to horn relay)
- Foot Switch Input (PF input) (req. KCT-19 & switch input to ground)
- KES-5 External Speaker Option (req. KCT-19)
- KES-3 Compact External Speaker Opt. (plugs into mobile 3.5mm phono-jack)

Accessories for the TK-760G/860G Series Radios

Model	Description	List
-------	-------------	------

AVL UNITS

Note: The 60G Series Radios have programmable data channel feature for steering the mobile to dedicated data channel per radio. For more information on AVL Units, please refer to the AVL pricepages.		
---	--	--

KGP-2A	GPS Receiver / Modem Unit (includes one dash-mount GPS antenna, mounting bracket, screw set)	525.00
KGP-2B	Base Modem Unit	225.00
KCT-35	KGP-2A & 2B Radio Interface Cable for 60G/62G/63G-Series Mobiles	21.00
KCT-36	KCT-35 Extension Cable; 117.6 inches (9.8 ft)	42.00
KPG-73D	Programming Software for KGP-2A/2B Windows™ 95/98/Me	99.00

CABLES

KCT-18	Ignition Sense Cable (Requires KCT-19)	13.00
KCT-19	Accessory Interface Cable (i.e., data, horn alert)	21.00

INSTALLATION ACCESSORIES

KLF-2	Line Filter (suppresses alternator whine, 25dB, 25A max).	39.50
KMB-10	Key lock adapter for the mobile bracket (KMB-6)	25.00
ST-865KW4 ¹	SmarTrunk II™ Logic Board (Requires ST-909) (for 60G/70G portables & 62G/60G mobiles only)	140.00
ST-909	Installation cable for ST-865KW4 (for 62G/60G-series mobiles only) <small>SmarTrunk II™ is a registered trademark of SmarTrunk Systems Inc.</small>	30.00

MICROPHONE AND SPEAKERS

KES-3	External speaker (compact low profile; black case; 3.5 mm phono plug-in)	42.00
KES-5	External Speaker, 40W max input, black case (60G-Series mobiles require a KCT-19 option)	59.00
KMC-27A	MIL-SPEC & Noise Canceling dynamic mobile microphone (8-pin mod. plug) (For 60G/62G Only)	99.00
KMC-27B	Standard dynamic mobile microphone (8-pin mod. plug) --- same as supplied w/ radio (for 60G/62G Mobile Radio Only)	40.00
KMC-28A	MIL-SPEC & Noise Canceling dynamic mobile microphone (8-pin mod. plug) w/ DTMF (for 60G/62G Mobile Radio Only)	155.00
KMC-9C	Control Station Desktop Microphone (8-pin mod. plug) (for 60G/62G Mobile Radio Only)	82.00

MISCELLANEOUS ITEMS

KAP-1	Horn Alert/P.A. Relay Option (requires KCT-19)	40.00
KPS-10A	DC Power Supply	209.00
KMB-20	Mobile cabinet for KPS-14/15 Power Supplies (mobile mounting hardware included) For 60/60G/60H/60HG/62/62G/60H/60HG/63G/80-series mobiles	25.00
KPS-15	DC Switching Power Supply (117/230 VAC; 23A max. continuous, 25A peak) *Compatible with medium & high power compact mobiles only: 60/60G/60H/60HG/62/62G/60H/60HG/80-series mobiles	167.00

SERVICE RELATED ACCESSORIES

KCT-20	KGP-1A & 1B Radio Interface Cable - Intent to Discontinue. Limited quantity available.	55.00
KCT-35	KGP-2A & 2B Radio Interface Cable for 60G/62G/63G-Series Mobiles	21.00
KCT-36	KCT-35 Extension Cable; 117.6 inches (9.8 ft)	42.00
KPG-46	Mobile Programming interface cable (8-pin mic jack mobiles) for 60G/62G/80 Series Mobiles	N/A
KPG-56D	Programming Software for 60G/70G Portables & 60G/62G Mobiles Models Only	N/A
KPG-61ED ²	Programming Software for KGP-1A/1B Parameters - Intent to Discontinue. Limited quantity avail.	25.00
KPG-73D	Programming Software for KGP-2A/2B Windows™ 95/98/Me	99.00

Installation / Tuning Charges for the TK-760G/860G Series Radios

<i>Model</i>	<i>Description</i>	<i>List</i>
L-136	Tune TK-760/760G/860/860G	\$20.00
L-888 ²	Install KCT-20 in 60G/62G Series Mobiles for KGP-1A/1B	21.00
L-895	Install KCT-19 in 60G/62G Series Mobiles for Data/MDT mode	17.00
L-896	Install KCT-19 in 60G/62G Series Mobiles for SmarTrunk Omni mode	17.00
L-897	Install KCT-19 in 60G/62G Series Mobiles for Emergency Foot Sw. Input	17.00
L-890	Log KGP-1A Serial Number (s) & KGP-1B Serial Number (For DigiMap DMTrack – AVL Products)	N/C
L-908	Install ST-865KW4/ST-909 (in 60G mobile)	20.00
L-930	Install KCT-35 in 60G/62G/63G Series Mobiles for KDS-100/KGP-2A/2B Interface (order KCT-35 separately)	21.00

www.DataSheet4U.com

¹ ST-865KW4/ST-909 - compatible with production lots starting Feb. 2000; Serial number 111xxxxx or higher (carton stamped "D"). These are not replacements for the ST-865KW2/ST-908 SmarTrunk II products for the 60/62-Series mobiles and 60/70-Series portables. For detailed information on SmarTrunk II- Kenwood radio features and logic controller information visit SmarTrunk Inc.'s web site for informative downloads such as the "ST-865KW4 SmarTrunk II Installation and Operation Manual for Kenwood "G" Series Transceivers" and the SmarTrunk II Digital Trunking System - System Overview manual.

² See AVL pricepages for further details.