

### **INCHANGE SEMICONDUCTOR**

D

pin 1, Gate

2, Drain

3, Source

# iscN-Channel MOSFET Transistor

# TK9A55DA, ITK9A55DA

123

TO-220F package

## • FEATURES

- Low drain-source on-resistance: RDs(ON) = 0.68Ω (typ.)
- · Enhancement mode:

Vth = 2.0 to 4.0V (VDs = 10 V, ID=1.0mA)


- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

## DESCRITION

Switching Voltage Regulators

#### • ABSOLUTE MAXIMUM RATINGS(T<sub>a</sub>=25°C)

SYMBOL	PARAMETER	VALUE	UNIT					
V <sub>DSS</sub>	Drain-Source Voltage	550	V					
V <sub>GS</sub>	Gate-Source Voltage	±30	V					
ID	Drain Current-Continuous	8.5	А					
I <sub>DM</sub>	Drain Current-Single Pulsed	34	А					
PD	Total Dissipation @T <sub>c</sub> =25℃	40	W					
Tj	Max. Operating Junction Temperature	Temperature 150						
T <sub>stg</sub>	Storage Temperature	-55~150	°C					



#### THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	МАХ	UNIT		
Rth(ch-c)	Channel-to-case thermal resistance	3.125	°C <b>/W</b>		
Rth(ch-a)	h(ch-a) Channel-to-ambient thermal resistance		°C <b>/W</b>		

1



# iscN-Channel MOSFET Transistor

# TK9A55DA, ITK9A55DA

### **ELECTRICAL CHARACTERISTICS**

 $T_{C}\text{=}25^{\circ}\!\!\!\mathrm{C}$  unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	ТҮР	МАХ	UNIT
BV <sub>DSS</sub>	Drain-Source Breakdown Voltage	V <sub>GS</sub> =0V; I <sub>D</sub> = 10mA	550			v
V <sub>GS</sub> (th)	Gate Threshold Voltage	V <sub>DS</sub> = 10V; I <sub>D</sub> =1.0mA	2.0		4.0	v
R <sub>DS(on)</sub>	Drain-Source On-Resistance	V <sub>GS</sub> =10V; I <sub>D</sub> =4.3A		680	860	mΩ
I <sub>GSS</sub>	Gate-Source Leakage Current	V <sub>GS</sub> = ±30V;V <sub>DS</sub> =0V			±1	μA
I <sub>DSS</sub>	Drain-Source Leakage Current	V <sub>DS</sub> =550V; V <sub>GS</sub> = 0V			10	μA
VSDF	Diode forward voltage	I <sub>DR</sub> =8.5A, V <sub>GS</sub> = 0 V			1.7	v

# **NOTICE:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.

2