


DETAIL A:



1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
VSS	VDD	VO	U/T	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	CS1	CS2	RST	VEE	A	K

NOTES:

- | | |
|----------------------------------|------------------------|
| 1. DISPLAY TYPE: | STN/YELLOW MODE |
| 2. VIEWING DIRECTION: | 6:00 |
| 3. POLARIZER MODE: | TRANSFLECTIVE/POSITIVE |
| 4. DRIVE METHOD: | 1/64 DUTY 1/9 BIAS |
| 5. LCD OPERATING VOLTAGE: | 11.0V |
| 6. OPERATING TEMP: | -20°C~+70°C |
| 7. STORAGE TEMP: | -30°C~+80°C |
| 8. CONTROLLER: | S6B0108A01-COCX |
| 9. BACKLIGHT: | LED<2.1V> |
| 10. BUILT IN DC-DC | |
| 11. BEZEL IS TO BE PAINTED BLACK | |
| 12. ALL UNMARKED TOLERANCES: | ±0.3mm |



TIAN-MA MICROELECTRONICS CO.

22/F., HANGJIU Building, Shennan Road, Central, Shenzhen, China

DRAWN BY:	TITLE: TM12864LBCW8	
CHECKED BY:	DWG NO: G-1	
APPROVED BY:	DWG NAME: TM12864LBCW8-1	
CONFIRMED BY:	SHEET NO: DP	