



NO.	PIN	NO.	PIN	NO.	PIN
1	NC	11	CAP3+	21	NC
2	NC	12	CAP1-	22	NC
3	CS1	13	CAP1+		
4	RES	14	CAP2+		
5	A0	15	CAP2-		
6	D6(SCL)	16	V1		
7	D7(SI)	17	V2		
8	VDD	18	V3		
9	VSS	19	V4		
10	VDUT	20	V0		

1. DISPLAY TYPE:	FSTN
2. VIEWING DIRECTION:	12:00
3. POLARIZER MODE:	TRANSFLECTIVE/POSITIVE
4. DRIVE METHOD:	1/65 DUTY 1/9 BIAS
5. LCD OPERATING VOLTAGE:	9.0V
6. OPERATING TEMP.:	-20°C~+70°C
7. STORAGE TEMP.:	-30°C~+80°C
8. CONTROLLER:	NT7502H-BDT
9. VDD=3.0V	
10. CONNECTOR:	FPC
11. WITHOUT BACKLIGHT	
12. UNMARKED TOLERANCES:	±0,3mm



TIAN-MA MICROELECTRONICS CO.

6/F., CASTIC Building, Shennan Road, Central, Shenzhen, China

DRAWN BY:	TITLE: TM13265ECIWUG			
CHECKED BY:				
APPROVED BY:	DWG NO: G-1	SCALE:		
CONFIRMED BY:	DWG NAME: TM13265ECIWUGG-1	SHEET NO: 1	UNIT: mm	