



1	2	3	4	5	6	7	8	9	10	11	12	13	14
V_{SS}	V_{DD}	V_0	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7

NOTES:

- | | |
|------------------------|------------------------|
| 1.DISPLAY TYPE: | TN |
| 2.VIEWING DIRECTION: | 6:00 |
| 3.POLARIZER MODE: | TRANSFLECTIVE/NEGATIVE |
| 4.OPERATING TEMP: | -10°C-60°C |
| 5.STORAGE TEMP: | -20°C-70°C |
| 6.OPERATING VOLTAGE: | 4.5V |
| 7.DRIVE METHOD: | 1/16 DUTY 1/5 BIAS |
| 8.WITHOUT BACKLIGHT | |
| 9.HEAT_SEAL CONNECTOR | |
| 10.CONTROLLER: | KS0032UM |
| 11.UNMARKED TOLERANCE: | ±0.3mm |



TIAN-MA MICROELECTRONICS CO.

6/F., CASTIC Building, Shennan Road, Central, Shenzhen, China

DRAWN BY:	TITLE: TM162AEIWG	 SCALE:
CHECKED BY:	DWG NO: G-1	
APPROVED BY:	DWG NAME: TM162AEIWGG-1	SHEET NO: 0F
CONFIRMED BY:		