



NOTES:

- | | |
|---------------------------|---------------------|
| 1. DISPLAY TYPE: | FSTN |
| 2. CHARACTERS: | 16 X 4 LINES |
| 3. VIEWING DIRECTION: | 6:00 |
| 4. POLARIZER MODE: | REFLECTIVE/POSITIVE |
| 5. DRIVE METHOD: | 1/16 DUTY 1/5 BIAS |
| 6. LCD OPERATING VOLTAGE: | 4.7V |
| 7. VDD=2.2V-5.5V | |
| 8. OPERATING TEMP: | 0°C-+50°C |
| 9. STORAGE TEMP: | -20°C-+60°C |
| 10. CONNECTOR: | HEAT-SEAL |
| 11. CONTROLLER: | S6A094 |
| 12. UNMARKED TOLERANCES: | ±0.3mm |

PIN	1	2	3	4	5	6	7	8	9	10	11	12	13
SYMBOL	RES	CAP1+	CAP1-	CAP2+	CAP2-	VOUT	VR	V0	V1	V2	V3	V4	VSS
PIN	14	15	16	17	18	19	20	21	22	23	24	25	26
SYMBOL	VDD	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	CSB	E	RDRW	WR



TIAN-MA MICROELECTRONICS CO.

5/F., CASTEC Building, Shennan Road, Central, Shenzhen, China

DRAWN BY: 张敏 2/4/01	TITLE: TM164ACAG	
CHECKED BY: 潘奇 2/20/01	DWG NO: G-1	
APPROVED BY: 李新 2/4/01	DWG NAME: TM164ACAGG-1	SCALE: mm
CONFIRMED BY: 李新 2/4/01	SHEET NO: OF	