

RF AMPLIFIER

MODEL *TM5325*

Available as: TM5325, 4 Pin TO-8 (T4)
 TN5325, 4 Pin Surface Mount (SM3)
 FP5325, 4 Pin Flatpack (FP4)
 BX5325, Connectorized Housing (H1)

Features

- Low Noise Figure: 2.0 dB Typical
- High Output Power: +24 dBm Typical
- Operating Temp. - 55 °C to +85 °C
- Environmental Screening Available

Specifications

CHARACTERISTIC	TYPICAL Ta= 25 °C	MIN/MAX Ta = -55 °C to +85 °C
Frequency	5 - 125 MHz	10 - 100 MHz
Gain (dB)	20.5	20.5 ± 1.0
Power @ 1 dB Comp. (dBm)	+24	+22.5 Min.
Reverse Isolation (dB)	- 24	- 23 Max.
VSWR In	1.70:1	2.2:1 Max.
Out	1.35:1	2.0:1 Max.
Noise figure (dB)	2.0	3.0 Max.
Power Vdc	+12	+12
mA	85	95 Max.

Note: Care should always be taken to effectively ground the case of each unit.


Typical Intermodulation Performance at 25 ° C

Second Order Harmonic Intercept Point +58 (Typ.)
 Second Order Two Tone Intercept Point +52 (Typ.)
 Third Order Two Tone Intercept Point +40 (Typ.)

Maximum Ratings

Ambient Operating Temperature -55°C to + 100 °C
 Storage Temperature -62°C to + 125 °C
 Case Temperature + 125 °C
 DC Voltage + 18 Volts
 Continuous RF Input Power + 13 dBm
 Short Term RF Input Power 50 Milliwatts
 (1 Minute Max.)
 Maximum Peak Power 0.5 Watt
 (3 µsec Max.)

Typical Performance Data



Linear S-Parameters

FREQ. MHz	S11		S21		S12		S22	
	Mag	Deg	Mag	Deg	Mag	Deg	Mag	Deg
5	.35	- 32	10.28	-157	.05	-159	.27	- 27
10	.27	- 28	10.95	-171	.05	-174	.16	- 32
50	.23	- 36	11.12	161	.06	151	.11	- 3
100	.26	- 68	11.10	139	.06	127	.10	-10
150	.32	-106	10.87	115	.07	103	.06	- 29

Amplifonix

2707 Black Lake Place, Philadelphia, PA 19154

TEL 215-464-4000 • • • • FAX 215-464-4001

2/13/03
www.DataSheet4U.com