

TMR7506-B

Unibody Low Temperature Coefficient Current Sensor

Description

TMR7506-B is an open loop current sensor for accurate measurement of DC, AC, pulsed current and arbitrary waveform current with galvanic isolation between primary and secondary circuits.



Features and Benefits

- Low temperature coefficient
- Galvanic isolation
- High immunity to external interference
- Excellent linearity
- Light weight design
- RoHS & REACH compliant

Applications

- DC motor drives
- Inverters and variable frequency drives (VFD)
- Uninterruptible power supplies (UPS)
- Power supplies for communication devices
- Battery management system (BMS)
- Switching power supplies
- Power supplies for welding application

Selection Guide

Model	Primary Nominal Current	Primary Current Measuring Range
TMR7506-0500B	50 A	±150 A
TMR7506-1000B	100 A	±300 A
TMR7506-2000B	200 A	±600 A
TMR7506-3000B	300 A	±900 A
TMR7506-4000B	400 A	±1000 A
TMR7506-5000B	500 A	±1000 A
TMR7506-6000B	600 A	±1000 A

Insulation and Environmental Characteristics

Parameters	Symbol	Typical	Unit
Dielectric Strength	V _D	5	kV(50Hz, 1min)
Insulation Resistance	R _{IS}	1000	MΩ
Creepage Distance	d _{CP}	30	mm
Clearance	d _{CL}	9	mm
Ambient Operating Temperature	T _A	-40 to +85	°C
Ambient Storage Temperature	T _{STG}	-40 to +85	°C
Mass	m	63	g

Catalogue

1. Specifications	03
2. Typical Output Characteristics.....	04
3. Typical Temperature Characteristics	05
4. Parameters Definition And Formula.....	07
5. Application Information	08
6. Dimensions	09

1. Specifications

$T_A = +25^\circ\text{C}$, $V_{CC} = \pm 15\text{ V}$, $R_L = 10\text{ k}\Omega$, unless otherwise noted

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
General Electrical Data						
Primary Nominal Current	I_{PN}	TMR7506-0500B	-	50	-	A
		TMR7506-1000B	-	100	-	
		TMR7506-2000B	-	200	-	
		TMR7506-3000B	-	300	-	
		TMR7506-4000B	-	400	-	
		TMR7506-5000B	-	500	-	
		TMR7506-6000B	-	600	-	
Primary Current Measuring Range	I_{PM}	TMR7506-0500B	-150	-	150	A
		TMR7506-1000B	-300	-	300	
		TMR7506-2000B	-600	-	600	
		TMR7506-3000B	-900	-	900	
		TMR7506-4000B	-1000	-	1000	
		TMR7506-5000B	-1000	-	1000	
		TMR7506-6000B	-1000	-	1000	
Sensitivity	S	$I_P = 0 \text{ to } \pm I_{PN}$	TMR7506-0500B	-	80.00	mV/A
			TMR7506-1000B	-	40.00	
			TMR7506-2000B	-	20.00	
			TMR7506-3000B	-	13.33	
			TMR7506-4000B	-	10.00	
			TMR7506-5000B	-	8.00	
			TMR7506-6000B	-	6.67	
Output Voltage	V_{OUT}	$I_P = 0 \text{ to } \pm I_{PM}$	-	$V_{OE} + S \times I_P$	-	V
Supply Voltage	V_{CC}	$\pm 5\%$	-	± 15	-	V
Current Consumption	I_C	$I_P = 0$	-	± 20	-	mA
Load Resistance	R_L	$I_P = 0 \text{ to } \pm I_{PN}$	1	10	-	k Ω
Load Capacitance	C_L	$I_P = 0 \text{ to } \pm I_{PN}$	-	100	-	pF
Static Performance Data						
Accuracy	X_G	$T_A = +25^\circ\text{C}, I_P = 0 \text{ to } \pm I_{PN}$	-1	± 0.5	1	% I_{PN}
		$T_A = -40^\circ\text{C} \text{ to } +85^\circ\text{C}, I_P = 0 \text{ to } \pm I_{PN}$	-3.5	± 1.5	3.5	
Linearity Error	ϵ_L	$T_A = -40^\circ\text{C} \text{ to } +85^\circ\text{C}, I_P = 0 \text{ to } \pm I_{PN}$	-	0.4	0.8	% I_{PN}
Symmetry	ϵ_{SYM}	$T_A = -40^\circ\text{C} \text{ to } +85^\circ\text{C}, I_P = 0 \text{ to } \pm I_{PN}$	99	100	101	%
Sensitivity Error	ϵ_S	$T_A = -40^\circ\text{C} \text{ to } +85^\circ\text{C}, I_P = 0 \text{ to } \pm I_{PN}$	-2	-	2	%
Offset Error	V_{OE}	$T_A = +25^\circ\text{C}, I_P = 0$	-20	± 10	20	mV
		$T_A = -40^\circ\text{C} \text{ to } +85^\circ\text{C}, I_P = 0$	-60	± 20	60	
Hysteresis	V_{OH}	$T_A = -40^\circ\text{C} \text{ to } +85^\circ\text{C}, I_P = \pm I_{PN} \rightarrow 0$	-20	± 10	20	mV
Dynamic Performance Data						
Response Time	t_R	$di/dt > 50\text{ A}/\mu\text{s}$, 10% to 90% of I_{PN}	0.9	2	-	μs
Bandwidth	BW	-1 dB	DC	50	-	kHz

2. Typical Output Characteristics




Figure 1. Output voltage versus primary current




Figure 2. Output voltage versus supply voltage
(@ $I_p = I_{PN}$)




Figure 3. Output voltage versus load resistance
(@ $I_p = I_{PN}$)




Figure 4. Output voltage versus load capacitance
(@ $I_p = I_{PN}$)




Figure 5. Bode plot of TMR7506-B

3. Typical Temperature Characteristics

AVG+3 σ AVG AVG-3 σ




Figure 6. Total error versus ambient temperature




Figure 7. Linearity error versus ambient temperature




Figure 8. Symmetry versus ambient temperature




Figure 9. Sensitivity @ I_{PN} = 50 A versus ambient temperature




Figure 10. Sensitivity @ I_{PN} = 100 A versus ambient temperature




Figure 11. Sensitivity @ I_{PN} = 200 A versus ambient temperature

Typical Temperature Characteristics

AVG+3 σ AVG AVG-3 σ




Figure 12. Sensitivity @ I_{PN} = 300 A versus ambient temperature




Figure 13. Sensitivity @ I_{PN} = 400 A versus ambient temperature




Figure 14. Sensitivity @ I_{PN} = 500 A versus ambient temperature




Figure 15. Sensitivity @ I_{PN} = 600 A versus ambient temperature




Figure 16. Hysteresis versus ambient temperature

4. Parameters Definition And Formula

1) Output Voltage

$$V_{OUT} = V_{OE} + S \times I_P$$

V_{OUT} stands for current sensor output voltage at given primary current, V_{OE} stands for offset error, S stands for sensitivity, I_P stands for primary current.

2) Accuracy

$$X_G = \underset{I_P \in [-I_{PN}, I_{PN}]}{\text{MAX}} \left(\frac{V_{OUT} - (S \times I_P)}{S \times I_{PN}} \times 100\% \right)$$

I_{PN} stands for nominal primary current.

3) Sensitivity

$$S = \frac{V_{OUT}(@I_{PN}) - V_{OUT}(@-I_{PN})}{2 \times I_{PN}}$$

$V_{OUT}(@I_{PN})$ and $V_{OUT}(@-I_{PN})$ stand for the voltage output at I_{PN} and $-I_{PN}$ respectively.

4) Linearity

$$\varepsilon_L = \underset{I_P \in [-I_{PN}, I_{PN}]}{\text{MAX}} \left(\frac{V_{OUT} - (\bar{V}_{OE} + \bar{S} \times I_P)}{S \times I_{PN}} \times 100\% \right)$$

\bar{S} and \bar{V}_{OE} stand for the average values of the sensitivity and offset error.

5) Symmetry

$$\varepsilon_{SYM} = \left| \frac{V_{OUT}(@I_{PN}) - \bar{V}_{OE}}{V_{OUT}(@-I_{PN}) - \bar{V}_{OE}} \right| \times 100\%$$

6) Hysteresis

$$V_{OH} = \text{MAX } \Delta H$$

ΔH is the maximum residual voltage between full scale positive and negative nominal current.

5. Application Information




Figure 17. Connection diagram of TMR7506

Mounting Recommendation

1. Mounting method: 3 × Φ 4.5 mm holes (pick one)
 1 × M4 copper or SS304 screw (recommended applied torque 0.75 N•m)
2. Primary through-hole dimensions: 20 mm × 15 mm
3. Secondary terminal: Molex 22041041
 Crimp Housing: Molex 22011042, Crimping Terminal: Molex 08500113

Remarks

1. V_{OUT} is positive when the primary current is in the same direction as the arrow indication on the label and vice versa.
2. Improper connection can cause permanent damage of the sensor.
3. Excessive capacitive load may result in distortion of output signals when measuring high frequency primary signal. Please refer to Output Voltage vs Load Capacitance Curve.
4. Dynamic performances (di/dt and response time) are best with a single busbar completely filling the primary hole.
5. Sensor is customizable upon request.

6. Dimensions





Figure 18. Sensor outline (unit: mm, tolerances for unmarked scales ± 1 mm)

Copyright © 2023 by MultiDimension Technology Co., Ltd.

Information furnished herein by MultiDimension Technology Co., Ltd. (hereinafter MDT) is believed to be accurate and reliable. However, MDT disclaims any and all warranties and liabilities of any kind, with respect to any examples, hints or any performance or use of technical data as described herein and/or any information regarding the application of the product, including without limitation warranties of non-infringement of intellectual property rights of any third party. This document neither conveys nor implies any license under patent or other industrial or intellectual property rights. Customer or any third-party must further determine the suitability of the MDT products for its applications to avoid the applications default of customer or third-party. MDT accept no liability in this respect.

MDT does not assume any liabilities of any indirect, incidental, punitive, special or consequential damages (including without limitation of lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory. Notwithstanding any damages that customer might incur for any reason whatsoever, MDT's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the terms and conditions of commercial sale of MDT.

Absolute maximum ratings are the extreme limits the device will withstand without damage to the MDT product. However, the electrical and mechanical characteristics are not guaranteed as the maximum limits (above recommended operating conditions) are approached. MDT disclaims any and all warranties and liabilities of the MDT product will operate at absolute maximum ratings.

Specifications may change without notice.

Please download latest document from our official website www.dowaytech.com/en.

Recycling

The product(s) in this document need to be handed over to a qualified solid waste management services company for recycling in accordance with relevant regulations on waste classification after the end of the product(s) life.



No.2 Guangdong Road, Zhangjiagang Free Trade Zone, Jiangsu, China

Web: www.dowaytech.com/en E-mail: info@dowaytech.com

