



TND322VD

Excellent Power Device Dual buffer driver for general purpose, Dual VEC8

ON Semiconductor®

<http://onsemi.com>

Features

- Dual buffer
- Monolithic structure (High voltage CMOS process adopted)
- Withstand voltage of 25V is assured
- Wide range of operating voltage : 4.5V to 25V
- Peak output current : $I_{O+}/I_{O-}=0.8A/1A$
- Fast switching time (30ns typical at 1000pF load)
- Fully compatible input to TTL / CMOS (V_{IH} =up to 2.6V, at $V_{DD}=4.5$ to 25V)
- Built-in input pull-down resistance

Specifications

Absolute Maximum Ratings at $T_a=25^\circ C$


| Parameter | Symbol | Conditions | Ratings | Unit |
|-----------------------------|-----------|------------|-------------------------|------------|
| Supply Voltage | V_{DD} | | 0 to 25 | V |
| Input Voltage | V_{IN} | | GND-0.3 to $V_{DD}+0.3$ | V |
| Allowable Power Dissipation | P_D max | | 0.2 | W |
| Junction Temperature | T_j | | -55 to +150 | $^\circ C$ |
| Storage Temperature | T_{stg} | | -55 to +150 | $^\circ C$ |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above these Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

Package Dimensions

unit : mm (typ)


7012-006




Product & Package Information

- Package : VEC8
- JEITA, JEDEC : -
- Minimum Packing Quantity : 3,000 pcs./reel

Packing Type : TL



Marking



TND322VD

Recommend Operating Conditions at Ta=25°C

| Parameter | Symbol | Conditions | Ratings | Unit |
|--------------------------|------------------|------------|-------------|------|
| Operating Supply Voltage | V _{DD} | | 4.5 to 25 | V |
| Operating Temperature | T _{opr} | | -40 to +125 | °C |

Electrical Characteristics (AC Characteristics) at Ta=25°C, V_{DD}=18V, V_{IN}=5V


| Parameter | Symbol | Conditions | Ratings | | | Unit |
|--------------------|-----------------|------------|---------|-----|-----|------|
| | | | min | typ | max | |
| Turn-On Rise Time | t _r | CL=1000pF | | 35 | 50 | ns |
| Turn-Off Fall Time | t _f | CL=1000pF | | 30 | 45 | ns |
| Delay Time | t _{D1} | CL=1000pF | | 30 | 45 | ns |
| | t _{D2} | CL=1000pF | | 45 | 60 | ns |

Electrical Characteristics (DC Characteristics) at Ta=25°C, V_{DD}=4.5 to 25V


| Parameter | Symbol | Conditions | Ratings | | | Unit |
|--|--------------------|--|----------------------|-----|------|------|
| | | | min | typ | max | |
| Logic "1" Input Voltage | V _{IH} | | 2.6 | | | V |
| Logic "0" Input Voltage | V _{IL} | | | | 0.8 | V |
| Logic "1" Input Bias Current | I _{IN} +V | IN=V _{DD} =25V | | 40 | 100 | μA |
| Logic "0" Input Bias Current | I _{IN} -V | IN=0V | -1 | | 1 | μA |
| High-level Output Voltage | V _{OH} | I _O =0A | V _{DD} -0.1 | | | V |
| Low-level Output Voltage | V _{OL} | I _O =0A | | | 0.1 | V |
| V _{DD} Supply Current | I _{supp} | V _{DD} =10V, V _{IN} =3V, (both inputs) | | 1.0 | 4.5 | mA |
| | | V _{DD} =10V, V _{IN} =0V, (both inputs) | | | 0.2 | mA |
| Output High Short Circuit Pulsed Current | I _O +V | DD=18V, PW≤10μs, V _{OUT} =0V | | 0.8 | | A |
| Output Low Short Circuit Pulsed Current | I _O -V | DD=18V, PW≤10μs, V _{OUT} =18V | | 1.0 | | A |
| Output On Resistance | ROUT | V _{DD} =18V, I _{load} =10mA, V _{OUT} ="H" | | 11 | 16.5 | Ω |
| | | V _{DD} =18V, I _{load} =10mA, V _{OUT} ="L" | | 6 | 10 | Ω |

TND322VD

Block Diagram











Switching Time Test Circuit





Ordering Information

| Device | Package | Shipping | memo |
|---------------|---------|----------------|---------|
| TND322VD-TL-E | VEC8 | 3,000pcs./reel | Pb Free |

TND322VD



TND322VD




Taping Specification

TND322VD-TL-E


1. Packing Format

| Package Name | Carrier Tape Type | Maximum Number of devices contained (pcs) | | | Packing format | |
|--------------|-------------------|---|-----------|-----------|---|--|
| | | Reel | Inner box | Outer box | Inner BOX (C-1) | Outer BOX (A-7) |
| VEC8 | CPH6 | 3,000 | 15,000 | 90,000 | 5 reels contained Dimensions:mm (external) 183×72×185 | 6 inner boxes contained Dimensions:mm (external) 440×195×210 |




2. Taping configuration

2-1. Carrier tape size (unit:mm)




2-2. Device placement direction




TND322VD

Outline Drawing

TND322VD-TL-E



Land Pattern Example



ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.