



P-Channel Enhancement-Mode Vertical DMOS FETs

Ordering Information

$BV_{DSS} /$ BV_{DGS}	$R_{DS(ON)}$ (max)	$I_{D(ON)}$ (min)	$V_{GS(th)}$ (max)	Order Number / Package		
				TO-39	TO-92	TO-220
-60V	3.5Ω	-1.5A	-2.4V	—	TP0606N3	TP0606N5
-100V	3.5Ω	-1.5A	-2.4V	TP0610N2	TP0610N3	—

* 14 pin side brazed ceramic DIP

** 14-pin plastic DIP

High Reliability Devices

See pages 5-4 and 5-5 for MILITARY STANDARD Process Flows and Ordering Information.

Features

- ☐ Low threshold — -2.4V max
- ☐ High input impedance
- ☐ Low input capacitance — 80pF typical
- ☐ Fast switching speeds
- ☐ Low on resistance
- ☐ Free from secondary breakdown
- ☐ Low input and output leakage
- ☐ Complementary N- and P-channel devices

Applications

- ☐ Logic level interfaces – ideal for TTL and CMOS
- ☐ Solid state relays
- ☐ Battery operated systems
- ☐ Photo voltaic drives
- ☐ Analog switches
- ☐ General purpose line drivers
- ☐ Telecom switches

Absolute Maximum Ratings

Drain-to-Source Voltage	BV_{DSS}
Drain-to-Gate Voltage	BV_{DGS}
Gate-to-Source Voltage	$\pm 20V$
Operating and Storage Temperature	-55°C to +150°C
Soldering Temperature*	300°C


* Distance of 1.6 mm from case for 10 seconds.

Low Threshold DMOS Technology

These low threshold enhancement-mode (normally-off) transistors utilize a vertical DMOS structure and Supertex's well-proven silicon-gate manufacturing process. This combination produces devices with the power handling capabilities of bipolar transistors and with the high input impedance and positive temperature coefficient inherent in MOS devices. Characteristic of all MOS structures, these devices are free from thermal runaway and thermally-induced secondary breakdown.

Supertex's vertical DMOS FETs are ideally suited to a wide range of switching and amplifying applications where very low threshold voltage, high breakdown voltage, high input impedance, low input capacitance, and fast switching speeds are desired.

Package Options



Thermal Characteristics

Package	I_D (continuous)*	I_D (pulsed)	Power Dissipation @ $T_C = 25^\circ\text{C}$	θ_{JC} $^\circ\text{C/W}$	θ_{JA} $^\circ\text{C/W}$	I_{DR}^*	I_{DRM}
TO-39	-1.0A	-4.0A	6W	20.8	125	-1.0A	-4.0A
TO-92	-0.5A	-3.5A	1W	125	170	-0.5A	-3.5A
TO-220	-2.0A	-4.5A	45W	2.7	70	-2.0A	-4.5A

* I_D (continuous) is limited by max rated T_J .


Electrical Characteristics (@ 25°C unless otherwise specified)

Symbol	Parameter		Min	Typ	Max	Unit	Conditions
BV_{DSS}	Drain-to-Source Breakdown Voltage	TP0610	-100			V	$V_{GS} = 0V, I_D = -2.0mA$
		TP0606	-60				
$V_{GS(th)}$	Gate Threshold Voltage		-1.0		-2.4	V	$V_{GS} = V_{DS}, I_D = -1.0mA$
$\Delta V_{GS(th)}$	Change in $V_{GS(th)}$ with Temperature				-5.0	mV/ $^\circ\text{C}$	$V_{GS} = V_{DS}, I_D = -1.0mA$
I_{GSS}	Gate Body Leakage				-100	nA	$V_{GS} = \pm 20V, V_{DS} = 0V$
I_{DSS}	Zero Gate Voltage Drain Current				-10	μA	$V_{GS} = 0V, V_{DS} = \text{Max Rating}$
					-1.0	mA	$V_{GS} = 0V, V_{DS} = 0.8 \text{ Max Rating}$ $T_A = 125^\circ\text{C}$
$I_{D(ON)}$	ON-State Drain Current		-0.4	-0.6		A	$V_{GS} = -5V, V_{DS} = -25V$
			-1.5	-2.5			$V_{GS} = -10V, V_{DS} = -25V$
$R_{DS(ON)}$	Static Drain-to-Source ON-State Resistance			5.0	7.0	Ω	$V_{GS} = -5V, I_D = -250mA$
				3.0	3.5		$V_{GS} = -10V, I_D = -0.75A$
$\Delta R_{DS(ON)}$	Change in $R_{DS(ON)}$ with Temperature				1.7	%/ $^\circ\text{C}$	$V_{GS} = -10V, I_D = -0.75A$
G_{FS}	Forward Transconductance		300	400		mS	$V_{DS} = -25V, I_D = -0.75A$
C_{ISS}	Input Capacitance			80	150	pF	$V_{GS} = 0V, V_{DS} = -25V$ $f = 1 \text{ MHz}$
C_{OSS}	Common Source Output Capacitance			50	85		
C_{RSS}	Reverse Transfer Capacitance			15	35		
$t_{d(ON)}$	Turn-ON Delay Time				10	ns	$V_{DD} = -25V$ $I_D = -1.0A$ $R_{GEN} = 25\Omega$
t_r	Rise Time				15		
$t_{d(OFF)}$	Turn-OFF Delay Time				20		
t_f	Fall Time				15		
V_{SD}	Diode Forward Voltage Drop				-1.8	V	$V_{GS} = 0V, I_{SD} = -1.0A$
t_{rr}	Reverse Recovery Time			300		ns	$V_{GS} = 0V, I_{SD} = -1.0A$

Notes:


1. All D.C. parameters 100% tested at 25°C unless otherwise stated. (Pulse test: 300 μs pulse, 2% duty cycle.)
2. All A.C. parameters sample tested.

Switching Waveforms and Test Circuit




Typical Performance Curves


Output Characteristics




Saturation Characteristics




Transconductance vs. Drain Current




Power Dissipation vs. Case Temperature



Maximum Rated Safe Operating Area




Thermal Response Characteristics




Typical Performance Curves


BV_{DSS} Variation with Temperature




On-Resistance vs. Drain Current




Transfer Characteristics



V_(th) and R_{DS} Variation with Temperature



Capacitance vs. Drain-to-Source Voltage



Gate Drive Dynamic Characteristics

