


Applications:

Cooper Crouse-Hinds nonmetallic switch and outlet boxes are used:

- In branch circuit wiring as a splice point
- To mount wiring devices such as switches and receptacles
- To provide mechanical protection for wiring systems and electrical devices

Features:

- · Available for use with wood or metal studs to meet any construction preference
- · Quick entry feature on all nonmetallic boxes offers labor savings - no need to break out knockouts - simply push the nonmetallic cable into the box. No tools are required. No need to remove knockouts.
- · Unique configuration of this quick entry feature on single gang boxes provides a self-feeding feature that eliminates the need to reach inside the box to pull the wire out.
- Integral labor saving clamping feature on two, three & four gang boxes. The multiple gang box unique entry also serves as a clamp, eliminating the need to mechanically secure the cable inside the box. There are no separate clamps or screws to install or tighten. Each entry into the multiple gang boxes has the quick entry feature allowing the installer to simply push the cable into the box without the need for tools or removal of knock-outs, so the cable can be inserted where it is required.



Certifications and Compliances:

- UL Listed File No. E102328
- Classified for use in fire rated (2 HR) wall or ceiling. Fire Rating No. R9933.

Standard Materials:

TP2000

• PVC-Polyvinyl Chloride compound

SWITCH BOXES - ANGLED NAILS **UL LISTED**



TP1600



TP1800





TP2300

Cat. #	Bracket or Nails	Capacity Cu. In.	н	w	D	Unit Qty.	Wt. Lbs. Per 100
TP1600	Nails	16.0	33/4"	21/4"	21/2"	100	21
TP1800	Nails	18.0	33/4"	21/4"	23/4"	100	23
TP1802	Speed-Mount & Nails	18.0	311/16"	21/4"	23/4"	100	20
TP2000	Nails	20.3	33/4"	21/4"	33/16"	100	25
TP2002	Speed-Mount & Nails	20.3	311/16"	21/4"	31/8"	100	21
TP2300	Nails	22.5	33/4"	21/4"	37/16"	50	27
TP2302	Speed-Mount & Nails	22.5	311/16"	21/4"	37/16"	50	23

SWITCH BOXES - INTEGRAL CLAMPS **UL LISTED**







TP	1690
(Old	Work)

TP2020 (For Wood or Metal Studs)

TP2030 (For Wood or Metal Studs)

Cat. #	Bracket or Nails	Capacity Cu. In.	н	w	D	Unit Qty.	Wt. Lbs. Per 100
TP1832	Speed-Mount & Bracket	18.0	3 ¹¹ / ₁₆ "	2 ¹ / ₄ "	2 ³ / ₄ "	100	18
TP1690		16.0	3 ⁵ / ₈ "	2 ⁵ / ₁₆ "	2 ³ / ₄ "	50	20
TP2020	Swing Clips & Integral Clamps Side Bracket (5/8" offset)	20.3	3% 311/ ₁₆ "	2 ⁹ / ₁₆ 2 ¹ / ₄ "	2% 33/ ₁₆ "	50 50	24
TP2030	Face Bracket (1/2" offset)	20.3	3 ¹¹ / ₁₆ "	2 ¹ / ₄ "	3 ³ / ₁₆ "	50	24
TP2332	Speed-Mount & Bracket	22.5	3 ¹¹ / ₁₆ "	2 ¹ / ₄ "	3 ⁷ / ₁₆ "	50	23