

# TPIC5421L H-BRIDGE GATE-PROTECTED LOGIC-LEVEL POWER DMOS ARRAY



SLIS027A – OCTOBER 1994 – REVISED OCTOBER 1995

- Low  $r_{DS(on)}$  . . . 0.4  $\Omega$  Typ
- Voltage Output . . . 60 V
- Input Protection Circuitry . . . 18 V
- Pulsed Current . . . 3 A Per Channel
- Extended ESD Capability . . . 4000 V
- Direct Logic-Level Interface

## description


The TPIC5421L is a monolithic gate-protected logic-level power DMOS array that consists of four electrically isolated N-channel enhancement-mode DMOS transistors, two of which are configured with common source. Each transistor features integrated high-current zener diodes ( $Z_{CXa}$  and  $Z_{CXb}$ ) to prevent gate damage in the event that an overstress condition occurs. These zener diodes also provide up to 4000 V of ESD protection when tested using the human-body model of a 100-pF capacitor in series with a 1.5-k $\Omega$  resistor.

The TPIC5421L is offered in a 20-pin wide-body surface-mount (DW) package and a 16-pin thermally-enhanced dual-in-line (NE) package and is characterized for operation over the case temperature of  $-40^{\circ}\text{C}$  to  $125^{\circ}\text{C}$ .



NC – No internal connection

## schematic



NOTE A: For correct operation, no terminal may be taken below GND.  
Pin numbers shown are for the DW package.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.



Copyright © 1995, Texas Instruments Incorporated



# TPIC5421L

## H-BRIDGE GATE-PROTECTED LOGIC-LEVEL POWER DMOS ARRAY

SLIS027A – OCTOBER 1994 – REVISED OCTOBER 1995

### electrical characteristics, $T_C = 25^\circ\text{C}$ (unless otherwise noted)

PARAMETER		TEST CONDITIONS		MIN	TYP	MAX	UNIT
$V_{(BR)DSX}$	Drain-to-source breakdown voltage	$I_D = 250\ \mu\text{A}$ ,	$V_{GS} = 0$	60			V
$V_{GS(th)}$	Gate-to-source threshold voltage	$I_D = 1\ \text{mA}$ , See Figure 5	$V_{DS} = V_{GS}$ ,	1.5	1.85	2.2	V
$V_{(BR)GS}$	Gate-to-source breakdown voltage	$I_{GS} = 250\ \mu\text{A}$		18			V
$V_{(BR)SG}$	Source-to-gate breakdown voltage	$I_{SG} = 250\ \mu\text{A}$		9			V
$V_{(BR)}$	Reverse drain-to-GND breakdown voltage (across D1, D2)	Drain-to-GND current = $250\ \mu\text{A}$		100			V
$V_{DS(on)}$	Drain-to-source on-state voltage	$I_D = 1\ \text{A}$ , See Notes 2 and 3	$V_{GS} = 5\ \text{V}$ ,		0.4	0.475	V
$V_{F(SD)}$	Forward on-state voltage, source-to-drain	$I_S = 1\ \text{A}$ , $V_{GS} = 0$ (Z1, Z2, Z3, Z4), See Notes 2 and 3 and Figure 12			0.9	1.1	V
$V_F$	Forward on-state voltage, GND-to-drain	$I_D = 1\ \text{A}$ (D1, D2), See Notes 2 and 3			4.6		V
$I_{DSS}$	Zero-gate-voltage drain current	$V_{DS} = 48\ \text{V}$ , $V_{GS} = 0$	$T_C = 25^\circ\text{C}$	0.05	1		$\mu\text{A}$
			$T_C = 125^\circ\text{C}$	0.5	10		
$I_{GSSF}$	Forward-gate current, drain short circuited to source	$V_{GS} = 15\ \text{V}$ ,	$V_{DS} = 0$		20	200	nA
$I_{GSSR}$	Reverse-gate current, drain short circuited to source	$V_{SG} = 5\ \text{V}$ ,	$V_{DS} = 0$		10	100	nA
$I_{lkg}$	Leakage current, drain-to-GND	$V_{DGND} = 48\ \text{V}$	$T_C = 25^\circ\text{C}$	0.05	1		$\mu\text{A}$
			$T_C = 125^\circ\text{C}$	0.5	10		
$r_{DS(on)}$	Static drain-to-source on-state resistance	$V_{GS} = 5\ \text{V}$ , $I_D = 1\ \text{A}$ , See Notes 2 and 3 and Figures 6 and 7	$T_C = 25^\circ\text{C}$	0.4	0.475		$\Omega$
			$T_C = 125^\circ\text{C}$	0.65	0.68		
$g_{fs}$	Forward transconductance	$V_{DS} = 15\ \text{V}$ , See Notes 2 and 3 and Figure 9	$I_D = 0.5\ \text{A}$ ,	1.25	1.4		S
$C_{iss}$	Short-circuit input capacitance, common source	$V_{DS} = 25\ \text{V}$ , $f = 1\ \text{MHz}$ ,	$V_{GS} = 0$ , See Figure 11		220	275	pF
$C_{oss}$	Short-circuit output capacitance, common source				120	150	
$C_{rss}$	Short-circuit reverse-transfer capacitance, common source				100	125	

NOTES: 2. Technique should limit  $T_J - T_C$  to  $10^\circ\text{C}$  maximum.

3. These parameters are measured with voltage-sensing contacts separate from the current-carrying contacts.

### source-to-drain and GND-to-drain diode characteristics, $T_C = 25^\circ\text{C}$

PARAMETER		TEST CONDITIONS		MIN	TYP	MAX	UNIT
$t_{rr}$	Reverse-recovery time	$I_S = 0.5\ \text{A}$ , $V_{GS} = 0$ , See Figures 1 and 14	$V_{DS} = 48\ \text{V}$ , $di/dt = 100\ \text{A}/\mu\text{s}$ ,	Z1 and Z3	55		ns
				Z2 and Z4	150		
				D1 and D2	200		
$Q_{RR}$	Total diode charge			Z1 and Z3	0.06		$\mu\text{C}$
				Z2 and Z4	0.3		
				D1 and D2	0.7		



# TPIC5421L

## H-BRIDGE GATE-PROTECTED LOGIC-LEVEL POWER DMOS ARRAY

SLIS027A – OCTOBER 1994 – REVISED OCTOBER 1995

### resistive-load switching characteristics, $T_C = 25^\circ\text{C}$

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
$t_{d(on)}$	Turn-on delay time	$V_{DD} = 25\text{ V},$ $R_L = 25\ \Omega,$ $t_{r1} = 10\text{ ns},$ See Figure 2		25	50	ns
$t_{d(off)}$	Turn-off delay time			20	40	
$t_{r2}$	Rise time			21	42	
$t_{f2}$	Fall time			9	18	
$Q_g$	Total gate charge	$V_{DS} = 48\text{ V},$ $I_D = 0.5\text{ A},$ $V_{GS} = 5\text{ V},$ See Figure 3		3.9	5	nC
$Q_{gs(th)}$	Threshold gate-to-source charge			0.55	0.8	
$Q_{gd}$	Gate-to-drain charge			2.5	3.6	
$L_D$	Internal drain inductance			5		nH
$L_S$	Internal source inductance			5		
$R_g$	Internal gate resistance			0.25		$\Omega$


### thermal resistance

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
$R_{\theta JA}$	Junction-to-ambient thermal resistance	DW package		90		$^\circ\text{C/W}$
		NE package	See Notes 4 and 6	60		
$R_{\theta JB}$	Junction-to-board thermal resistance	DW package	See Notes 4 and 6	53		
$R_{\theta JP}$	Junction-to-pin thermal resistance	DW package	See Notes 5 and 6	30		
		NE package		25		

- NOTES:
- Package mounted on an FR4 printed-circuit board with no heatsink.
  - Package mounted in intimate contact with infinite heatsink.
  - All outputs with equal power




**PARAMETER MEASUREMENT INFORMATION**



†  $I_{RM(REC)}$  = maximum recovery current  
 ‡ The above waveform is representative of Z2, Z4, D1, and D2 in shape only.

**Figure 1. Reverse-Recovery-Current Waveforms of Source-to-Drain Diode**



**TEST CIRCUIT**

NOTE A:  $C_L$  includes probe and jig capacitance.

**Figure 2. Resistive-Switching Test Circuit and Voltage Waveforms**

# TPIC5421L H-BRIDGE GATE-PROTECTED LOGIC-LEVEL POWER DMOS ARRAY

SLIS027A – OCTOBER 1994 – REVISED OCTOBER 1995

## PARAMETER MEASUREMENT INFORMATION





Figure 3. Gate-Charge Test Circuit and Waveform




- NOTES: A. The pulse generator has the following characteristics:  $t_r \leq 10$  ns,  $t_f \leq 10$  ns,  $Z_O = 50 \Omega$ .  
B. Input pulse duration ( $t_w$ ) is increased until peak current  $I_{AS} = 3$  A.

$$\text{Energy test level is defined as } E_{AS} = \frac{I_{AS} \times V_{(BR)DSX} \times t_{av}}{2} = 180 \text{ mJ,}$$


where  $t_{av}$  = avalanche time

Figure 4. Single-Pulse Avalanche-Energy Test Circuit and Waveforms


**TYPICAL CHARACTERISTICS**




**Figure 5**



**Figure 6**



**Figure 7**



**Figure 8**

# TPIC5421L H-BRIDGE GATE-PROTECTED LOGIC-LEVEL POWER DMOS ARRAY

SLIS027A – OCTOBER 1994 – REVISED OCTOBER 1995

## TYPICAL CHARACTERISTICS




Figure 9




Figure 10




Figure 11





Figure 12




**TYPICAL CHARACTERISTICS**

**DRAIN-TO-SOURCE VOLTAGE AND  
 GATE-TO-SOURCE VOLTAGE  
 vs  
 GATE CHARGE**



**Figure 13**

**REVERSE-RECOVERY TIME  
 vs  
 REVERSE  $di/dt$**




**Figure 14**

**TPIC5421L**  
**H-BRIDGE GATE-PROTECTED LOGIC-LEVEL**  
**POWER DMOS ARRAY**

SLIS027A – OCTOBER 1994 – REVISED OCTOBER 1995

**THERMAL INFORMATION**


**MAXIMUM DRAIN CURRENT**  
**vs**  
**DRAIN-TO-SOURCE VOLTAGE**



† Less than 2% duty cycle

**Figure 15**


**MAXIMUM PEAK AVALANCHE CURRENT**  
**vs**  
**TIME DURATION OF AVALANCHE**



**Figure 16**

**THERMAL INFORMATION**

**NE PACKAGE†**  
**NORMALIZED JUNCTION-TO-AMBIENT THERMAL RESISTANCE**  
**VS**  
**PULSE DURATION**



† Device mounted on FR4 printed-circuit board with no heatsink.

NOTES A:  $Z_{\theta JA}(t) = r(t) R_{\theta JA}$   
 $t_w$  = pulse duration  
 $t_c$  = cycle time  
 $d$  = duty cycle =  $t_w/t_c$


**Figure 17**

**TPIC5421L**  
**H-BRIDGE GATE-PROTECTED LOGIC-LEVEL**  
**POWER DMOS ARRAY**

SLIS027A – OCTOBER 1994 – REVISED OCTOBER 1995

**THERMAL INFORMATION**

**DW PACKAGE†**  
**JUNCTION-TO-BOARD THERMAL RESISTANCE**  
**VS**  
**PULSE DURATION**



† Device mounted on a 24 in<sup>2</sup>, 4-layer FR4 printed-circuit board with no heatsink.

- NOTES A:  $Z_{\theta JB}(t) = r(t) R_{\theta JB}$   
 $t_w$  = pulse duration  
 $t_c$  = cycle time  
 $d$  = duty cycle =  $t_w/t_c$

**Figure 18**

**PACKAGING INFORMATION**

Orderable Device	Status <sup>(1)</sup>	Package Type	Package Drawing	Pins	Package Qty	Eco Plan <sup>(2)</sup>	Lead/Ball Finish	MSL Peak Temp <sup>(3)</sup>
TPIC5421LDW	OBSOLETE	SOIC	DW	20		TBD	Call TI	Call TI
TPIC5421LNE	OBSOLETE	PDIP	NE	16		TBD	Call TI	Call TI

<sup>(1)</sup> The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

<sup>(2)</sup> Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS) or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

**TBD:** The Pb-Free/Green conversion plan has not been defined.

**Pb-Free (RoHS):** TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

**Green (RoHS & no Sb/Br):** TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

<sup>(3)</sup> MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.


**Important Information and Disclaimer:**The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

NE (R-PDIP-T\*\*)

PLASTIC DUAL-IN-LINE PACKAGE

20 PIN SHOWN



- NOTES: A. All linear dimensions are in inches (millimeters).  
 B. This drawing is subject to change without notice.  
 C. Falls within JEDEC MS-001 (16 pin only)

DW (R-PDSO-G20)

PLASTIC SMALL OUTLINE



- NOTES:
- All linear dimensions are in inches (millimeters). Dimensioning and tolerancing per ASME Y14.5M-1994.
  - This drawing is subject to change without notice.
  - Body dimensions do not include mold flash or protrusion not to exceed 0.006 (0,15).
  - Falls within JEDEC MS-013 variation AC.

## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

### Products

Audio	<a href="http://www.ti.com/audio">www.ti.com/audio</a>
Amplifiers	<a href="http://amplifier.ti.com">amplifier.ti.com</a>
Data Converters	<a href="http://dataconverter.ti.com">dataconverter.ti.com</a>
DLP® Products	<a href="http://www.dlp.com">www.dlp.com</a>
DSP	<a href="http://dsp.ti.com">dsp.ti.com</a>
Clocks and Timers	<a href="http://www.ti.com/clocks">www.ti.com/clocks</a>
Interface	<a href="http://interface.ti.com">interface.ti.com</a>
Logic	<a href="http://logic.ti.com">logic.ti.com</a>
Power Mgmt	<a href="http://power.ti.com">power.ti.com</a>
Microcontrollers	<a href="http://microcontroller.ti.com">microcontroller.ti.com</a>
RFID	<a href="http://www.ti-rfid.com">www.ti-rfid.com</a>
RF/IF and ZigBee® Solutions	<a href="http://www.ti.com/lprf">www.ti.com/lprf</a>

### Applications

Communications and Telecom	<a href="http://www.ti.com/communications">www.ti.com/communications</a>
Computers and Peripherals	<a href="http://www.ti.com/computers">www.ti.com/computers</a>
Consumer Electronics	<a href="http://www.ti.com/consumer-apps">www.ti.com/consumer-apps</a>
Energy and Lighting	<a href="http://www.ti.com/energy">www.ti.com/energy</a>
Industrial	<a href="http://www.ti.com/industrial">www.ti.com/industrial</a>
Medical	<a href="http://www.ti.com/medical">www.ti.com/medical</a>
Security	<a href="http://www.ti.com/security">www.ti.com/security</a>
Space, Avionics and Defense	<a href="http://www.ti.com/space-avionics-defense">www.ti.com/space-avionics-defense</a>
Transportation and Automotive	<a href="http://www.ti.com/automotive">www.ti.com/automotive</a>
Video and Imaging	<a href="http://www.ti.com/video">www.ti.com/video</a>
Wireless	<a href="http://www.ti.com/wireless-apps">www.ti.com/wireless-apps</a>

TI E2E Community Home Page

[e2e.ti.com](http://e2e.ti.com)

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2011, Texas Instruments Incorporated