


SOP-8

DIP-8

Pin Definition:

- | | |
|----------------|----------------|
| 1. Output A | 8. Vcc |
| 2. Input A (-) | 7. Output B |
| 3. Input A (+) | 6. Input B (-) |
| 4. Ground | 5. Input B (+) |

General Description

The TS4558 is dual general purpose operational amplifier, and provide the high common-mode input voltage range and the absence of latch-up make these amplifiers ideal for voltage follower application.

The devices are short circuit protected and the internal frequency compensation ensures stability without external components. The TS4558 is offered in 8 pin SOP-8 and DIP-8 package.

Features

- Short circuit protection
- Wide common-mode and differential ranges
- No frequency compensation required
- Low power consumption
- No latch-up
- 3MHz unity gain bandwidth guaranteed
- Gain and phase match between amplifiers


Applications

- DVD player
- Audio application


Ordering Information

Part No.	Package	Packing
TS4558CD C3	DIP-8	50pcs / Tube
TS4558CS RL	SOP-8	2.5Kpcs / 13" Reel

Block Diagram



Schematic (each amplifier)



Absolute Maximum Rating

Parameter	Symbol	Value	Unit
Supply Voltage	V _{CC} +	18	V
Supply Voltage	V _{CC} -	-18	V
Differential Input Voltage	V _{IDR}	±30	V
Input Voltage	V _{in}	30	V
Package Thermal Impedance	DIP-8	θ _{ja}	°C/W
	SOP-8		
Operating Junction Temperature Range	T _J	0 ~ +70	°C
Storage Temperature Range	T _{STG}	-65 ~ +150	°C
Lead Temperature 1.6mm(1/16") from case for 10Sec.	T _{LEAD}	260	°C

Note: Maximum ratings are those values beyond which damage to the device may occur, and functional operation should be restricted to the recommended operating condition.

Recommended Operating Conditions

Parameter	Symbol	Value	Unit
Supply Voltage	V _{CC} +	15	V
Supply Voltage	V _{CC} -	-15	V

Electrical Specifications (V_{CC} = ±15V, T_a = 25°C; unless otherwise noted)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Input Offset Current	I _{io}		--	20	±200	nA
Input Bias Current	I _{ib}		--	150	500	nA
Input Resistance	R _i		0.3	5	--	MΩ
Unity Gain Bandwidth	B ₁		--	3	--	MHz
Large-Signal Voltage Gain	A _v	R _L ≥ 2kΩ, V _c = ±10V	20	300	--	V/mV
Output Voltage Swing	V _{om}	R _L ≥ 10kΩ	±12	±14	--	V
		R _L ≥ 2kΩ	±10	±14	--	
Input Common-Mode Voltage Range	V _{icr}		±12	±13	--	V
Common-Mode Rejection Ratio	CMRR	R _s ≤ 10kΩ	70	90	--	dB
Supply Voltage Rejection Ratio	PSRR	R _s ≤ 10kΩ	--	30	150	uV/V
Slew Rate	SR	R _L = 2kΩ, V _{in} = 10V, L = 100pF	0.8	1.6	--	V/uS
Supply Current	I ₊ , I ₋		--	2.5	5.6	mA
Power Consumption	P _c	R _L = ∞	--	75	170	mV
Input Noise Voltage	V _n	R _s = 1kΩ, f = 30Hz~30KHz	--	--	3.5	uVrms
Source Current	I _{source}		-20	--	--	mA
Sink Current	I _{sink}		20	--	--	mA

Note : All characteristics are measured under open-loop conditions with zero common-mode input voltage, unless otherwise specified.

Electrical Characteristics Curve




Figure 1. Burst Noise vs. Source Resistance




Figure 2. RMS Noise vs. Source Resistance




Figure 3. Output Noise vs. Source Resistance





Figure 4. Spectral Noise Density



Unlike conventional peak reading or RMS meters, this system was especially designed to provide the quick response time essential to burst (popcorn) noise testing.

The test time employed is 10 sec and the 20 μ V peak limit refers to the operational amplifier input thus eliminating errors in the closed loop gain factor of the operational amplifier.

Figure 5. Burst Noise Test Circuit

Electrical Characteristics Curve




Figure 6. Open Loop Frequency Response




Figure 7. Phase Margin vs. Frequency




Figure 8. Positive Vout Swing vs. Load Resistance





Figure 9. Negative Vout Swing vs. Load Resistance



**Figure 10. Power Bandwidth
(Large Signal Swing vs. Frequency)**








Figure 11. Transient Response Test Circuit

SOP-8 Mechanical Drawing



SOP-8 DIMENSION				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX.
A	4.80	5.00	0.189	0.196
B	3.80	4.00	0.150	0.157
C	1.35	1.75	0.054	0.068
D	0.35	0.49	0.014	0.019
F	0.40	1.25	0.016	0.049
G	1.27BSC		0.05BSC	
K	0.10	0.25	0.004	0.009
M	0°	7°	0°	7°
P	5.80	6.20	0.229	0.244
R	0.25	0.50	0.010	0.019

DIP-8 Mechanical Drawing



DIM	DIP-8 DIMENSION			
	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	9.07	9.32	0.357	0.367
B	6.22	6.48	0.245	0.255
C	3.18	4.45	0.125	0.135
D	0.35	0.55	0.019	0.020
G	2.54 (typ)		0.10 (typ)	
J	0.29	0.31	0.011	0.012
K	3.25	3.35	0.128	0.132
L	7.75	8.00	0.305	0.315
M	-	10°	-	10°

TS4558

Dual General Purpose Operational Amplifier

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.