

TSF80R1K3S1



800V 4A N-Channel SJ-MOSFET

General Description

Truesemi SJ-FET is new generation of high voltage MOSFET family that is utilizing an advanced charge balance mechanism for outstanding low on-resistance and lower gate charge performance.

This advanced technology has been tailored to minimize conduction loss, provide superior switching performance, and withstand extreme dv/dt rate and higher avalanche energy.

SJ-FET is suitable for various AC/DC power conversion in switching mode operation for higher efficiency.



Features

- 850V @ $T_J = 150\text{ }^{\circ}\text{C}$
- Typ. RDS(on) = 1.1Ω
- Ultra Low gate charge (typ. Qg = 15nC)
- 100% avalanche tested

Absolute Maximum Ratings

Symbol	Parameter	Value	Unit
V _{DSS}	Drain-Source Voltage	800	V
I _D	Drain Current -Continuous (TC = 25°C) -Continuous (TC = 100°C)	4* 2.5*	A
I _{DM}	Drain Current – Pulsed (Note 1)	11*	A
V _{GSS}	Gate-Source voltage	±30	V
E _{AS}	Single Pulsed Avalanche Energy (Note 2)	46	mJ
I _{AR}	Avalanche Current (Note 1)	1	A
E _{AR}	Repetitive Avalanche Energy (Note 1)	0.2	mJ
dv/dt	Peak Diode Recovery dv/dt (Note 3)	15	V/ns
P _D	Power Dissipation (TC = 25°C) -Derate above 25°C	26 0.3	W W/°C
T _J , T _{STG}	Operating and Storage Temperature Range	-55 to +150	°C
T _L	Maximum Lead Temperature for Soldering Purpose, 1/8" from Case for 5 Seconds	300	°C

* Drain current limited by maximum junction temperature.

Thermal Characteristics

Symbol	Parameter	Value	Unit
R _{θJC}	Thermal Resistance, Junction-to-Case	4.9	°C/W
R _{θCS}	Thermal Resistance, Case-to-Sink Typ.	--	°C/W
R _{θJA}	Thermal Resistance, Junction-to-Ambient	80	°C/W

Electrical Characteristics TC = 25°C unless otherwise noted

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Off Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = 250µA, T _J = 25°C	800	--	--	V
		V _{GS} = 0V, I _D = 250µA, T _J = 150°C	--	850	--	V
ΔBV _{DSS} / ΔT _J	Breakdown Voltage Temperature Coefficient	I _D = 250µA, Referenced to 25°C	--	0.6	--	V/°C
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 800V, V _{GS} = 0V T _C = 25°C	--	--	1	µA
		V _{DS} = 640V, V _{GS} = 0V T _C = 150°C	--	10	--	µA
I _{GSSF}	Gate-Body Leakage Current, Forward	V _{GS} = 30V, V _{DS} = 0V	--	--	100	nA
I _{GSSR}	Gate-Body Leakage Current, Reverse	V _{GS} = -30V, V _{DS} = 0V	--	--	-100	nA
On Characteristics						
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 250µA	2.5	--	4.5	V
R _{DS(on)}	Static Drain-Source On-Resistance	V _{GS} = 10V, I _D = 2A	--	1.1	1.3	Ω
g _{FS}	Forward Trans conductance	V _{DS} = 40V, I _D = 2A (Note 4)	--	8	--	S
R _g	Gate resistance	f=1MHz,open drain	--	3.5	--	Ω
Dynamic Characteristics						
C _{iss}	Input Capacitance	V _{DS} = 25V, V _{GS} = 0V, f = 1.0MHz	--	320	--	pF
C _{oss}	Output Capacitance		--	75	--	pF
C _{rss}	Reverse Transfer Capacitance		--	5	--	pF
Switching Characteristics						
t _{d(on)}	Turn-On Delay Time	V _{DD} = 400V, I _D = 2A R _G = 20Ω (Note 4, 5)	--	10	--	ns
t _r	Turn-On Rise Time		--	8	--	ns
t _{d(off)}	Turn-Off Delay Time		--	60	--	ns
t _f	Turn-Off Fall Time		--	13	--	ns
Q _g	Total Gate Charge	V _{DS} = 480V, I _D = 2A V _{GS} = 10V (Note 4, 5)	--	15	--	nC
Q _{gs}	Gate-Source Charge		--	3	--	nC
Q _{gd}	Gate-Drain Charge		--	6	--	nC
Drain-Source Diode Characteristics and Maximum Ratings						
I _s	Maximum Continuous Drain-Source Diode Forward Current	--	--	4	--	A
I _{SM}	Maximum Pulsed Drain-Source Diode Forward Current	--	--	12	--	A
V _{SD}	Drain-Source Diode Forward Voltage	V _{GS} = 0V, I _F = 2A	--	0.9	1.5	V
t _{rr}	Reverse Recovery Time	V _{GS} = 0V, I _F = 2A di _F /dt = 100A/µs (Note 4)	--	180	--	ns
Q _{rr}	Reverse Recovery Charge		--	1.5	--	µC


NOTES:

1. Repetitive Rating: Pulse width limited by maximum junction temperature
2. I_{AS}=1A, V_{DD}=50V, Starting T_J=25 °C
3. I_{SD}≤4A, di/dt ≤ 200A/us, V_{DD} ≤ BV_{DSS}, Starting T_J = 25 °C
4. Pulse Test: Pulse width ≤ 300us, Duty Cycle ≤ 2%
5. Essentially Independent of Operating Temperature Typical Characteristics

Typical Performance Characteristics

1 Power dissipation


$$P_{\text{tot}} = f(T_c)$$



2 Safe operating area

$$I_D = f(V_{DS}); \quad T_c = 25^\circ\text{C}; \quad D = 0$$


parameter: t_p



3 Max. transient thermal impedance

$$Z_{\text{thJC}} = f(t_p)$$


parameter: $D = t_p/T$



4 Typ. output characteristics

$$I_D = f(V_{DS}); \quad T_j = 25^\circ\text{C}; \quad t_p = 10 \mu\text{s}$$


parameter: V_{GS}



Typical Performance Characteristics


5 Typ. output characteristics

$I_D=f(V_{DS})$; $T_j=150\text{ }^\circ\text{C}$; $t_p=10\text{ }\mu\text{s}$
parameter: V_{GS}




6 Typ. drain-source on-state resistance

$R_{DS(on)}=f(I_D)$; $T_j=150\text{ }^\circ\text{C}$
parameter: V_{GS}




7 Drain-source on-state resistance

$R_{DS(on)}=f(T_j)$; $I_D=2.5\text{ A}$; $V_{GS}=10\text{ V}$



8 Typ. transfer characteristics


$I_D=f(V_{GS})$; $|V_{DS}|>2|I_D|R_{DS(on)max}$; $t_p=10\text{ }\mu\text{s}$
parameter: T_j



Typical Performance Characteristics


9 Typ. gate charge

$V_{GS}=f(Q_{gate})$; $I_D=4\text{ A}$ pulsed
parameter: V_{DD}




10 Forward characteristics of reverse diode

$I_F=f(V_{SD})$; $t_p=10\text{ }\mu\text{s}$
parameter: T_j




11 Avalanche energy

$E_{AS}=f(T_j)$; $I_D=0.8\text{ A}$; $V_{DD}=50\text{ V}$



12 Drain-source breakdown voltage


$V_{BR(DSS)}=f(T_j)$; $I_D=0.25\text{ mA}$



Typical Performance Characteristics


13 Typ. capacitances

$C = f(V_{DS})$; $V_{GS} = 0$ V; $f = 1$ MHz



14 Typ. Coss stored energy


$E_{oss} = f(V_{DS})$




Test circuits

Switching times test circuit and waveform for inductive load

Switching times test circuit for inductive load




Switching time waveform




Unclamped inductive load test circuit and waveform

Unclamped inductive load test circuit





Unclamped inductive waveform




Test circuits

Test circuit and waveform for diode characteristics



Package Outline TO-220F



DIM	MILLIMETERS
A	10.16 ± 0.30
A1	7.00 ± 0.20
A2	3.12 ± 0.20
A3	9.70 ± 0.30
B	15.90 ± 0.50
B1	15.60 ± 0.50
B2	4.70 ± 0.30
B3	6.70 ± 0.30
C	3.30 ± 0.25
C1	3.25 ± 0.30
C2	28.70 ± 0.50
D	Typical 2.54
D1	1.47 (MAX)
D2	0.80 ± 0.20
E	2.55 ± 0.25
E1	0.70 ± 0.25
E2	$1.0 \times 45^\circ$
E3	0.50 ± 0.20
E4	2.75 ± 0.30