

SOT-23

Pin Definition:

1. Gate
2. Source
3. Drain

TSM320N03CX

30V N-Channel Power MOSFET

Key Parameter Performance

Parameter		Value	Unit
V_{DS}		30	V
$R_{DS(on)}$ (max)	$V_{GS} = 4.5V$	32	$m\Omega$
	$V_{GS} = 2.5V$	40	
Q_g		8.4	nC


Features

- ✓ Improved dv/dt capability
- ✓ Fast switching

Ordering Information

Part No.	Package	Packing
TSM320N03CX RFG	SOT-23	3kpcs / 70Reel

Note: 60 denotes for Halogen- and Antimony-free as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds

Block Diagram


N-Channel MOSFET

Absolute Maximum Ratings ($T_C = 25^\circ C$ unless otherwise noted)

Parameter		Symbol	Limit	Unit
Drain-Source Voltage		V_{DS}	30	V
Gate-Source Voltage		V_{GS}	± 12	V
Continuous Drain Current	$T_C = 25^\circ C$	I_D	5.3	A
	$T_C = 100^\circ C$		3.4	A
Pulsed Drain Current ^(Note 1)		I_{DM}	21.2	A
Power Dissipation @ $T_C = 25^\circ C$		P_D	1.56	W
Operating Junction Temperature		T_J	150	$^\circ C$
Storage Temperature Range		T_{STG}	-55 to +150	$^\circ C$

Thermal Performance

Parameter	Symbol	Limit	Unit
Thermal Resistance - Junction to Ambient	R_{JA}	80	$^\circ C/W$

Electrical Specifications ($T_C = 25^\circ\text{C}$ unless otherwise noted)

Parameter	Conditions	Symbol	Min	Typ	Max	Unit
Static						
Drain-Source Breakdown Voltage	$V_{GS} = 0V, I_D = 250\mu A$	BV_{DSS}	30	--	--	V
Drain-Source On-State Resistance	$V_{GS} = 4.5V, I_D = 4A$	$R_{DS(ON)}$	--	27	32	m_{Ω}
	$V_{GS} = 2.5V, I_D = 3A$		--	32	40	
Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = 250\mu A$	$V_{GS(TH)}$	0.4	0.6	0.9	V
Zero Gate Voltage Drain Current	$V_{DS} = 30V, V_{GS} = 0V$	I_{DSS}	--	--	1	μA
	$V_{DS} = 24V, T_J = 125^{\circ}C$		--	--	10	
Gate Body Leakage	$V_{GS} = \pm 12V, V_{DS} = 0V$	I_{GSS}	--	--	± 100	nA
Forward Transconductance ^(Note 2)	$V_{DS} = 10V, I_D = 3A$	g_{fs}	--	7	--	S
Dynamic						
Total Gate Charge ^(Note 2,3)	$V_{DS} = 10V, I_D = 4A,$ $V_{GS} = 4.5V$	Q_g	--	8.4	--	nC
Gate-Source Charge ^(Note 2,3)		Q_{gs}	--	1	--	
Gate-Drain Charge ^(Note 2,3)		Q_{gd}	--	2.2	--	
Input Capacitance	$V_{DS} = 10V, V_{GS} = 0V,$ $f = 1.0MHz$	C_{iss}	--	695	--	pF
Output Capacitance		C_{oss}	--	45	--	
Reverse Transfer Capacitance		C_{rss}	--	36	--	
Switching						
Turn-On Delay Time ^(Note 2,3)	$V_{DD} = 10V, I_D = 1A,$ $V_{GS} = 4.5V, R_{GEN} = 25_{\Omega}$	$t_{d(on)}$	--	4.5	--	ns
Turn-On Rise Time ^(Note 2,3)		t_r	--	13	--	
Turn-Off Delay Time ^(Note 2,3)		$t_{d(off)}$	--	27	--	
Turn-Off Fall Time ^(Note 2,3)		t_f	--	8.3	--	
Source-Drain Diode Ratings and Characteristic						
Maximum Continuous Drain-Source Diode Forward Current	Integral reverse diode in the MOSFET	I_S	--	--	5.3	A
Maximum Pulse Drain-Source Diode Forward Current		I_{SM}	--	--	21.2	A
Diode-Source Forward Voltage	$V_{GS} = 0V, I_S = 1A$	V_{SD}	--	--	1	V







Note:

- Pulse width limited by safe operating area
- Pulse test: pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$
- Switching time is essentially independent of operating temperature.


TSM320N03CX

30V N-Channel Power MOSFET

Electrical Characteristics Curves




SOT-23 Mechanical Drawing



Unit: Millimeters

Marking Diagram



- 32** = Device Code
- Y** = Year Code
- M** = Month Code for Halogen Free Product
(**O**=Jan, **P**=Feb, **Q**=Mar, **R**=Apr, **S**=May, **T**=Jun, **U**=Jul, **V**=Aug, **W**=Sep, **X**=Oct, **Y**=Nov, **Z**=Dec)
- L** = Lot Code

TSM320N03CX

30V N-Channel Power MOSFET

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.