


## Trench Schottky Rectifier

### FEATURES

- Patented Trench Schottky technology
- Excellent high temperature stability
- Low forward voltage
- Low power loss/ high efficiency
- High forward surge capability
- Ideal for automated placement
- Moisture sensitivity level: level 1, per J-STD-020
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21 definition


**TO-277A (SMPC)**


### TYPICAL APPLICATIONS

Trench Schottky barrier rectifier are designed for high frequency miniature switched mode power supplies such as adapters, lighting and on-board DC/DC converters.

### MECHANICAL DATA

**Case:** TO-277A (SMPC)

Molding compound meets UL 94 V-0 flammability rating

Packing code with suffix "G" means green compound (halogen-free)

**Terminal:** Matte tin plated leads, solderable per JESD22-B102

Meet JESD 201 class 2 whisker test

**Polarity:** Indicated by cathode band

**Weight:** 0.095g (approximately)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T <sub>A</sub> =25°C unless otherwise noted)							
PARAMETER		SYMBOL	TSP10U100S		TSP10U120S		UNIT
Marking code			10U100		10U120		
Maximum repetitive peak reverse voltage		V <sub>RRM</sub>	100		120		V
Maximum average forward rectified current		I <sub>F(AV)</sub>	10				A
Peak forward surge current, 8.3 ms single half sine-wave superimposed on rated load per diode		I <sub>FSM</sub>	140				A
			TYP	MAX	TYP	MAX	
Maximum instantaneous forward voltage per diode (Note 1)	I <sub>F</sub> = 5A	V <sub>F</sub>	0.51	-	0.56	-	V
	I <sub>F</sub> = 10A		0.60	0.68	0.68	0.78	
	I <sub>F</sub> = 5A		0.42	-	0.49	-	
	I <sub>F</sub> = 10A		0.52	0.60	0.57	0.67	
Maximum instantaneous reverse current per diode at rated reverse voltage	T <sub>J</sub> = 25°C	I <sub>R</sub>	10	150	10	150	μA
	T <sub>J</sub> = 125°C		6	30	6	30	mA
Typical thermal resistance		R <sub>θJL</sub>	11				°C/W
Operating temperature range		T <sub>J</sub>	- 55 to +150				°C
Storage temperature range		T <sub>STG</sub>	- 55 to +150				°C

Note 1: Pulse Test with Pulse Width=300μs, 1% Duty Cycle

**ORDERING INFORMATION**

PART NO.	PACKING CODE	PACKING CODE SUFFIX	PACKAGE	PACKING
TSP10U1xxS (Note 1,2)	S1	G	SMPC	1,500/ 7" Plastic reel
	S2		SMPC	6,000/ 13" Plastic reel

Note 1: "xx" defines voltage from 100V (TSP10U100S) to 120V (TSP10U120S)

Note 2: Whole series with green compound


**EXAMPLE**

PREFERRED PART NO.	PART NO.	PACKING CODE	PACKING CODE SUFFIX	DESCRIPTION
TSP10U100S S1G	TSP10U100S	S1	G	Green compound


**RATINGS AND CHARACTERISTICS CURVES**

( $T_A=25^\circ\text{C}$  unless otherwise noted)


**FIG.1 FORWARD CURRENT DERATING CURVE**




**FIG. 2 TYPICAL FORWARD CHARACTERISTICS**




**FIG. 2 TYPICAL FORWARD CHARACTERISTICS**




**FIG. 3 TYPICAL REVERSE CHARACTERISTICS**



**FIG. 3 TYPICAL REVERSE CHARACTERISTICS**




**FIG. 4 TYPICAL JUNCTION CAPACITANCE**




**PACKAGE OUTLINE DIMENSIONS**

**TO-277A (SMPC)**



DIM.	Unit (mm)		Unit (inch)	
	Min	Max	Min	Max
A	5.650	5.750	0.222	0.226
B	6.350	6.650	0.250	0.262
C	4.550	4.650	0.179	0.183
D	3.540	3.840	0.139	0.151
E	4.235	4.535	0.167	0.179
F	1.850	2.150	0.073	0.085
G	3.170	3.470	0.125	0.137
H	1.043	1.343	0.041	0.053
I	1.000	1.300	0.039	0.051
J	1.930	2.230	0.076	0.088
K	0.175	0.325	0.007	0.013
L	1.000	1.200	0.039	0.047

**SUGGESTED PAD LAYOUT**



Symbol	Unit (mm)	Unit (inch)
A	4.80	0.189
B	4.72	0.186
C	1.40	0.055
D	1.27	0.050
E	6.80	0.268
F	1.04	0.041

**MARKING DIAGRAM**



P/N = Marking Code  
 YW = Date Code  
 F = Factory Code

## Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.