


APPLICATIONS

- It is suitable to fit all modes of control found in applications such as overvoltage crowbar protection, motor control circuits in power tools and kitchen aids, in-rush current limiting circuits, capacitive discharge ignition, voltage regulation circuits etc.
- Minimum Lot-to-Lot variations for robust device performance and reliable operation


ABSOLUTE MAXIMUM RATINGS (T_a=25°C)

SYMBOL	PARAMETER	MIN	UNIT
V _{DRM}	Repetitive peak off-state voltage	800	V
V _{RRM}	Repetitive peak reverse voltage	800	V
I _{T(RMS)}	RMS on-state current	25	A
I _{T(AV)}	Average on-state current	16	A
I _{TSM}	Surge non-repetitive on-state current	314	A
T _j	Operating junction temperature	110	°C
T _{stg}	Storage temperature	-45~150	°C

ELECTRICAL CHARACTERISTICS (T_c=25°C unless otherwise specified)

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
I _H	Holding current	I _T =500mA Gate open		50	mA
I _L	Latching current	I _G -1.2I _{GT}		90	mA
V _{TM}	On-state voltage	I _{TM} = 50A; T _p =380 μs		1.6	V
I _{GT}	Gate-trigger current	V _D = 12 V; I _T = 0.1 A		40	mA
V _{GT}	Gate-trigger voltage	V _D = 12 V; I _T = 0.1 A		1.3	V
I _{RRM}	Repetitive peak reverse current	V _{RRM} = V _{DRM}	T _c =25°C	5	μA
			T _c =125°C	4	mA
I _{DRM}	Repetitive peak off-state current	V _{RRM} = V _{DRM}	T _c =25°C	5	μA
			T _c =125°C	4	mA

Notice:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.

