

U74AUC1G08

CMOS IC

SINGLE 2-INPUT AND GATE


■ DESCRIPTION

The **U74AUC1G08** is a 2-input AND gate which provides the function $Y = A \cdot B$ or $Y = \overline{A} + \overline{B}$ in positive logic.


This device has power-down protective circuit, preventing device destruction when it is powered down.

■ FEATURES

- * Operate from 0.8V to 2.7V
- * Low power dissipation : $I_{CC} = 10\mu A$ (Max.)
- * $\pm 8mA$ Output Driver : $V_{CC} = 1.8V$
- * I_{off} Supports partial-Power-Down Mode Operation



SOT-23-5
(JEDEC TO-236)




SOT-353

■ ORDERING INFORMATION


Ordering Number	Package	Packing
U74AUC1G08G-AE5-R	SOT-23-5	Tape Reel
U74AUC1G08G-AL5-R	SOT-353	Tape Reel

U74AUC1G08G-AE5-R 	(1)Packing Type (2)Package Type (3)Green Package	(1) R: Tape Reel (2) AE5: SOT-23-5, AL5: SOT-353 (3) G: Halogen Free and Lead Free
---------------------------	--	--

■ MARKING





■ PIN CONFIGURATION



■ FUNCTION TABLE (each gate)

INPUT		OUTPUT
A	B	Y
L	L	L
L	H	L
H	L	L
H	H	H

■ LOGIC DIAGRAM (positive logic)



ABSOLUTE MAXIMUM RATING

PARAMETER	SYMBOL	TEST CONDITIONS	RATINGS	UNIT
Supply Voltage	V _{CC}		-0.5 ~ +3.6	V
Input Voltage	V _{IN}		-0.5 ~ +3.6	V
Output Voltage	V _{OUT}	Output in the high or low state	-0.5 ~ V _{CC} +0.5	V
		Output in the power-off state	-0.5 ~ +3.6	V
V _{CC} or GND Current	I _{CC}		±100	mA
Continuous Output Current	I _{OUT}	V _{OUT} =0 ~ V _{CC}	±20	mA
Input Clamp Current	I _{IK}	V _{IN} <0	-50	mA
Output Clamp Current	I _{OK}	V _O >V _{CC} or V _{OUT} <0	-50	mA
Storage Temperature Range	T _{STG}		-65 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ RECOMMENDED OPERATING CONDITIONS

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Supply Voltage	V _{CC}	Operating	0.8		2.7	V
Input Voltage	V _{IN}		0		3.6	V
Output Voltage	V _{OUT}	High or low state	0		V _{CC}	V
Operating Temperature	T _A		-40		85	°C
Input Transition Rise or Fall Rate	Δt/Δv	V _{CC} =0.8V ~ 1.95V			20	ns/V
		V _{CC} =2.3V ~ 2.7V			10	ns/V

■ STATIC CHARACTERISTICS (T_A =25°C , unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
High-level Input Voltage	V _{IH}	V _{CC} =0.8V		V _{CC}		V
		V _{CC} =1.1V ~ 1.95V	0.65×V _{CC}			V
		V _{CC} =2.3V ~2.7V	1.7			V
Low-level Input Voltage	V _{IL}	V _{CC} =0.8V			0	V
		V _{CC} =1.1V ~ 1.95V			0.35×V _{CC}	V
		V _{CC} =2.3V ~2.7V			0.7	V
High-Level Output voltage	V _{OH}	V _{CC} =0.8 ~ 2.7V, I _{OH} =-100μA	V _{CC} -0.1			V
		V _{CC} =0.8V, I _{OH} =-700μA		0.55		V
		V _{CC} =1.1V, I _{OH} =-3mA	0.8			V
		V _{CC} =1.4V I _{OH} =-5mA	1			V
		V _{CC} =1.65V, I _{OH} =-8mA	1.2			V
		V _{CC} =2.3V, I _{OH} =-9mA	1.8			V
Low-Level Output voltage	V _{OL}	V _{CC} =0.8 ~ 2.7V, I _{OL} =100μA			0.2	V
		V _{CC} =0.8V, I _{OL} =700μA		0.25		V
		V _{CC} =1.1V, I _{OL} =3mA			0.3	V
		V _{CC} =1.4V, I _{OL} =5mA			0.4	V
		V _{CC} =1.65V, I _{OL} =8mA			0.45	V
		V _{CC} =2.3V, I _{OL} =9mA			0.6	V
Input Leakage Current	I _{II(LEAK)}	V _{CC} =0 ~ 2.7V, V _{IN} =V _{CC} or GND		±0.1	±5	μA
Power OFF Leakage Current	I _{off}	V _{CC} =0V, V _{IN} or V _{OUT} =2.7V		±0.1	±10	μA
Quiescent Supply Current	I _{CC}	V _{CC} =0.8V to 2.7V, V _{IN} =V _{CC} or GND, I _{OUT} =0		0.1	10	μA
Input Capacitance	C _I	V _{CC} =2.5V, V _{IN} =V _{CC} or GND		3		pF


■ DYNAMIC CHARACTERISTICS ($T_A = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Propagation delay from inputs (A or B) to output(Y)	t_{PLH} / t_{PHL}	$C_L=15\text{pF}, R_L=2\text{K}\Omega$	$V_{CC}=0.8\text{V}$	4.7		ns
			$V_{CC}=1.2\pm0.1\text{V}$	0.9		ns
			$V_{CC}=1.5\pm0.1\text{V}$	0.6		ns
			$V_{CC}=1.8\pm0.15\text{V}$	0.4	1.1	ns
			$V_{CC}=2.5\pm0.2\text{V}$	0.2		ns
		$C_L=30\text{pF}, R_L=1\text{K}\Omega$	$V_{CC}=1.8\pm0.15\text{V}$	0.7	1.4	ns
		$C_L=30\text{pF}, R_L=500\Omega$	$V_{CC}=2.5\pm0.2\text{V}$	0.5		ns

■ OPERATING CHARACTERISTICS ($f=10\text{MHz}, T_A = 25^\circ\text{C}$, unless otherwise specified)


PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Power Dissipation Capacitance	C_{PD}	$V_{CC}=0.8\text{V}$		15		pF
		$V_{CC}=1.2\text{V}$		15		pF
		$V_{CC}=1.5\text{V}$		15		pF
		$V_{CC}=1.8\text{V}$		15		pF
		$V_{CC}=2.5\text{V}$		19		pF

■ TEST CIRCUIT AND WAVEFORMS



TEST CIRCUIT

V_{CC}	C_L	R_L	V_M
0.8V	15pF	2k Ω	$V_{CC}/2$
1.2V±0.1V	15pF	2k Ω	$V_{CC}/2$
1.5V±0.1V	15pF	2k Ω	$V_{CC}/2$
1.8V±0.15V	15pF	2k Ω	$V_{CC}/2$
2.5V±0.2V	15pF	2k Ω	$V_{CC}/2$
1.8V±0.15V	30pF	1k Ω	$V_{CC}/2$
2.5V±0.2V	30pF	500 Ω	$V_{CC}/2$



PROPAGATION DELAY TIMES

Notes: 1. C_L includes probe and jig capacitance.
2. All input pulses are supplied by generators having the following characteristics: PRR ≤10MHz, $Z_O = 50\Omega$.

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.