

SURFACE MOUNT ZENER DIODE

**REVERSE VOLTAGE – 2.4 to 36 Volts
POWER DISSIPATION – 0.4 Watts**


FEATURES

- Planar die construction
- 400mW power dissipation rating
- Ultra-small surface mount package

MECHANICAL DATA

- Case: SOD-323 plastic
- Case Material: "Green" molding compound, UL flammability classification 94V-0, (No Br. Sb. Cl)
- Moisture Sensitivity: Level 1 per J-STD-020D
- Lead Free in RoHS 2002/95/EC Compliant

SOD-323



SOD-323		
Dim.	Min.	Max.
A	0.80	1.00
A1	0.00	0.10
A3	0.15 REF	
b	0.25	0.4
C	0.089	0.177
D	1.60	1.80
E	1.15	1.35
L	0.08	--
HE	2.30	2.70
Dimensions in millimeter		

MAXIMUM RATING @ T_A = 25°C unless otherwise specified

PARAMETER	SYMBOL	VALUE	UNIT
Continuous forward current	I _F	200	mA
Power dissipation (Note 2)	P _D	400	mW
Operating temperature range	T _J	150	°C
Storage temperature range	T _{STG}	-55~+150	°C

THERMAL CHARACTERISTICS @ T_A = 25°C unless otherwise specified

PARAMETER	SYMBOL	VALUE	UNIT
Typical thermal resistance (Note 1, 2)	R _{thJ_S} R _{thJ_A}	130 340	°C/W

DEVICE MARKING @ T_A = 25°C unless otherwise specified

DEVICE P/N	MARKING	PIN DIAGRAM	EQUIVALENT CIRCUIT DIAGRAM
UDZSXVXB	XX=Specific device code (See below table)		

Note:

1. Thermal resistance junction to soldering point and ambient.
2. Device mounted on a printed-circuit board measuring 11 × 25 × 1.6 mm.

ELECTRIAL CHARACTERISTIC (Ta = 25°C)
UDZSXVB Series



Device	Device Marking	Zener Voltage			Operating resistance		Rising operating resistance		Temp. Coeff. Sz(mV/K) @Izt=5mA		Maximum Reverse Current	
		Vz(V)			Zz (Ω)		Zzk (Ω)		Min	Max	IR	VR
		Min	Max	Iz (mA)	Max	Iz (mA)	Max	Iz (mA)			uA	V
UDZS2V4B	22	2.43	2.63	5	100	5	1000	0.5	-3.5	0	100	1
UDZS2V7B	32	2.69	2.91	5	110	5	1000	0.5	-3.5	0	100	1
UDZS3V0B	42	3.01	3.22	5	120	5	1000	0.5	-3.5	0	50	1
UDZS3V3B	52	3.32	3.53	5	120	5	1000	0.5	-3.5	0	20	1
UDZS3V6B	62	3.6	3.845	5	100	5	1000	1	-3.5	0	10	1
UDZS3V9B	72	3.89	4.16	5	100	5	1000	1	-3.5	-2.5	5	1
UDZS4V3B	82	4.17	4.43	5	100	5	1000	1	-3.5	0	5	1
UDZS4V7B	92	4.55	4.75	5	100	5	800	0.5	-3.5	0.2	2	1
UDZS5V1B	A2	4.98	5.2	5	80	5	500	0.5	-2.7	1.2	2	1.5
UDZS5V6B	C2	5.49	5.73	5	60	5	200	0.5	-2	2.5	1	2.5
UDZS6V2B	E2	6.06	6.33	5	60	5	100	0.5	0.4	3.7	1	3
UDZS6V8B	F2	6.65	6.93	5	40	5	60	0.5	1.2	4.5	0.5	3.5
UDZS7V5B	H2	7.28	7.6	5	30	5	60	0.5	2.5	5.3	0.5	4
UDZS8V2B	J2	8.02	8.36	5	30	5	60	0.5	3.2	6.2	0.5	5
UDZS9V1B	L2	8.85	9.23	5	30	5	60	0.5	3.8	7.0	0.5	6
UDZS10B	05	9.77	10.21	5	30	5	60	0.5	4.5	8.0	0.1	7
UDZS11B	15	10.78	11.22	5	30	5	60	0.5	5.4	9.0	0.1	8
UDZS12B	25	11.74	12.24	5	30	5	80	0.5	6.0	10.0	0.1	9
UDZS13B	35	12.91	13.49	5	37	5	80	0.5	7.0	11.0	0.1	10
UDZS15B	45	14.34	14.98	5	42	5	80	0.5	9.2	13.0	0.1	11
UDZS16B	55	15.85	16.51	5	50	5	80	0.5	10.4	14.0	0.1	12
UDZS18B	65	17.56	18.35	5	65	5	80	0.5	12.4	16.0	0.1	13
UDZS20B	75	19.52	20.39	5	85	5	100	0.5	14.4	18.0	0.1	15
UDZS22B	85	21.54	22.47	5	100	5	100	0.5	16.4	20.0	0.1	17
UDZS24B	95	23.72	24.78	5	120	5	120	0.5	18.4	22.0	0.1	19
UDZS27B	A5	26.19	27.53	5	150	5	150	0.5	21.4	25.3	0.1	21
UDZS30B	C5	29.19	30.69	5	200	5	200	0.5	24.4	29.4	0.1	23
UDZS33B	E5	32.15	33.79	5	250	5	250	0.5	27.4	33.4	0.1	25
UDZS36B	F5	35.07	36.87	5	300	5	300	0.5	30.4	37.4	0.1	27

Note:

1. The zener voltage (Vz) is measured 40ms after power is supplied.
2. The operating resistances (Zz, Zzk) are measured by superimposing a minute alternating current on the regulated current (Iz).

REV. 5, Aug.-2016, KSJR21

RATING AND CHARACTERISTIC CURVES (Ta = 25°C)
UDZSXVB Series



FIG.1 ZENER VOLTAGE CHARACTERISTICS




FIG.2 DERATING CURVE





FIG.3 ZENER VOLTAGE TEMP. VS. COEFFICIENT CHARACTERISTICS



Important Notice and Disclaimer

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.