

Pb Free Plating Product

# UF4001 thru UF4007




## 1.0 AMP.ULTRA FAST RECOVERY RECTIFIERS

### Features

- Plastic package has Underwriters Laboratories Flammability Classification 94V-0
- Ideally suited for use in very high frequency switching power supplies, inverters and as free wheeling diodes
- Ultrafast recovery time for high efficiency
- Excellent high temperature switching
- Soft recovery characteristics

### Mechanical Data

- Case: molded plastic, DO-41
- Epoxy: UL 94V-0 rate flame retardant
- Lead: Axial leads, solderable per MIL-STD-202, Method 208 guaranteed
- Polarity: Color band denotes cathode end
- Mounting Position: Any



### Absolute Maximum Ratings and Characteristics

Ratings at 25 °C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate current by 20%.

| Parameter   | Symbols         | UF4001      | UF4002 | UF4003 | UF4004 | UF4005 | UF4006 | UF4007 | Units        |
|---|-----------------|-------------|--------|--------|--------|--------|--------|--------|--------------|
| Maximum Recurrent Peak Reverse Voltage  | $V_{RRM}$       | 50          | 100    | 200    | 400    | 600    | 800    | 1000   | V            |
| Maximum RMS Voltage   | $V_{RMS}$       | 35          | 70     | 140    | 280    | 420    | 560    | 700    | V            |
| Maximum DC Blocking Voltage   | $V_{DC}$        | 50          | 100    | 200    | 400    | 600    | 800    | 1000   | V            |
| Maximum Average Forward Rectified Current 0.375"(9.5mm) Lead Length at $T_A = 55^\circ C$           | $I_{(AV)}$      | 1           |        |        |        |        |        |        | A            |
| Peak Forward Surge Current, 8.3 ms Single Half-sine -wave Superimposed on Rated Load (JEDEC Method) | $I_{FSM}$       | 30          |        |        |        |        |        |        | A            |
| Maximum Forward Voltage at 1 A DC   | $V_F$           | 1           |        |        | 1.7    |        |        | V      |              |
| Maximum Reverse Current at Rated DC Blocking Voltage<br>$T_A = 25^\circ C$<br>$T_A = 100^\circ C$   | $I_R$           | 5<br>500    |        |        |        |        |        |        | $\mu A$      |
| Typical Junction Capacitance <sup>1)</sup>  | $C_J$           | 17          |        |        |        |        |        |        | pF           |
| Typical Thermal Resistance <sup>2)</sup>  | $R_{\theta JA}$ | 60          |        |        |        |        |        |        | $^\circ C/W$ |
| Maximum Reverse Recovery Time <sup>3)</sup>   | $t_{rr}$        | 50          |        |        | 75     |        |        | ns     |              |
| Operating and Storage Temperature Range   | $T_J, T_S$      | -55 to +150 |        |        |        |        |        |        | $^\circ C$   |

<sup>1)</sup> Measured at 1 MHz and applied reverse voltage of 4 V DC.

<sup>2)</sup> Thermal resistance junction to ambient and from junction to lead at 0.375"(9.5mm) lead length P.C.B mounted.

<sup>3)</sup> Reverse recovery test conditions:  $I_F = 0.5 A$ ,  $I_R = 1 A$ ,  $I_{rr} = 0.25 A$ .

