



UL1015 series

600V PVC Hookup Wire



Materials For Industry

Features

- UL1015
- CSA Type TEW
- Passes VW-1 Vertical Wire Flame Test

Applications

Rated 2500V peak for electronic circuits and internal wiring of electronic and electrical equipment.

UL1015 series 600V PVC WIRE					
PART NUMBER	GAUGE	STRANDING	OUTSIDE DIAMETER	STOCK COLORS	SPOOL PUT-UPS/FT
61-1015-24XXX	24	7 x 32	.088	0-9	1000
61-1015-22XXX	22	7 x 30	.093	0-9	1000
61-1015-20XXX	20	10 x 30	.100	0-9	1000
61-1015-18XXX	18	16 X 30	.110	0-9	500
61-1015-16XXX	16	26 X 30	.123	0-9	500
61-1015-14XXX	14	41 X 30	.138	0-9	500
61-1015-12XXX	12	65 X 30	.158	0-9	250
61-1015-10XXX	10	105 X 30	.180	0-9	250
61-1028-8XXX	8	133 x 29	.262	0-9	100
61-1283-6XXX	6	133 x 27	.332	0-9	100

XXX— Standard colors include:

0/BLK, 1/BRN, 2/RED, 3/ORG, 4/YEL, 5/GRN, 6/BLU, 7/VIO, 8/GRY, 9/WHT

Ordering Info: (Type of material) (size) (color)
611015 18 XXX

For striped wire: Add “/” and the striped color, example 611015-24BLK/WHT

Technical Data

Specifications:

Tinned copper conductor
 Polyvinylchloride insulation
 Dielectric Strength 600 V/Mil
 Flammability VW-1
 Temperature range -10°C to +105°C

Source Associates, Inc.
 (408)970-0128 Fax (408)970-9748
 www.source.as e-mail: sales@source.as